F4 Annual Vehicle Inspection

Team:		**Chassis #:**	Chassis: RFID:
Car #:		**Engine #:**	
Driver:		**ECU #:**	
Date/Time:		**Trans S/N #:**	
Inspector:		**ADR S/N:**	
Sticker #:		**Yellow Flag S/N:**	
		Transponder #:	

Checked	Item	Book	Section
	Record chassis, RFID, engine, ECU, gearbox, ADR, yellow light, transponder numbers above		
	Car livery and numbers complete and comply with Style Guide.	F4 Sport	Append 3
	Head restraint unmodified/undamaged	FIA Tech	2.7.1
	Maximum added head restraint rear padding 10mm.	FIA Tech	14.6.2
	Maximum added head restraint side padding 20mm. Low friction surface required.	FIA Tech	14.6.3
	TRS or Sabelt belts per 8853-2016. Lap belt adjusters not allowed per TAMF4-2020-003.	F4 Sport	Append 1
	Extraction seat unmodified, except belt hole sizing for alternate anchor points	F4 Sport	26.3.h
	Extraction seat properly installed. Check extraction belt condition and access.	FIA Tech	14.7
	Extraction seat removal without driver. No tools, no obstructions.	FIA Tech	14.7
	ADR installed and operational. Stephan log ADR number.	F4 Sport	26.4
	ADR dash light working	F4 Sport	26.4
	Yellow light system installed and working	F4 Sport	26.4
	Ballast securely mounted	FIA Tech	4.2
	Fire extinguisher charged	FIA Tech	14.1.3
	Fire extinguisher activation battery OK	FIA Tech	14.1.5
	Fire extinguisher mounts unmodified. Adequate clearance for underfloor mounting bolts.	FIA Tech	2.7.1
	Fire system (E) sticker in place	FIA Tech	14.1.5
	Dash master switch works. Sticker (Lightning bolt) in place.	FIA Tech	14.2.1
	Exterior master switch works. Sticker (Lightning bolt) in place.	FIA Tech	14.2.2
	Rain light working. New version installed.	FIA Tech	14.5
	Transponder fitted and working. Location per Ligier bulletin F4.13.06.27	F4 Sport	26.7
	Lifting strap location at roll hoop unobstructed		
	Camera mounted to Ligier bracket on left side of roll hoop, per Ligier Bulletin F4.13.08.24	F4 Sport	26.9
	2017 wheel tethers installed per Ligier bulletin F4.14.10.03.17. No damage or fraying.	FIA Tech	10.4.2
	Ligier-logo Fondmetal or Dynamic front and rear wheels only. No Jongbloed.	F4 Sport	26.3o
	Rear tow hook fitted and painted red	FIA Tech	14.9
	Anti-intrusion kit installed. Front plate, new style attenuator per Ligier bulletin F4-16.14.		
	HPD cam cover breather must be installed with safety wire per TAMF4-2020-028		
	Confirm correct fuel pump bolts per HPD bulletin HPD-F4-2018-EN003		
	Verify correct ECU firmware and calibration		