

[POWER² AMPLIFIER]

If there were a word in the new millennium that has become ubiquitous and all but neutered of its former meaning, it would be the word, “power.” But you know, we’re going to spit in the face of that fact, slam our stake in the ground and hang with it. Why? Because our Power2 is true. It’s clean. And it’s a friggen’ load of 2-channel manhood. What else you gonna call it? Used with The Controller for our “stereo systems,” the Power2 is also a perfect choice to push back channels in 6.1 and 7.1 channel rigs too.



[SPECIFICATIONS]

Power Output:	2 x 200W RMS @ 8ohms THD+N <0.05% - all channels driven simultaneously
Frequency Response:	+/-0.5dB 20-20kHz
Dynamic Range:	112dB A-weighted @ full power
Damping Factor:	2000 @ 8ohms 100Hz
Peak Current:	35A
IM Distortion:	(CCIF) 0.0005%
TM Distortion:	0.003%
Soft Clipping	
NHTBus Features :	Intelligent operation with NHT Controller. Monitoring of amplifier status
Amplifier Control:	On/Standby/Mute. Control of individual channel operation - On/Off. Utilizes Ethernet infrastructure
Protection Features:	Phase-to-phase short. Phase-to-ground short. Under voltage. Thermal protection
Rear Panel Connectors & Components:	2 single-ended RCA input connectors, 2 pair of binding posts for speaker output - banana spacing 12V trigger input/output on 1/8" sub mini jacks NHTBus connector on RJ45, IEC mains voltage socket
Front Panel Features:	2 dual-color LED's for each channel indicating OK/Fault Standby, Touch sensor, Standby indicator
Weight:	22.2 lbs.
Power ² Dimensions:	3.875" H x 17.25" W x 17" D

