Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

CLUB RACING BOARD MINUTES | December 2, 2025

The Club Racing Board met by teleconference on December 2, 2025. Participating were Dayle Frame, Chairman; David Arken, David Locke, Jim Goughary, Peter Keane, Sam Henry and Shelly Pritchett, secretary. Also participating were: Bob Crawford, BoD Chairman and Mark Weber, BoD liaisons; Eric Prill, Vice President, Road Racing, Sydney Davis Yagel, Senior Manager of Race Operations, Scott Schmidt, Road Racing Technical Manager, Scott Dobler, Road Racing Series Manager, Jon Krolewicz Sr. Manager, Regional Track Program Development.

We appreciate the feedback and perspectives that our members provide, and we'd like to thank you for your outreach and being part of the process. Should you have any requests or feedback to share with the Club Racing Board or a class advisory committee, please visit https://crbscca.com/ to submit a letter. The following decisions were made:

Member Advisory
None.

No Action Required
AS
1. #39195 (Jason Smith) Update LM7 1 7/8
There are plenty of options for the 1-3/4 header requirements.

2. #39241 (Michael Kamalian) 2018+ Mustang Restrictor Change
Other restrictor plate changes in the class will improve your competitiveness at the current restrictor size.

3. #39261 (Barry Borgschatz Jr) Transmission/Final Drive - Driveshaft Loop
This rule does not need to be a mandate, but a driver choice.

4. #39462 (Andrew Kuhn) Weight Change Recommendation.
Please see the response to letter #39055, Technical Bulletin.

5. #39469 (Chris Itterly) Clutch Diameter Rule Proposal
Please see the response to letter number 39235 in current Fastrack.

B-Spec
1. #39354 (ENRIK BENAZIC) Adjust Weight of the 2005/2006 Mini Cooper
Your request will be considered along with all recommended BOP changes for 2026.

FA
1. #39298 (Reilly Harris) Floor and Diffuser Rule Change Request
Please see the response to letter #39608 in this Fastrack.

2. #39300 (Reilly Harris) Carbon Fiber Rule Change Request
Please see the response to letter #39608 in this Fastrack.

3. #39301 (Reilly Harris) Forward Facing Opening Rule Change Request
Please see the response to letter #39608 in this Fastrack.

FC
1. #39391 (Stephen Jenks) Change Metrik RF2 minimum weight to 1210#
Please see the response to letter #39612 in this Fastrack.

2. #39434 (Tim Minor) Metrix Weight Reduction
Please see the response to letter #39612 in this Fastrack.

P
1. #39494 (Jim Devenport) Revert P rules back to former P1 rule set
Please see the response to letter #39476 in this Fastrack.

2. #39541 (Johnnie Crean) Request to Remove Restrictions on Carbon Brakes
Please see the response to letter #39476 in this Fastrack.

GCR
1. #39108 (David Gomberg) Follow up to Letter 39105
The changes you suggest should be part of a larger GCR review effort with the involvement of the SCCA National Staff, Executive Stewards, Club Racing Board, and Board of Directors.

2. #39347 (Andrew Aquilante) More Thought Needs to be Given to Letter 38418
Complicated graphics on cars and having numbers easily readable by Timing and Scoring, corner workers, and emergency crews is a significant issue. This response was a compromise requiring consultation between T&S and the Race Director/Chief Steward and takes legibility of car numbers out of the sole purview of T&S as well as not mandating number boards.

GT2
1. #38972 (Richard Grant) New Car Classification Porsche 718 Cayman GT-4 RS Clubsport
This car is already classified in GT2-ST.

GTX
1. #39342 (Javier Delgado) GTX Category
In GTX-Misc. there are no specific years for either of the cars in question.

IT General
1. #39125 (Barry Borgschatz, Jr) Improved Touring E
ITE is a regional class and isn't under the national IT rules. Any changes would need to be submitted to the Division.

FP
1. #39512 (Steven Sargis) Proposed Rule Changes
The effect of recent changes made within FP, and the overall competition balance of the class, will be closely monitored.

2. #39518 (David Strittmatter) FP Parity Adjustments
The effect of recent changes made within FP, and the overall competition balance of the class, will be closely monitored.

3. #39571 (Jeff Winterfield) FP Miata 1.6, Honda and GTL Weight Proposal
The effect of recent changes made within FP, and the overall competition balance of the class, will be closely monitored.

HP
1. #39488 (Chuck Allard) 914 Porsche Five Lug Wheel Request
Hubs are unrestricted per rule 9.1.5.E.4.e.

STU
1. #39559 (Michael Heintzman) 39258 GT3U Car Ride Height
We will continue to collect data and monitor the class. Please bring your car out and race it so we can collect data.

T1
1. #39463 (Roy Lipner) GT4 Tire Selection
The GT4 cars in T1 have the option to use either Pirelli or Michelin tires if they are using non-DOT approved racing slicks. We have also allowed T1-GT4 cars to use any DOT approved race tire conforming to the size shown in the spec line.

T2
1. #39481 (joe Aquilante) Do Not allow TCR Cars Into T-2
The TAC has passed this concern to the CRB. They will continue to watch BoP and adjust as needed.

2. #39497 (Andrew Aquilante) Against TCR Cars in to T2
The TAC has passed this concern to the CRB. They will continue to watch BoP and adjust as needed.

T4
1. #39449 (Chris Giles) Call Rule Changes = Why I am Not Renewing My License and Racing
The RX8 is currently the performance target for T4. The car was dominant in 2024 and very competitive in 2025, aside from the 3.7 liter Mustang. The Mustang was an exact replica of the one that has been in the class from its inception, aside from the engine and that was restricted by 7mm or 11.66% (in area) since the Runoffs. It is now the smallest FPR in the class by 12mm. The TAC doesn't believe it is a threat at this time. Changes were made to the MX5 that will allow some cars to lose 100 lbs. All changes, aside from the Mustang, were made to bring other cars in-line with the RX-8. Taking weight out of the RX8 at this point is counterproductive to BOP efforts.

<u>Not Recommended</u>
GCR
1. #39403 (Luis Goncalves) 9.3.55. WINDOW SAFETY NETS
The Club Racing Board does not recommend this change. Coverage with an SFI 37.1 window net is directly dependent on the size of the driver's door window opening.

2. #39418 (Bill Skibbe) Letter 38549 Non Working Transponder
The Club Racing Board does not recommend this change. Timing a vehicle with a non-functional transponder should be at the discretion of the Chief of Timing and Scoring.

General
1. #38775 (Andrew Jenkins) Change Novice Permit Requirements to Races
Hi Andrew, Thank you for your thoughts on weekends vs. races when it comes to fulfilling Novice Permit requirements.

We do think that weekends are the appropriate measurement. First, because we believe the cycle of a racing event and all sessions are what is important to the learning process, and a full set of sessions gives time to be properly evaluated. Second, there are some regional event weekends with one race, some with two, and we've seen up to four races per class run within a single event sanction which could further create confusion and odd opportunities.

In addition, we are taking a broader look at SCCA licensing, and we will consider allowing a driver on a Novice Permit running multiple classes run in one weekend to count as multiple events, the way it's currently allowed for Full Competition License renewal. (Appendix C: 2.2.B)

Thank you again, and we appreciate your participation in the Road Racing rules process.

2. #39383 (Stephen Blethen) SM and SMX Combination Request
In SCCA racing, combining SM and SMX into a single class is not a sound approach. The performance disparity between the two is significant, approximately seven seconds per lap based on the best laps from the 2025 SCCA Runoffs, and such a merger would compromise the integrity and competitiveness of SM, one of SCCA's most successful classes.

3. #39386 (Brian Farnham) Runoffs Qualification Path and Schedule Format
The Road Racing Department has addressed many of your concerns in this announcement: https://www.scca.com/articles/2020067-2026-runoffs-classes-and-qualification-criteria-announced. We also understand the concerns of speed disparity and the Runoffs Race Director is prepared to take action, when needed. As an organization, SCCA is primarily focused on providing access and promoting participation as we head into 2026.

4. #39428 (Barry Borgschatz) Entry Fees for SCCA Road Racing/Time Trials
We appreciate your concern. Regions and organizers are faced with varying costs across the country, and because of that, it wouldn't be in our best interest to set a entry fee cap. We hope that regions and organizers are operating from a balanced budget that benefits both the region/organizer and drivers.

IT General
1. #39149 (Barry Borgschatz Jr) Engine Classifications
ITE is a regional class and isn't under the national IT rules. Any changes would need to be submitted to the Division.

2. #39201 (Barry Borgschatz Jr) Roll Cage Dash Bar
ITE is a regional class and isn't under the national IT rules. Any changes would need to be submitted to the Division.

FP
1. #39510 (Thomas Gaydos) 1988-1991 Prep 1 Honda CRX SI BOP
This change is not recommended at this time. The effect of recent changes made within FP will be closely monitored.

HP
1. #39522 (Doug DeRonne) Ford Festiva 12:0:1 Compression Request
This request is not recommended at this time. The letter writer is encouraged to develop to the current specs to fully understand this classifications potential.

2. #39584 (Brian Downey) Tubeframe Cars
There is no intention or desire by the Production Advisory Committee to add tube frame cars into either EP or HP.

STL
1. #39382 (Stephen Blethen) STL Ride Height
Not consistent with class philosophy.

STU
1. #38953 (Armen Megregian) GT3 into STU for 2026
We will be collecting data throughout the season and will make adjustments as needed.

2. #39147 (Eric Heinrich) STU TCR GT3U Solution.
TCR cars are no longer in STU. Adjustments have been made and will continue to be made throughout the year.

3. #39279 (Peter Federlin) Parity in the Class
TCR cars are no longer in STU. Adjustments have been made and will continue to be made throughout the year.

T1
1. #39360 (Rylan Hazelton) Consider Adding an Option for TCR in T1?
The TCR cars were only recently added to T2 and we'd like to see how that works out before making any changes. In T1, even though the lap times are similar, we are concerned about the discrepancies in on-track characteristics.

T4
1. #39381 (Stephen Blethen) Request to Make SCCA National Championship More Competitive
The committee is not ready to make this change at this time.

2. #39414 (Tony Kiratsous) BOP/Scion FRS Wheel Size
We have collected a large amount of data on these cars as they competed over the past few years. Most recently, we reviewed data from the Runoffs where leading examples went head-to-head. The Mustang and RX-8 have wider wheels but are 525lbs and 325lbs heavier respectively.

Recommended Items
The following subjects will be referred to the Board of Directors for approval. Address all comments, both for and against, to the Club Racing Board. It is the BoD's policy to withhold voting on a rules change until there has been input from the membership on the presented rules. Member input is suggested and encouraged. Please send your comments via the form at www.clubracingboard.com.

AS

1. #39083 (American Sedan Committee) 2026 rule updates (Errors and Omissions)
In AS Spec Lines, remove "Gear ratios std. or alt." column in entirety.

In GCR, Section 9.1.6.D.3.a.4., add attached:

Make	*1st*	*2nd*	*3rd*	*4th*	*5th*	*6th*
GM	*2.97*	*2.07*	*1.43*	*1*	*0.84*	*0.56*
All Transmissions must be in stock configurations	*2.97*	*1.58*	*1.19*	*1*	*0.77*	*0.63*
	3.01	*2.07*	*1.43*	*1*	*0.84*	*0.57*
	2.66	*1.78*	*1.3*	*1*	*0.74*	*0.5*
	2.66	*1.78*	*1.3*	*1*	*0.83*	*0.63*
	2.29	*1.61*	*1.21*	*1*	*0.82*	*0.68*
Ford	*3.66*	*2.43*	*1.69*	*1.32*	*1*	*0.65*
All Transmissions must be in stock configurations	*2.66*	*1.78*	*1.3*	*1*	*0.8*	*0.63*
	2.97	*2.1*	*1.46*	*1*	*0.8*	*0.63*
	2.66	*1.81*	*1.3*	*1*	*0.76*	*0.5*
	2.21	*1.61*	*1.21*	*1*	*0.82*	*0.68*
	3.24	*2.1*	*1.43*	*1*	*0.81*	*0.62*
	3.25	*2.23*	*1.61*	*1.24*	*1*	*0.63*
	3.24	*2.1*	*1.43*	*1*	*0.81*	*0.62*
Dodge	*2.97*	*2.1*	*1.46*	*1*	*0.74*	*0.5*
All Transmissions must be in stock configurations	*2.26*	*2.07*	*1.43*	*1*	*0.77*	*0.63*

All Cars	*4 speed transmissions "Dog Box" is allowed with a 50lb penalty*	*2.88*	*1.91*	*1.34*	*1*	
-+ .05 tolerance		*2.2*	*1.64*	*1.28*	*1*	
	*5 Speed Transmissions "Dog Box" is **NOT** allowed*	*2.87*	*1.89*	*1.28*	*1*	*0.81*
		2.95	*1.94*	*1.34*	*1*	*0.73*
		2.95	*1.94*	*1.34*	*1*	*0.63*

In GCR, Section 9.1.6.D.1.a.2.b.1., change the following:
"*Factory engine mounted fuel pumps must be maintained. If a fuel cell is used, any* ~~Any~~ fuel pump(s), fuel pressure regulators, or filters may be used and may be relocated, but shall not be located in the driver/passenger compartment. If a mechanical pump is removed, a blanking plate may be used to cover the original mounting location."

In GCR, Section 9.1.6.D.7.g. add the following:
"*5. Allow modification to the K/cross member/cradle for Header clearance. All resulting clearances shall be welded fully closed.*"

2. #39235 (American Sedan Committee) Errors and Omissions, Flywheel/Clutch
In GCR, Section 9.1.6.D.1.l.2., change as follows:
"~~Any clutch disc and pressure plate of stock diameter may be used.~~*Any single disc clutch 10.5" in diameter or larger may be used. Drilling and tapping the flywheel is permitted for allowing the installation of the smaller pressure plate, if needed.*"

B-Spec
1. #39349 (Alex Ratcliffe) 2002-2006 Mini Allow Adjustable Lower Control Arms
In B-Spec Spec Lines, Mini Cooper (R50) MT (2002-2006) update the Notes section as follows:
"Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Allow rear sway bar Progress #62.0210*, Mevotech lateral link CMK100003.*"

In B-Spec Spec Lines, Mini Cooper (R50) CVT (2002-2006), update the Notes section as follows:
"Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Allow rear sway bar Progress #62.0210*, Mevotech lateral link CMK100003.* CVT equipped cars allow Setrab 50-119-7612 transmission cooler in addition to OEM."

GCR
1. #38831 (Greg Amy) 9.3.19.C.1 FIA 8856-2018 Suits Expiration
In Required Equipment, GCR section 9.3.19.C.1, add the following effective 1/1/26:
"Driving suits that effectively cover the body from the neck to the ankles and wrists. One piece suits are highly recommended. All suits must bear an SFI 3.2A/1, SFI 3.4, or higher SFI certification label or an FIA 1986 Standard, FIA Standard 8856-2000, or FIA Standard 8856-2018 homologation label. Underwear of fire resistant material shall be used, but is optional with suits carrying an FIA Standard 1986 Standard or FIA Standard 8856-2000 label or SFI 3-2A/5 or higher (e.g., /10, /15, /20) certification label. *FIA 8856-2018 suits do not expire regardless of manufacturing date, but they must be maintained in acceptable condition (e.g., no rips, tears, other damage).*"

2. #39361 (SCCA Staff) 9.3.30 In-Car Flagging change
In In-Car Flagging System, GCR section 9.3.30, change as follows effective 1/1/26:
"1. All cars competing in ~~the~~ SCCA *Hoosier Super Tour events and the* Runoffs ~~(beginning in 2024)~~ must have a functioning *Flagtronics* FT200 or FT-RD unit that provides visual notification of changing course conditions to the driver while on track at all times. Driver notification may be made through the FT200 or FT-RD display or through the car's dash via an FT200 CAN Bus connection. ~~It is recommended that the Flagtronics unit be installed with thebuttons within the driver's reach while belted in the normal driving position to allow the driver to respond to messages from Race Control in the event of an impact that triggers the Flagtronics impact alert.~~ The unique ID number of the Flagtronics unit must be provided to the SCCA during the event registration process or as defined by the event supplemental regulations.

2. ~~Flagtronics is required at all Hoosier Super Tour events. Use of Flagtronics may be required at select U.S. Majors Tour events, or available as an option to participants, as per the event supplemental regulations.~~ *It is recommended that the Flagtronics unit be mounted in view of the forward-facing camera in a location where the buttons are within the driver's reach while belted in the normal driving position to allow the driver to respond to messages from Race Control in the event of an impact that triggers the Flagtronics impact alert.*

3. ~~SCCA may access any data recorded by the unit for CRB use to assist in performance balancing.~~*Missing Flagtronics units will be considered non-compliant. Non-operational Flagtronics units may be considered non-compliant.*"

3. #39474 (Sydney Yagel) Update 3.1.1.D.2
In Event Format / Schedule, GCR section 3.1.1.D.2.a, change as follows effective 1/1/26:
"There ~~shall~~*will* be a maximum of two (2) races per race weekend. At least one race for each race group will be 35 minutes in ~~length~~*duration* with a maximum *length* of 50 miles~~ (variations may be approved by the head of Road Racing and published in the supplemental regulations)~~. The other race of the weekend ~~shall~~*will* be a minimum of 25 minutes in ~~length~~*duration with a maximum length of 40 miles*. *Variations of these event formats may be approved by the head of Road Racing and published in the supplemental regulations.*"

4. #39482 (Sydney Yagel) Update 3.6.2
In Trophies, GCR section 3.6.2, change as follows effective 1/1/26:
"*a.* U.S. Majors Tour event trophies will be awarded on the following minimum basis for each participating class:
[*No changes to the existing table*]

b. Conference and Super Tour Championship awards and recognitions may be limited to drivers who complete a minimum of three (3) or more events within a specific Championship."

5. #39730 (Club Racing Board) RUSH SPORTS RACER (RSR) (REGIONAL ONLY CLASS)
In GCR, create Section 9.1.8.J. as follows:
"9.1.8.J. RUSH SPORTS RACER (RSR) (REGIONAL ONLY CLASS)
1. Definition

The purpose of this class is to provide the membership with a regional single-make, one design, fixed specifications, open cockpit, sports racer.

A. Vehicle Manufacturer and Car Eligibility
Rush Auto Works
4541 Brittmoore Rd, Houston, TX 77041
(713) 937-0000
Website: rushautoworks.com
Email: info@rushautoworks.com

B. Rush Sports Racer (RSR)
Only Rush Race Cars manufactured by Rush Auto Works Inc (RAW). and maintained in their original spec condition are eligible for competition. All cars must operate using Rush Auto Works mechanical parts available from Rush Auto Works aftersales department. All preparation, maintenance, and service of Rush Auto Works cars must be provided in accordance with official Rush Auto Works documentation and technical bulletins.

2. Homologation

Rush SR chassis are homologated with SCCA, but require a homologation certificate from SCCA, which can be obtained by contacting the Technical Services Department. Cars will only receive a certificate if they can show they meet the fuel cell requirement below.

3. Fuel Cells

If the car has an early blue plastic fuel cell, it must be completely covered in metal per section 9.3 of the GCR. This option may go away in 2027. The only other allowed fuel cells are either the side mounted or behind the seat units produced by RAW.

4. Minimum Weight

Weight with Nankang AR-1 tires: 1350 lbs
Weight with Hoosier W3 wet tires: 1325 lbs

5. Ballast

A. To reach minimum weight, competitors are permitted to attach ballast to the chassis on the 1-1/2" flat bar rails in front and behind the driver's seat.

B. Any weight added shall be secured by a minimum of two (2) 8mm bolts with Ny-lock nuts. All bolts shall be at least SAE grade 5 or metric grade 8.8 or stronger.

C. Ballast must be clearly marked with the car number and must be positioned to maintain proper weight distribution.

6. Setup

Maximum camber is -2.6 degrees and minimum ride height is 17.75" measured from the ground to the top of the front bar of the chassis where the chassis tag is located.

7. Bodywork & Aerodynamic Devices

A. Only bodywork and aerodynamic devices, body panels, wings, splitters, and diffusers as originally manufactured and purchased from RAW shall be permitted. No bodywork component or aerodynamic device shall be substituted with any item not manufactured by RAW and in original configuration as supplied by RAW. No part of the bodywork may be worked upon or modified beyond what is specifically permitted. All parts must comply in terms of size, look, and material to the original parts.

B. It shall be allowed to finish the RAW-supplied body panels by sanding, surface preparation, painting, or wrapping. The three slots in the front fender upper surfaces may have the forward faces removed to allow air to escape the front wheel area.

C. The front splitter angle may be adjusted using the front splitter stays. Additional horizontal bracing on the splitter braces is permitted. The optional RAW-manufactured high downforce front splitter and billet splitter mounts are permissible for all competition. Splitter mounts must remain unmodified in their original mounting positions.

D. The rear wing may be adjusted only using one of the six adjustment holes as provided on the RAW wing adjuster plates. No modification to the wing element, end plates, or wing mounting brackets including their mount to the bodywork shall be permitted. No other bodywork or aerodynamic device modifications shall be permitted.

8. Chassis and Frame

No chassis modifications shall be permitted under any circumstance. All members and components of the front crash box, welded chassis frame, and rear crash structure must remain in original configuration as supplied by RAW. It is not permitted to carry out any strengthening work on the frame (welds, brackets, etc.) without the authorization of RUSH Auto Works Inc. No modification to the floor, undertray, or rear diffuser is permitted.

9. Suspension Components and Wheel Bearings

A. Only suspension, wheel hubs, brake discs and calipers, shocks, steering rack and column, pedal box, differential assembly, shock absorbers, springs, and anti-roll bars as originally manufactured and purchased from RAW shall be permitted. No suspension component mentioned in section shall be substituted with any item not manufactured by RAW and in original configuration unless specifically permitted.

B. Only springs as supplied by RAW are permitted and can be run in any configuration.

C. The shock absorber must remain stock using only components supplied by RAW. The length of the shock absorber may be adjusted using the body lock nut on the shaft. The perch height for the spring may have its position adjusted. The compression and rebound valve settings may be adjusted. The shock absorber can use any viscosity shock oil. The internal valve discs can be adjusted in quantity using RAW-supplied discs only. The optional shock N2 chamber systems are permissible for all competition.

D. Wheel bearings must remain stock. No modification of the bearing or seal is permitted.

10. Permitted Adjustments

The front and rear toe alignment may be adjusted via the stock track rods. The front and rear camber may be adjusted by addition or removal of 0.5mm, 1.0mm, and 2.0mm camber shims as supplied by RAW. The front and rear anti-roll bars may be adjusted by position of the ARB anchor position on the ARB. The ARB may be disconnected. The front and rear ride heights may be adjusted. The corner weights may be adjusted through permitted means as contained herein.

11. Brake System

Only brake components as originally manufactured and purchased from RAW shall be permitted. This entails Brake Pads, Rotors, Calipers, ETC. The use of OBP Master Cylinders is mandatory but can be sized from ¾ inch to 1 inch. Brake fluid type is open but must meet minimum DOT 4 specification.

12. Engine

A. Only engines as originally manufactured and purchased from RAW shall be permitted. The RAW engine unit is sealed. Tampering with or removal of the engine seal by competitor or anyone other than RAW is not allowed. To ensure engine integrity, seals are applied by RAW directly. Any necessary engine maintenance work/engine replacement is the direct responsibility of RUSH Auto Works Inc.

B. Only RAW factory or Denso OEM starters are permitted inside the Rush Spec Series. Participants in violation of this section will be disqualified until the violation has been replaced or fixed.

13. Engine Control Unit.

The engine ECU may at no time be tampered with or re-flashed other than by RAW. ECUs may be inspected for flash updates by tech. ECUs which have been flashed shall be confiscated and the competitor disqualified from the event. In agreement with Event Officials, ECUs (engine control units) may be replaced at any time during the event.

14. Transmission and Driveline

A. Only transmission and driveline components as originally manufactured and/or purchased from RAW shall be permitted unless specifically addressed here. No transmission or driveline component shall be substituted with any item not manufactured or supplied by RAW and in original configuration. In agreement with Event Officials, the Series reserves the right to pick the transmission unit and send it to RUSH Auto Works for conformity checks.

B. The front sprocket may be adjusted from 14-tooth to 15-tooth Sprockets. The rear sprocket must remain a 44-tooth sprocket.

C. The differential may be adjusted to have 1, 3, or 5 clutch contact faces per side (20%, 60%, or 100%). The differential may be used in the 1.5 or 2.0 differential ramp position.

15. Wheels and Tires

A.

Dry: Nankang AR-1 185/60R13 Front and 205/60R13 Rear
Wet: Hoosier 44421W3 Front and 44426W3 Rear

B. The use of only ONE set of dry tires shall be permitted per race weekend. This rule shall apply from the first qualifying session of an event weekend. Drivers may use new or scrub tires during practice. Tires shall be marked following the first qualifying session of the event weekend and shall be used for all sessions of the event thereafter. If deemed damaged, authorization from the Chief of Tech may be granted for use of a replacement tire for the remaining sessions of the event.

16. Cockpit

No modification can be made to the pedal assembly beyond permitted adjustments to master cylinder sizing. It is not permitted to use rails, brackets, and any kind of non-original material to change the seat position. The use of alternative mirrors is permitted.

17. Mandatory Safety Equipment

- *Camber Plate Upgrade*
- *Case Saver*
- *Clutch Switch or equivalent*

18. Data Acquisition and Telemetry

Only Aim MXM, MXL, or MXS data systems are permitted. It is permitted to add data sensor packs only sold by RAW Aftersales. Telemetry systems different from the original or which provide redundant data to the original system are not permitted. All data (telemetry, video logger) must be always available to Race Officials. Race officials reserve the right to download and disseminate Aim data from any competitor at will. It is not permitted to reset the data acquisition system at the end of official practice, qualifying sessions, or races.

19. Miscellaneous Permitted Additions

It is permissible to add a chain guard to protect the engine bay from lubricant splatter. The optional RAW-manufactured wind deflector is allowed.

20. Transponders

The transponder must be located in the position specified by RUSH Auto Works technical documentation (see technical bulletin for location diagram)."

General

1. #39498 (SCCA Staff) Update Appendix B Organizational and Administrative Procedures

In GCR, Section APPENDIX B. ORGANIZATIONAL AND ADMINISTRATIVE PROCEDURES FOR EVENTS, change as follows:

"**APPENDIX B. ORGANIZATIONAL AND ADMINISTRATIVE PROCEDURES FOR EVENTS**

This section contains administrative procedures and information for members and race organizers. This section mandates certain actions, but it may not be protested or appealed.

1. ORGANIZING EVENTS

1.1. SCHEDULING

1.1.1. Divisional Scheduling Representatives

The Executive Steward of each Division will appoint a Divisional Scheduling Representative who will:

A. Work with the Regions to prepare a ~~R~~*r*ace ~~S~~*s*chedule for the following calendar year for all events to be conducted within their Division, including potential U.S. Majors Tour dates. All U.S. Majors Tour dates must be *submitted to the Head of Road Racing no later than November 1. U.S. Majors Tour dates must be approved* ~~confirmed~~ by the Head of Road Racing before being listed on the calendar.

B. *Submit all scheduled Region events in their Division into the online Event Sanctioning Dashboard in the Member Account Portal (MAP) for inclusion on the SCCA.com calendar. Event records must include accurate dates, locations, host Regions, and program types, and should be submitted no later than December 1.* ~~Submit the necessary documents and fees if applicable, to the National Office to support those events.~~

C. Submit *a* copy of the final racing schedule for their Division to ~~the Manager of Road Racing, and to the Chair of the Club Racing Board,~~ the Regional Executives of all Regions in their Division, and to the Scheduling Representatives of the other Divisions no later than December 1~~st~~.

~~The Scheduling Representative must be appointed in sufficient time to assure that the Race Schedule is completed and filed with the National Office no later than December 1.~~

1.1.2. Scheduling Policies and Procedures

A. The Division's ~~R~~*r*ace ~~S~~*s*chedule encompasses all road race activities *listed in GCR section 3*~~, including U.S. Major Tour events, Regional Events, Drivers' Schools, and SCCA Test Days~~, *as well as Race Experience events*.

B. Alternative Drivers' Schools (3.1.3.C) ~~and Racing Experience Sessions~~ are not required to appear on Division~~al~~ Schedules but must be sanctioned.

C. No U.S. Majors Tour events may be scheduled for a weekend that is less than two weeks prior to the start of the *first* Runoffs *qualifying day*.

1.2. POSTPONING OR CANCELLING EVENTS

All or part of an event may be postponed or cancelled under the following conditions:

A. Provision is made in the Supplemental Regulations for the event, or
B. The SOM order that all or part of the event be postponed or cancelled for reasons of safety or forces beyond their control.

1. Postponement - After consulting with the organizing Region, the SOM may postpone the classes not afforded the opportunity to race (as opposed to practice or qualify), provided a scheduled date is available at the same facility within the same competition year. The postponed races shall be run under the original sanction number.

2. Cancellation –
   a. An entire event (all classes, all sessions) postponed for more than 24 hours is considered cancelled, and entry fees shall be returned. If an event is cancelled during the competition, then the entry fees shall be prorated and a reasonable portion of the entry fee shall be returned.
   b. If drivers have participated in on-track sessions prior to the cancellation of their race sessions, they will be given credit for a start, and regions may award drivers' points according to their qualifying position. If a race is started and cancelled before halfway time or laps, then only race starters will be awarded points based on qualifying position.

3. Credit for Start - If an entire event is cancelled (all classes, all sessions), there shall be no credit for a start. If a race is postponed, the competitors have the option of either competing in the *postponed*~~post-poned~~ race, or receiving a

prorated refund and being classified as DNS for that race, provided they have participated in a practice session or are shown on the qualifying results for that race.

1.3.1. Applying for an SCCA Sanction

Regions should submit sanction applications at least 90 days before the event date. ~~Sanction applications must be submitted for approval at least 45 days prior to the scheduled date of the event with the~~ *~~following~~A rush service fee will automatically apply to Road Racing sanction applications submitted or remaining incomplete within 45 days of the scheduled event date. All applications must be submitted with the following materials:*

A. *Completion of*~~Completing~~ the online Event Sanction Process *in the Member Account Portal (MAP).* ~~or completing a current SCCA Sanction Application Form~~

B. Entry Form *(if paper registration is permitted.)*

C. Supplemental Regulations

D. *Event Schedule*~~Schedule of Events~~

1.3.2. Sanction Requirements

In addition to the items listed in App B.1.3.1, the following conditions must be met before a sanction number can be issued:

A. The race event is listed on the official SCCA calendar.

B. SCCA has approved the course for Road Racing.

C. The organizer owes no event related fees for prior events. See App B.1.6 for information about event fees.

D. Online Event Page Requirement

Each region is required to maintain an online event page for every sanctioned event, which may be hosted on the registration platform. The page must clearly direct participants to the complete and current version of the entire Supplemental Regulations containing all information required under Appendix B Section 1.4.1. The event page itself does not need to duplicate the content of the Supplemental Regulations, but must include, at a minimum, the event name, date(s), location, participant eligibility and eligible classes. The page must be published at the time the sanction request is submitted and remain accessible through the conclusion of the event.

1.3.3. Sanctioning for Alternative Drivers' Schools

SCCA Regions wishing to hold a Drivers' School using the Alternative Driving School method *must complete the online Event Sanction Process through the Member Account Portal (MAP) and submit all required materials* ~~submit a sanction applications to the National Office~~ no less than 10 days prior to *the scheduled school date. Required materials include:* ~~holding a school and include the following:~~

A. *Completion of the online* Sanction Application ~~Form~~ *in MAP*

B. Name(s) of approved Instructor(s)

C. Date~~s~~ of *on-track observation activity* ~~"school" elements (classroom/ *and* on-track)~~

D. Approval by the Divisional Executive Steward or a designee.

1.3.4 Courses

The words "course" and "circuit" and "track" are considered interchangeable for the purpose of these rules.

1.3.4.1. Types of SCCA Course Approval

SCCA must approve any course for a Road Racing event. For a particular track, the SCCA may:

A. Limit the types of events.

B. Restrict the number of cars which may be started simultaneously or in total.

C. Restrict the number of entries which may be accepted for an event.

D. Restrict the classes and categories of cars.

E. Restrict the license grades of drivers.

F. Disapprove the course for all SCCA speed events.

1.3.4.2. Application ~~F~~*f*or ~~A~~*a*n Event ~~O~~*o*n ~~A~~*a*n Unapproved Course

If a Region plans to hold an event at a new course or use a new unapproved, configuration at an existing course, they must contact sanction@scca.com with the full name of the course, physical address, configuration name and length. The Sanction Department will create a pending location record to allow the event to be calendared and a sanction request to be submitted.

The Region is responsible for coordinating with the Divisional Executive Steward to schedule a track review prior to the event. The track review must be completed and approval granted prior to the scheduled event. If the course and/or configuration is not approved, the sanction – whether pending or already issued-may be revoked. ~~A Sanction Application for an event at a course not already approved by the SCCA must be submitted at least 2 months before the proposed event, and must include a full description of the course and facilities, including a scale map.~~

1.4 SUPPLEMENTAL REGULATIONS AND ENTRY FORMS

Organizers may distribute Supplemental Regulations or *accept event registrations* ~~Entry Forms~~ *prior to receiving an official SCCA sanction for all types of events, except a Super Tour. Submission timelines for required documentation remain in effect. Accepting registrations – whether online or otherwise – is contingent upon final sanction approval and may be subject to withdrawal or modification if the sanction is not granted.* ~~for an SCCA event prior to obtaining an SCCA sanction.~~

1.4.1 Required Contents of Supplemental Regulations

Supplemental Regulations *define the specific conditions under which an SCCA event is conducted. These regulations are drafted by the sanctioning Region, and for the U.S. Majors Tour – which include both Conference Majors and Super Tour events-a standardized template is available from the SCCA Road Racing Department.* ~~establish specific conditions for an event.~~

Before a sanction for an event can be issued, *any regulations that differ from the General Competition Rules (GCR) must be reviewed and approved by* the Divisional Executive Steward or a designee. ~~must approve all Regulations different than those of the GCR.~~ The Club Racing Board has the right of review and final approval at its discretion.

For Conference Majors, Supplemental Regulations are drafted by the sanctioning Region and must be reviewed and approved by the Divisional Executive Steward (or designee) and the Head of Road Racing.

For Super Tour events, Supplemental Regulations are drafted by the sanctioning region in coordination with the Super Tour staff and must be reviewed and approved by the Divisional Executive Steward (or designee) and the Head of Road Racing.

~~For U.S. Majors Tour events, Supplemental Regulations are drafted by the sanctioning Region and the U.S. Majors Tour staff. The Supplemental Regulations are submitted by the sanctioning Region, reviewed and approved by the Division's Executive Steward (or a designee), and reviewed and approved by the Head of Road Racing.~~

The Divisional Executive Steward (or designee) is responsible for uploading the approved Supplemental Regulations and related documents via the online Event Sanction Process in the Member Account Portal (MAP).

Supplemental Regulations must contain the following information for the event:

A. The name *of the event*, location, dates, ~~nature~~ *event category (e.g., Road Racing)*, and event type *(e.g., Regional, Conference Majors, Super Tour)*.

B. Supplemental Regulations must be updated with the sanction number and sanction type immediately *upon issuance*.

C. Conspicuously placed ~~words~~*statement*: "Held under the *current* SCCA General Competition Rules *as amended by Fastrack*."

D. The name and *contact information (address, phone and email address)* ~~address~~ of the ~~organizers~~ *organizing Region*.

E. A complete description of the event, including the course length, *configuration,* and types of sessions and races, the *eligible car classes*~~classes of cars eligible~~, and the race groups (See AppB.1.4.2.) *If Regional-Only classes are included in the event, the full ruleset or URL link to the ruleset for each Regional-Only class must be included.*

F. *A detailed schedule and location of on- and off-track activities, including registration, technical inspections, operating hours of official scales, driver meetings and social functions.*~~Schedules and locations of on and off-track activities, inspections, and meetings.~~

G. The name and *contact information* ~~address~~ of the Registrar or *designated entry contact,* ~~other person to whom the entry is to be sent,~~ closing date for receipt of entries, and amount of the entry fee.

H. Instructions for accessing and completing event registration including participant eligibility, links to the online registration platform and waiver process information.

I. The names of the Chief Steward and the Chair of the SOM. For Super Tour events, add the Race Director and the Series Administrator.

J. The *method by which*~~way~~ results will be determined and *how awards*~~trophies~~, and prizes *will be distributed.*~~awarded.~~

~~K. The times official scales will be available for competitors to check the weight of their cars.~~

~~L.~~ *K.* The brand and general description of any required spec fuel (e.g., Sunoco 100 octane unleaded)*, including availability and purchase instructions*.

~~M.~~ *L.* All other information necessary for the proper conduct of the event, not already included in the GCR *or the Supplemental Regulations*.

~~N.~~ *M. A statement regarding refunds:* A driver who has been on track (turned a wheel) in any sanctioned session of an event is considered to have participated in the event and is not eligible for a refund, unless the event supplemental regulations specifically state otherwise.

N. It is recommended to include the SCCA's Welcoming Environment Statement at the beginning of the Supplemental Regulations.

1.4.2 Combining Classes into Race Groups

A. The speed and performance differences among the cars may not be extreme.

B. Any Formula classes may be combined with *Prototype/*Sports Racing classes.

C. It is preferable to combine *Prototype/*Sports Racing classes with appropriate Formula classes rather than with Production*-based* or GT classes.

D. It is preferable not to combine *Prototype classes,* FA, FC, FE, *FE2*, or FX, with FV, F600 or FF. ~~.FV may be combined with F600 and FF.~~

E. SRF/SRF3 may be combined with F and H Production and GTL.

F. Formula classes shall not be combined with cars from any other category except *Prototype/*Sports Racing. The only exception is in race groups *consisting*~~con-sisting~~ solely of Vintage/Historic cars.

G. It is preferable not to combine GT1, AS, T1, T2, T3, and STU with P~~1~~, P2, SRF, *SRF3*, FP, HP, or GTL.

H. Vintage cars may not be grouped with any other type of cars at SCCA Regional or U.S. Majors Tour events but may be combined at Drivers' Schools.

I. Vintage/Historic sanctioned race groups may include non-vintage classes.

1.4.3 Additional Classes

Organizers may include classes not specified in 9.1, provided the conditions and specifications are clearly outlined or referred to in the Supplemental Regulations. Including those additional classes may not jeopardize the full schedule of sessions for the SCCA recognized classes. *All cars participating in an SCCA-sanctioned event are required to have an SCCA Vehicle Logbook.*

1.4.4 Multiple Types of *Competitions* on a Single Weekend

It is not generally permitted for race groups from different types of competitions on the same weekend to run simultaneously. *Please contact the SCCA Road Racing Department with questions.*

1.4.5 Required Contents of Entry Forms

Entry forms, whether submitted through an online registration platform or via paper form, must include the following fields and declarations:

A. *The words: "Held under the current SCCA General Competition Rules as amended by Fastrack."*
B. *The SCCA sanction number assigned to the event.*
C. *Space for the full name, address, SCCA membership number, Region of Record, license type, sponsor information, emergency contact, and name of entrant (if assigned) for each driver entering the event.*
D. *Space for a full description of the car to be entered, including car make and model and car number.*
E. *Acknowledgment of the following declaration, captured either by a physical signature on a paper form or checkbox confirmation in online registration platforms:*
    a. *By submitting this entry, I agree to comply with the current SCCA General Competition Rules (GCR) as amended by Fastrack, including all applicable event entry standards, waiver provisions, and media rights policies. I understand that participation in this event requires adherence to these rules and procedures, and I affirm my commitment to upholding SCCA's values and fostering a welcoming, respectful, and inclusive environment throughout the event.*
    b. *I understand that participation in any capacity in motorsports is dangerous. Known or unknown conditions and situations involving myself or others, including but not limited to vehicle preparation, equipment condition, facility and environment, physical fitness, medical conditions, medications, knowledge, abilities, or skill can cause injury (significant or otherwise) and death. I understand that I cannot participate in the event if I am on*

medication or have a medical condition that impacts my ability to participate. My decision to enter an event in any capacity, and to continue my participation throughout the event, is voluntary and with the knowledge of the above conditions and potential outcomes.

F. Any other information required for the clarification of all other details of the event.

~~A. Spaces for full names, addresses, membership numbers, sponsorship information and license type and numbers of entrant(s) and driver(s), and for driver's Region of Record.~~

~~B. Space for full description of cars to be entered.~~

~~C. The words: "Held under the SCCA General Competition Rules."~~

~~D. Spaces for signature(s) of entrant(s) and driver(s) for waiving liability and/or indemnity declarations, acknowledging the authority of the GCR, declaring that the entered car complies with the provisions of the GCR, and the person(s) to be notified in case of accident.~~

~~E. The sanction number assigned to the event.~~

~~F. Any other information required for the clarification of all other details of the event.~~

1.5. ORGANIZER'S ADDITIONAL RESPONSIBILITIES

In addition to the responsibilities listed above, organizers must fulfill the following requirements:

1.5.1. Entry List

An official *entry* list of *registered participants must* ~~competitors entered in the event~~ ~~shall~~ be made available ~~to all~~ *before the event begins. This may be posted digitally via the registration platform or event website. It must be accessible to all participants.* ~~entrants at no charge as early as possible before the event begins.~~

1.5.2. Results

Organizers must distribute Official Race Results to all participants in a timely manner within 7 days of the event, or within 7 days of any protest or Court of Appeals decision affecting results, whichever occurs first. Results must be made available by one or more of the following methods:

- *Printed or photocopied copies at the event*
- *Posted to a shared digital location (e.g., event website, registration platform, or shared drive) accessible to all participants*

A copy of the Official Race Results must also be submitted in PDF format to the SCCA Road Racing Department at roadracing@scca.com.

~~The organizer is responsible to distribute results as follows:~~

~~Printed or photocopied Official Race Results available for each entrant at the event; or mailed at the organizer's expense or emailed (at the entrant's option) within 7 days of the event, 7 days of the notification of any protest decision affecting Results, or 7 days of a Court of Appeals decision, whichever is applicable and whichever comes first.~~

1.5.3. Post-Event Reporting

~~The o~~*O*rganizer*s* ~~is~~ *are* responsible for submitting all ~~SCCA~~ required audits and ~~appropriate~~ fees to the *SCCA* National Office within the time limits *specified in Appendix B.1.6.*~~, as specified in AppB.1.6. and the SCCA Insurance Handbook on the sanction application and audit form.~~

1.6. RACE EVENT FEES

Organizers are responsible for submitting post-event documentation and ensuring timely payment of all applicable fees. The MyLaps Orbits Backup File and a copy of the Official Race Results in PDF format must be submitted to roadracing@scca.com for all Regional, Conference Majors and Super Tour events. Future sanctions may be withheld for outstanding balances. The Program Event Fees schedule is available in the Member Account Portal under Member Resources → File Cabinet → Sanction & Audit.

1.6.1. Regional Events

Regional events include all Road Racing events that are not Conference Majors or Super Tour events. For these events, organizers must:

- *A. Submit the post-event audit form using the online Event Sanctioning tool in the Member Account Portal within 14 days of the event's conclusion.*
- *B. Pay the following fees ~~per the~~ within 28 days of the event:*
  - *a. Event Fee – supports administrative and operational costs of sanction and insurance*
  - *b. Volunteer Fee – supports SCCA volunteer worker rewards program*
  - *c. Compliance Surcharge Fee – see the Program Event Fees for the current list of compliance classes and associated surcharges*

Late Fees may apply if payments are not received within the specified timeframe.

1.6.2. U.S. Majors Tour Events

The SCCA National Office will invoice the organizing Region based on the Orbits Backup File and Official Race Results for all applicable fees.

- *A. Pay the following fees within 28 days of the invoice date.*
  - *a. Event Fee*
  - *b. Volunteer Fee*
  - *c. Compliance Surcharge Fee*
  - *d. Super Tour Assessment Fee (for Super Tour events only)*

~~A. Post-Event Audit~~

~~Upon the conclusion of Regional race events, a post-event audit form must be submitted to the SCCA National Office *using the online Event Sanctioning tool in the SCCA Member Account Portal* within 14 days following the event. Audit forms and f*The* fee~~

~~schedule are *is* available from the SCCA National Office and can be found *in*on the *File Cabinet in the SCCA Member Account Portal*.SCCA website.~~

~~B. Sanction*Event* Fee~~

~~The appropriate sanction *event* fees for a Regional race event listed on the audit form and *theon the* fee schedule must be paid within 28 days of the completion of the event or late fees may apply.~~

~~C. Insurance Fee~~

~~The appropriate insurance fees for a Regional race event listed on the audit form and the fee schedule must be paid within 28 days of the completion of the event or late fees may apply.~~

~~D*C.* Compliance Surcharge~~

~~Upon the conclusion of Regional race events, a *compliance* surcharge for each Spec Racer *Ford* and Formula Enterprises car that turned a wheel on the course must be paid within 28 days of the completion of the event.~~

~~E*D.* Volunteer Fee~~

~~A Volunteer Incentive Fee, as listed on the audit form and the fee schedule, must be paid within 28 days of the completion of the event to support the SCCA volunteer incentive and rewards program.~~

~~F.*E*. U.S. Majors Tour Assessment~~

~~For all U.S. Majors Tour Events, a "per entry" fee will be assessed and must be paid within 14 days of the event. No further sanctions will be issued to a region until this has been paid. This fee includes the following components:~~

~~1. Sanction fee~~

~~2. Compliance Surcharge~~

~~3. Insurance Fees - The fee schedule is available from the SCCA National Office, or on the SCCA website.~~

~~4. Volunteer Incentive Fee - The fee schedule is available from the SCCA National Office, or and can be found~~

~~5. U.S. Majors Tour Assessment~~

2. INSURANCE COVERAGES AND LIMITS

2.1. Insurance Requirements

All SCCA sanctioned events must be insured for Event Liability and Participant Accident insurance coverage. General Liability and Participant Accident coverage must be provided by the SCCA Event Insurance Plan.

The Race Director or Chief Steward must delay an event until they are satisfied that the required insurance is in place."

ITR
1. #39252 (Scott Krzastek) Letter #38971 Adjustment
Please see letter # 39105 in current Fastrack.

Prod General

1. #39508 (Jon Brakke) Revisions to Transmission Rules Consistent with Spec Line Format
In GCR, Section 9.1.5.E.1.n., change as follows:
"5. The *"Trans. Speeds"* number ~~of transmission speeds~~ listed in a car's specification line *indicates the maximum* ~~is the~~ number of forward gears *that may be* operable by the driver from the normal seated position (e.g. a 6 speed transmission with 1 forward gear removed/disabled is considered a 5 speed transmission).

6. The "Trans. Speeds" number listed in a car's specification line indicates the maximum number of forward gears that may be operable by the driver from the normal seated position (e.g. a 6 speed transmission with 1 forward gear removed/disabled is considered a 5 speed transmission)."

SM

1. #39090 (Spec Mazda (SM/SMX) Committee) Include Runoffs in Tire Limiting
In GCR, Section 9.1.7.C.6. Tires, change as follows:
"Competitors must use the official Hoosier Dry tire or Wet tire for Regional and Majors competition *including the Runoffs.*
a. Tires must be used in complete sets. No mixing of wet and dry tires on the car. Tires must be run unmodified.

b. Hoosier dry P205/50ZR15 SM7.5. Hoosier wet P205/50ZR15 SMW.

c. SM TIRE MARKING:

1. SM cars are limited to one set of Hoosier SM 7.5 P205/50/ZR15 per Hoosier Super Tour *& Runoffs* event weekend*s* for all dry qualifying and race sessions. This limitation does not include testing or practice sessions. Approved rain tires will not be required to be marked."

SMX5

1. #39091 (Spec Mazda (SM/SMX) Committee) Add Runoffs to Tire Limiting for SMX
In GCR, Section 8.1.7.1.D.16, change as follows:
"SMX cars are limited to one set of Toyo RR P235/40/ZR17 per Hoosier Super Tour event *& Runoffs* weekend*s* for all dry qualifying and race sessions. This limitation does not include testing or practice sessions. Approved rain tires will not be required to be marked."

ST General

1. #39450 (Lisa Keyes) Request for STL Rule Review – Aftermarket Dash Allowance
In GCR, Section 9.1.4.E.6., change as follows:
"~~Stock d~~*D*ash/instrument panel cover ~~(dash pad)~~ must be used *which fully encloses instrument wiring and mechanical components*. Original instruments/gauges may be replaced, or supplemented, with additional engine monitoring gauges. Accessories, lights and switches may be added or removed. Box-type extensions from the dash pad may be used to mount switches and controls, in the areas where the OEM insert panels were mounted, so that they more easily accessible to the driver. Audio and video systems may be removed.

In GCR, Section 9.1.4.E.8., change as follows:

"~~8. Dash pad modification – It is permitted to modify the dash pad in order to run the roll cage tubes through the dash area as long as the dash pad is modified only enough for roll cage fitment. If necessary, the dash pad may be parted to ease installation around roll cage. Any such parting shall be done in such a way as to minimize the appearance that they have been separated once pieces of dash pad are installed.~~"

Taken Care Of

B-Spec

1. #39321 (Chris Capaldi) OBX #10-2101-2S Header Availability and Competitive Parity

This has been a topic of intense debate for the BSAC over the past year. The lack of commercial availability of the approved OBX header for the 07-10 Mini Cooper/Clubman has created a dichotomy of "haves" and "have-nots" among the Mini contingent in B-Spec, with some drivers resorting to cloning the approved part or paying thousands of dollars for an existing unit. The BSAC has weighed and debated numerous options for how to handle this situation. Ultimately, we have determined that the best course of action for the long term viability of the category is to eventually expire this header from spec lines that is currently permitted on and robustly ensure the competitiveness of the OEM manifold/catalyst configuration.

While the BSAC is aware that there are plenty of cars currently competing with this header or a counterfeit version, there are also competitors are not and either cannot find this part, or cannot afford to purchase an existing example or have one cloned. As Chris pointed out in his letter and as the committee concluded as well, this does not preserve fairness and technical parity across the class. It also should not continue to be class philosophy to have multiple configurations for a spec line as it makes managing BOP more difficult. A task that is already not simple given the diversity of platforms, tracks, and driver skill within the series.

The Mini has proven to be a competitive platform since the inception of B-Spec as a pro category in World Challenge. However, current BOP has resulted in it carrying a significant amount of ballast as well as being given a restrictor plate. Traditionally, aftermarket parts such as air intakes and headers are only approved for use in B-Spec when a car clearly needs to be sped up in order to compete (I.E. Mazda 2, second/first generation Honda Fits, Nissan Versa, etc.). However, this is a practice that the committee wants to use sparingly in the future as we cannot guarantee the availability of aftermarket performance parts. Additionally, allowing a power-adder such as a header for a vehicle that is required to race with a restrictor plate AND hundreds of pounds of ballast is objectively absurd.

Data gathered over the past years shows that despite its current minimum weight, the Mini Cooper is still one of the best handling cars in the category thanks to its independent rear suspension and other attributes. The spec line for Mini equipped with a header currently requires a 40 mm restrictor plate. The current spec line for the OEM manifold/catalyst equipped Minis requires a 45 or 44 mm plate depending on the model year due to minor engine differences between the two generations of R56 Mini Cooper.

It is the committee's recommendation that the restrictor plate diameter of the OEM manifold/catalyst equipped Minis be opened to improve their acceleration performance. It is also our recommendation that the OBX header eventually be removed from B-Spec competition. The committee is also aware that OEM catalyst cost and availability is rapidly becoming a widespread issue across the category. This is a topic will we be rapidly addressing for all spec lines.

The committee's desire is to provide a ruleset and BOP for the category that is fair, cost controlled and promotes growth. Allowing parts that are no longer available is not conducive to achieving that goal. Discussing this topic over the past year has

also prevented us from working on other pressing matters that are crucial to the category's long term success. We are eager to move this class towards a successful future instead of clinging to pieces of its past.

GCR
1. #39422 (Paul Gauzens) Support Letter #39158 Standardize Car Number Boards
Please see the response to letter #39158 in the December 2025 Fastrack.

General
1. #39388 (Dave Weitzenhof) Support for letter #39386 by Brian Farnham
Please see letter # 39386 in current Fastrack.

2. #39395 (Barry Shelton) Support letter # 39386
Please see letter # 39386 in current Fastrack.

3. #39396 (Jay Messenger) Support for letter 39386
Please see letter # 39386 in current Fastrack.

4. #39398 (Raymond Blethen) Support letter #39386
Please see letter # 39386 in current Fastrack.

5. #39400 (Joe Fisher) Provide More Avenues to Reach the Runoffs
Please see letter # 39386 in current Fastrack.

6. #39404 (Brian Styczynski) In support of letter 39386
Please see letter # 39386 in current Fastrack.

7. #39410 (Simon Stallings) Support of Letter #39386
Please see letter # 39386 in current Fastrack.

8. #39412 (H. Cory McLeod) Support for Letter #39324 - Return F600 to the Runoffs
Please see letter # 39319 in the December Fastrack.

9. #39415 (Jeff Jorgenson) Support of letter #39324
Please see letter # 39319 in the December Fastrack.

10. #39433 (John Spinello) Letter #39386
Please see letter # 39386 in current Fastrack.

11. #39457 (Jim Lepetich) Request for Consideration of John LaRue Letter #39303
Please see letter # 39294 in December Fastrack.

HP
1. #39570 (Nils Hagen-Frederiksen) Letter in Support of Jonathan Kinberg Regarding BMW 2002 Classing
Please see response to Letter #39567 in current Fastrack.

2. #39573 (John Hotz) BMW 2002 Reclassification Support
Please see response to Letter #39567 in current Fastrack.

3. #39574 (John Jenkins) BMW 2002 Reclassification Support
Please see response to Letter #39567 in current Fastrack.

4. #39576 (Hayes Lewis) In Support of Letter 39567
Please see response to Letter #39567 in current Fastrack.

5. #39577 (Reena Eary) BMW 2002 Reclassification Support
Please see response to Letter #39567 in current Fastrack.

6. #39578 (Drew Eary) Reclassification of BMW 2002 for HP
Please see response to Letter #39567 in current Fastrack.

7. #39586 (Michael Kelley) Support of Letter 39567
Please see response to Letter #39567 in current Fastrack.

8. #39587 (Bruce Shelton) BMW 2002 Reclassification Support
Please see response to Letter #39567 in current Fastrack.

9. #39592 (Ralph Pagington) BMW 2002 Reclassification Support
Please see response to Letter #39567 in current Fastrack.

Prod General
1. #39364 (Tim Schreyer) Please Provide Update on Current State of Letter 34738
Please see letter # 37190 in December Fastrack.

STL
1. #39318 (Charles Mathes) Request weight adjustment in STL
Please see letter # 39579 in current Fastrack.

STU
1. #38838 (Douglas Hillmann) STU GT3 Integration
TCR cars have been removed from STU and placed in T2 and are no longer an issue.

2. #39496 (Peter St Pierre) Balance of Performance
TCR cars are no longer in STU. Adjustments have been made and will continue to be made throughout the year.

T2
1. #39290 (Rylan Hazelton) Correction to Honda TCR spec
The spec line currently says 92.5% in the "Power Level" column.

T4

1. #39380 (Stephen Blethen) Request to Make SCCA National Championship More Competitive
In letter # 37997, earlier this year, we asked to remove the camber limit. It will be removed as of 1/1/2026.

What Do You Think

None.

Resumes

1. #39557 (Spec Mazda (SM/SMX) Committee) Grant West New SMAC Member
Grant West has been added as a new member of the SMAC Committee.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

DATE: December 20, 2025
NUMBER: TB 26-01
FROM: Club Racing Board
TO: Competitors, Stewards, and Scrutineers
SUBJECT: Errors and Omissions, Competition Adjustments, Clarifications, and Classifications

All changes are effective 1/1/2026 unless otherwise noted. If any day of a race event falls on the first day of the month, the previous month's rules will be in effect for that event only. The new rules will become effective at the conclusion of the race event, unless otherwise noted.

American Sedan
AS
1. #39055 (Jason Smith) Edelbrock manifold (& timing kit) to Chevy LS Spec Lines Request
In GCR, Section 9.1.6.D.2.h.2., add the following:
"*(Effective 2/1/2026) i. Weight based on full preparation chassis choice spec line for GM LM7 5.3L*
Carburetor Option:
Must use the full prep 4776 holly carburetor and spacer gasket
Edelbrock Performer RPM 71187 intake manifold
MSD 6014 ignition box
(Edelbrock part # kit 7118)"

2. #39501 (American Sedan Committee) Restrictor Plate Change for Gen 2 Ford Coyote Engine
In AS Spec Lines, change Restrictor as follows:
Ford Mustang Incl. Cobra and Cobra R (79-93) and Mercury Capri (79-86) with Restricted Prep Engine: "~~64 mm~~*61 mm*"
Ford Mustang GT (94-04) with Restricted Prep Engine: "~~64 mm~~*61 mm*"
Ford Mustang Coupe GT (05-14) Restricted Prep 5.0L/6 speed 4 valves per cylinder: "~~64 mm~~*61 mm*"
Ford Mustang GT (05-14) with Restricted Prep Engine: "~~64 mm~~*61 mm*"
Ford Mustang GT 5.0L (15-17) Restricted Preparation: "~~64 mm~~*61 mm*"

B-Spec/C-Spec
1. #39062 (B-Spec/C-Spec Committee) Notes section cleanup
In B-Spec Spec Lines, Chevrolet Sonic Sedan MT (12-19), change Notes as follows:
"~~GM suspension kit #23123679 permitted. Bilstein B14 kit #47-171725 verifed compatible. Allow rear sway bar ZZ Performance #ZZ-SNCRSB. Allow Aluminum Radiator #ZZP-ZZ013. Allow Babyface Fabrication brake caliper piston SNC-SS.~~*Approved parts: ZZ Performance rear sway bar ZZ-SNCRSB, ZZ Performance radiator ZZP-ZZ013, Babyface Fabrication brake caliper piston SNC-SS. Bilstein B14 kit 47-171725 verified compatible.*"

In B-Spec Spec Lines, Chevrolet Sonic Sedan AT (12-19), change Notes as follows:
"~~GM suspension kit #23123679 permitted. Bilstein B14 kit #47-171725 verifed compatible. Allow rear sway bar ZZ Performance #ZZ-SNCRSB. For automatic allow Setrab 1-series Part No. FP119M221. Allow Aluminum Radiator #ZZP-ZZ013. Allow Babyface Fabrication brake caliper piston SNC-SS.~~*Approved parts: ZZ Performance rear sway bar ZZ-SNCRSB, ZZ Performance radiator ZZP-ZZ013, Babyface Fabrication brake caliper piston SNC-SS, Setrab transmission cooler 50-119-7612. Bilstein B14 kit 47-171725 verified compatible. This configuration is not currently eligible for Runoffs competition. This car must compete in three separate Majors/Super Tour events so performance data can be collected. In addition to an SCCA data box, OBDII data collected via an AIM or similar device must be submitted.*"

In B-Spec Spec Lines, Chevrolet Sonic Hatchback MT (12-19), change Notes as follows:
"~~GM suspension kit #23123679 permitted. Bilstein B14 kit #47-171725 verifed compatible. Allow rear sway bar ZZ Performance #ZZ-SNCRSB. Allow Aluminum Radiator #ZZP-ZZ013. Allow Babyface Fabrication brake caliper piston SNC-SS.~~*Approved parts: ZZ Performance rear sway bar ZZ-SNCRSB, ZZ Performance radiator ZZP-ZZ013, Babyface Fabrication brake caliper piston SNC-SS. World Challenge suspension kit permitted but no longer available. Bilstein B14 kit 47-171725 verified compatible.*"

In B-Spec Spec Lines, Chevrolet Sonic Hatchback AT (12-19), change Notes as follows:
"~~GM suspension kit #23123679 permitted. Bilstein B14 kit #47-171725 verifed compatible. Allow rear sway bar ZZ Performance #ZZ-SNCRSB. For automatic allow Setrab 1-series Part No. FP119M221. Allow Aluminum Radiator #ZZP-ZZ013. Allow Babyface Fabrication brake caliper piston SNC-SS.~~*Approved parts: ZZ Performance rear sway bar ZZ-SNCRSB, ZZ Performance radiator ZZP-ZZ013, Babyface Fabrication brake caliper piston SNC-SS, Setrab transmission cooler 50-119-7612. Bilstein B14 kit #47-171725 verified compatible. This configuration is not currently eligible for Runoffs competition. This car must compete in three separate Majors/Super Tour events so performance data can be collected. In addition to an SCCA data box, OBDII data collected via an AIM or similar device must be submitted.*"

In B-Spec Lines, Ford Fiesta Hatchback (11-19), change Notes as follows:
"~~Suspension kit #M-FR3-FAEB allowed. Rear axle bushing #000-04-2203-RR allowed. Allow rear torque bar Corksport #Mz2-3-070. Cold air intake K&N 69-3530TS is allowed. Powerflex PFR19-1511BX2 rear suspension bushing allowed. Eibach rear sway bar #35143.312 o r35143.320 is allowed. Mazda front hub D651-33-06 and rear hub D651-26-15XE allowed.~~*Approved parts: Eibach rear sway bar 35143.312, Corksport rear torque bar MZ2-3-070, K&N intake 69-3530TS, Powerflex rear suspension bushing PFR19-1511BX2, Mazda front hub D651-33-06, Mazda rear hub D651-26-15XE.*"

In B-Spec Spec Lines, Ford Fiesta Sedan (11-19), change Notes as follows:
"~~Suspension kit #M-FR3-FAEB allowed. Rear axle bushing #000-04-2203-RR allowed. Allow rear torque bar Corksport #Mz2-3-070. Cold air intake K&N 69-3530TS is allowed. Powerflex PFR19-1511BX2 rear suspension bushing allowed. Eibach rear sway bar #35143.312 o r35143.320 is allowed. Mazda front hub D651-33-06 and rear hub D651-26-15XE allowed.~~*Approved parts: Eibach rear sway bar 35143.312, Corksport rear torque bar MZ2-3-070, K&N intake 69-3530TS, Powerflex rear suspension bushing PFR19-1511BX2, Mazda front hub D651-33-06, Mazda rear hub D651-26-15XE.*"

In B-Spec Spec Lines, Honda Fit MT (07-08), change Notes as follows:
"~~Bilstein B14 kit 47172401 verified compatible. Allow rear sway bar Progress #62.1060. Allow Injen Intake SP1511 OEM exhaust manifold required. Primary catalyst may be removed. Allow Torque Solution Shifter Cable Bushing kit TS-SCB-506.~~*Approved parts: Progress rear sway bar 62.1060, Injen intake SP1511, Torque Solution shifter cable bushings TS-SCB-506. Bilstein B14 kit 47172401 verified compatible. OEM exhaust manifold required. Primary catalyst may be removed.*"

In B-Spec Spec Lines, Honda Fit AT (07-08), change Notes as follows:
"~~Bilstein B14 kit 47172401 verified compatible. Any aftermarket header allowed. Allow rear sway bar Progress # 62.1060. Any Cold Air Intake Package allowed (any manufacturer).~~*Approved parts: Progress rear sway bar 62.1060, Injen intake SP1511, Setrab transmission cooler 50-119-7612, any aftermarket header. Bilstein B14 kit 47172401 verified compatible.*"

In B-Spec Spec Lines, Honda Fit MT (09-14), change Notes as follows:
"~~Allow damper and spring set 51600F23SA100, Damper FR LH 51605F23SA100, Damper FR RH 51606F23SA100, Damper RR 52610F23SA100, Spring adjust asy RR 52691F23SA010. Seat upper FR spring 51688F23SA200, 51402FC4YA00 front helper spring and 51403FC4YA00 front spacer permitted. Front Damper Mount P/N 51920-F23S-A30 is allowed. Allow rear sway bar Progress # 62.1061 Allow Injen Intake SP1512, K&N Intake 69-1017TTK, or HPS intake 827-102 with a 25lb adder. Allow Acuity Shifter Base Bushing Kit 1954 Two pedal shutdown may be disabled by cutting/de-pinning pin 42 (BKSW) at the main ECU connector in the engine bay.~~*Approved parts: Progress rear sway bar #62.1061, Injen Intake SP1512, K&N Intake 69-1017TTK, or Weapon R Intake 301-166-301, Acuity shifter bushing kit 1954. World Challenge suspension kit permitted but no longer available. Two pedal shutdown may be disabled by cutting/de-pinning pin 42 (BKSW) at the main ECU connector in the engine bay.*"

In B-Spec Spec Lines, Honda Fit AT (09-14), change Notes as follows:
"~~Allow damper and spring set 51600F23SA100, Damper FR LH 51605F23SA100, Damper FR RH 51606F23SA100, Damper RR 52610F23SA100, Spring adjust asy RR 52691F23SA010. Seat upper FR spring 51688F23SA200, 51402FC4YA00 front helper spring and 51403FC4YA00 front spacer permitted. Front Damper Mount P/N 51920-F23S-A30 is allowed. Allow rear sway bar Progress # 62.1061. Allow Setrab 50-119-7612 transmission cooler in addition to OEM. Any aftermarket exhaust/header allowed. Any Cold Air Intake Package allowed (any manufacturer). Weapon R Intake 301-166-301.~~*Approved parts: Progress rear sway bar 62.1061, Injen Intake SP1512, any aftermarket header, Setrab transmission cooler 50-119-7612. Two pedal shutdown may be disabled by cutting/de-pinning pin 42 (BKSW) at the main ECU connector in the engine bay.*"

In B-Spec Spec Lines, Honda Fit MT (15-19), change Notes as follows:
"~~Allow damper FR LH 51605F23SA81, Damper FR RH FR RH 51606F23SA81, Damper RR 52610F23SA80, Spring adjust assy RR 52691F23SA80, Camber Adjuster Comp, Damper 51920F23SA82. Allow rear sway bar Progress 62.1063.~~*Approved parts: Progress rear sway bar 62.1063.*"

In B-Spec Spec Lines, Honda Fit CVT (15-19), change Notes as follows:
"~~Allow damper FR LH 51605F23SA81, Damper FR RH FR RH 51606F23SA81, Damper RR 52610F23SA80, Spring adjust assy RR 52691F23SA80, Camber Adjuster Comp, Damper 51920F23SA82. Allow rear sway bar Progress 62.1063. Allow Setrab 50-119-7612 transmission cooler in addition to OEM.~~*Approved parts: Progress rear sway bar 62.1063, Setrab transmission cooler 50-119-7612. This configuration is not currently eligible for Runoffs competition. This car must compete in three separate Majors/Super Tour events so performance data can be collected. In addition to an SCCA data box, OBDII data collected via an AIM or similar device must be submitted.*"

In B-Spec Spec Lines, Hyundai Accent Hatchback (12-17), change Notes as follows:
"~~Allow AKSJ03-10-001 Damper Frt Assembly; AKSJ03-20-001 Damper-ASTRear; KSJ03-20-003 Rear Upper Spring Perch Delrin; AKSJ03-60-001 Sump Pan Extension. Allow rear torque bar Evilla Motorsports #KR-B1. Bilstein B8 shock 33- 187112 approved for use in rear suspension. Bilstein B14 kit #47167490 front shocks verified compatible. Allow BabyFace Fabrication sump extension #BF-HYU-PAN Vehicles equipped with rear drum brakes subtract 25 lb.~~*Approved parts: Evilla Motorsports rear torque bar KR-B1, BabyFace Fabrication sump extension BF-HYU-PAN. Vehicles equipped with rear drum brakes subtract 25 lbs.*"

In B-Spec Spec Lines, Hyundai Accent Sedan (12-17), change Notes as follows:
"~~Allow AKSJ03-10-001 Damper Frt Assembly; AKSJ03-20-001 Damper-AST-Rear; KSJ03-20- 003 Rear Upper Spring Perch Delrin; AKSJ03-60-001 Sump Pan Extension. Allow rear torque bar Evilla Motorsports #KR-B1. Bilstein B8 shock 33-187112 approved for use in rear suspension.~~*Approved parts: Evilla Motorsports rear torque bar KR-B1, BabyFace Fabrication sump extension BF-HYU-PAN. Vehicles equipped with rear drum brakes subtract 25 lbs.*"

In B-Spec Spec Lines, Kia Rio Hatchback (12-15), change Notes as follows:
"~~Allow AKSJ03-10-001 Damper Frt Assembly; AKSJ03-20-001 Damper-AST-Rear; KSJ03-20- 003 Rear Upper Spring Perch Delrin; AKSJ03-60-001 Sump Pan Extension. Allow rear torque bar Evilla Motorsports #KR-B1. Bilstein B14 kit #47167490 front shocks verified compatible. Allow BabyFace Fabrication sump extension #BF-HYU-PAN Bilstein B8 shock 33-187112 approved for use in rear suspension.~~*Approved parts: Evilla Motorsports rear torque bar KR-B1, BabyFace Fabrication sump extension BF-HYU-PAN. World Challenge suspension kit permitted but no longer available.*"

In B-Spec Spec Lines, Kia Rio Sedan (12-17), change Notes as follows:
"~~Allow AKSJ03-10-001 Damper Frt Assembly; AKSJ03-20-001 Damper-AST-Rear; KSJ03-20- 003 Rear Upper Spring Perch Delrin; AKSJ03-60-001 Sump Pan Extension. Allow rear torque bar Evilla Motorsports #KR-B1. Bilstein B8 shock 33-187112 approved for use in rear suspension.~~*Approved parts: Evilla Motorsports rear torque bar #KR-B1, BabyFace Fabrication sump extension BF-HYU-PAN.*"

In B-Spec Spec Lines, Mazda2 (10-14), change Notes as follows:
"~~Rear sway bar 0000-04-2203-RR or 0000-04-2312, Allow rear torque bar Corksport #Mz2- 3-070. Cold air intake Corksport Mz2-6-117-31100 and air duct Mz2-6-120-10 are allowed. Exhaust Header (cat delete) HB.EM 60-404-S-SS, HP-MZD001, allowed with a 50lb adder or Mazda Motorsports PN 0000-06-2410 with no weight adder permitted. Powerflex PFR19- 1511BX2 rear suspension bushings allowed. Allow Mazda part number 0000-01-2501-CR Radiator. Allow Mazda undertray part number DO8C-56-110A, DO8C-56-311, DO7A-56-321.~~*Approved parts: Mazda Motorsports rear sway bar 0000-04-2203-RR, Eibach/Mazda Motorsports rear sway bar 35143.312/0000-04-2312, Corksport rear torque bar #MZ2- 3-070, Corksport intake MZ2-6-117-31100, Corksport air duct MZ2-6-120-10, Powerflex PFR19-1511BX2 rear suspension bushings, Mazda Motorsports radiator 0000-01-2501-CR, Mazda Motorsports header 0000-06-2410, Mazda undertray/side shields DO8C-56-110A, DO8C-56-311, DO7A-56-321.*"

In B-Spec Spec Lines, Mini Cooper Hatchback (R50) MT (02-06), change Notes as follows:
"~~Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Allow rear sway bar Progress #62.0210.~~*Approved parts: Progress rear sway bar 62.0210, Mevotech leteral link CMK100003. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches.*"

In B-Spec Spec Lines, Mini Cooper Hatchback (R50) CVT (02-06), change Notes as follows:
"~~Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Allow rear sway bar Progress #62.0210.CVT equipped cars allow Setrab 50-119-7612 transmission cooler in addition to OEM.~~*Approved parts: Progress rear sway bar 62.0210, Mevotech leteral link CMK100003, Setrab transmission cooler 50-119-7612. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches.*"

In B-Spec Spec Lines, Mini Cooper (R56) MT (07-10), change Notes as follows:
"~~Allow L/F Strut-spring assembly 31 31 1 126, R/F Strut-spring assembly 31 31 1 125, Rear Shock-spring assembly 33 50 1 125. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Adjustable front camber plate part number 31 30 1 507 is allowed. Allow rear sway bar Progress #62.0210. OBX header part #10-2101-2S permitted.~~*Approved parts: Progress rear sway bar 62.0210, OBX header 10-2101-2S. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches.*

In B-Spec Spec Lines, Mini Cooper (R56) AT (07-10), change Notes as follows:
"~~Allow L/F Strut-spring assembly 31 31 1 126, R/F Strut-spring assembly 31 31 1 125, Rear Shock-spring assembly 33 50 1 125.Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Adjustable front camber plate part number 31 30 1 507 is allowed. Allow rear sway bar Progress #62.0210. OBX header part #10-2101-2S permitted. Automatic equipped cars only allow Setrab 50-119-7612 transmission cooler in addition to OEM.~~*Approved parts: Progress rear sway bar 62.0210, Setrab transmission cooler 50-119-7612. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. This configuration is not currently eligible for Runoffs competition. This car must compete in three separate Majors/Super Tour events so performance data can be collected. In addition to an SCCA data box, OBDII data collected via an AIM or similar device must be submitted.*"

In B-Spec Spec Lines, Mini Cooper Clubman (R55) (07-10), change Notes as follows:
"~~Allow L/F Strut-spring assembly 31 31 1 126, R/F Strut-spring assembly 31 31 1 125, Rear Shock-spring assembly 33 50 1 125. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Adjustable front camber plate part number 31 30 1 507 is allowed. Allow rear sway bar Progress #62.0210. OBX header part #10-2101-2S permitted.~~*Approved parts: Progress rear sway bar 62.0210, OBX header 10-2101-2S. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches.*

In B-Spec Spec Lines, Mini Cooper (R56LCI) MT (11-13), change Notes as follows:
"~~Allow L/F Strut-spring assembly 31 31 1 126, R/F Strut-spring assembly 31 31 1 125, Rear Shock-spring assembly 33 50 1 125. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Adjustable front camber plate part number 31 30 1 507 is allowed. Allow rear sway bar Progress #62.0210.~~*Approved parts: Progress rear sway bar 62.0210. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches.*"

In B-Spec Spec Lines, Mini Cooper (R56LCI) AT (11-13), change Notes as follows:
"~~Allow L/F Strut-spring assembly 31 31 1 126, R/F Strut-spring assembly 31 31 1 125, Rear Shock-spring assembly 33 50 1 125. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Adjustable front camber plate part number 31 30 1 507 is allowed. Allow rear sway bar Progress #62.0210. OBX header part #10-2101-2S permitted with 41mm FPR. Automatic equipped cars only allow Setrab 50- 119-7612 transmission cooler in addition to OEM.~~*Approved parts: Progress rear sway bar 62.0210, Setrab transmission cooler 50-119-7612. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. This configuration is not currently eligible for Runoffs competition. This car must compete in three separate Majors/Super Tour events so performance data can be collected. In addition to an SCCA data box, OBDII data collected via an AIM or similar device must be submitted.*"

In B-Spec Spec Lines, Mini Cooper Clubman (R55) (11-15), change Notes as follows:
"~~Allow L/F Strut-spring assembly 31 31 1 126, R/F Strut-spring assembly 31 31 1 125, Rear Shock-spring assembly 33 50 1 125. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Adjustable front camber plate part number 31 30 1 507 is allowed. Allow rear sway bar Progress #62.0210.~~*Approved parts: Progress rear sway bar 62.0210. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches.*"

In B-Spec Spec Lines, Mini Cooper Coupe (R58) (12-15), change Notes as follows:
"~~Allow L/F Strut-spring assembly 31 31 1 126, R/F Strut-spring assembly 31 31 1 125, Rear Shock-spring assembly 33 50 1 125. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. Adjustable front camber plate part number 31 30 1 507 is allowed. Allow rear sway bar Progress #62.0210.~~*Approved parts: Progress rear sway bar 62.0210. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches.*"

In B-Spec Spec Lines, Nissan Versa Sedan (2012-2019), change Notes as follows:
"~~Hardrace HR-Q0146 19mm rear sway bar permitted. Allow Injen intake SP1906.~~*Approved parts: Hardrace rear sway bar HR-Q0146, Injen intake SP1906.*"

In B-Spec Spec Lines, Nissan Versa Hatchback (2012-2019), change Notes as follows:
"~~Hardrace HR-Q0146 19mm rear sway bar permitted. Allow Injen intake SP1906.~~*Approved parts: Hardrace rear sway bar HR-Q0146, Injen intake SP1906.*"

In B-Spec Spec Lines, Nissan Versa (2020-), change Notes as follows:
"~~This configuration is not currently eligible for Runoffs competition. This car must compete in three (3) separate Super Tour weekends so that performance data can be collected. In addition to SCCA data box, OBDII data collected via an AIM or similar device must be submitted.~~*This configuration is not currently eligible for Runoffs competition. This car must compete in three separate Majors/Super Tour events so performance data can be collected. In addition to an SCCA data box, OBDII data collected via an AIM or similar device must be submitted.*"

In B-Spec Spec Lines, Toyota/Scion IA Sedan (16-20), change Notes as follows:
"~~This configuration is not currently eligible for Runoffs competition. This car must compete in three (3) separate Super Tour weekends so that performance data can be collected. In addition to SCCA data box, OBDII data collected via an AIM or similar device must be submitted. Allow ST Suspension Kit 1327502.~~*Approved parts: ST suspension kit 1327502. This configuration is not currently eligible for Runoffs competition. This car must compete in three separate Majors/Super Tour events so performance data can be collected. In addition to an SCCA data box, OBDII data collected via an AIM or similar device must be submitted.*"

In B-Spec Spec Lines, Toyota Yaris Hatchback (07-11), change Notes as follows:
"~~Speed sensor may be disconnected. Cold air intake K&N 69-8612TFK is allowed. Rear Swaybar PTR11-52071 is allowed.~~ *Approved parts: TRD rear sway bar PTR11-52071, K&N intake 69-8612TFK. Speed sensor may be disconnected.*"

In B-Spec Spec Lines, Toyota Yaris Hatchback (12-18), change Notes as follows:
"~~Rear Swaybar PTR11-52071 is allowed. Cold air intake K&N 69-8612TFK is allowed. Speed sensor may be disconnected. Vehicles equipped with rear disc brakes add 25 lb.~~*Approved parts: TRD rear sway bar PTR11-52071, K&N intake 69-8612TFK. Speed sensor may be disconnected. Vehicles equipped with rear disc brakes add 25 lbs.*"

In B-Spec Spec Lines, Toyota Yaris Sedan (07-12), change Notes as follows:
"~~Rear Swaybar PTR11-52071 is allowed. Cold air intake K&N 69-8612TFK is allowed. Speed sensor may be disconnected.~~
Approved parts: TRD rear sway bar PTR11-52071, K&N intake 69-8612TFK. Speed sensor may be disconnected."

2. #39475 (B-Spec/C-Spec Committee) 2026 BOP Recommendations
In B-Spec Spec Lines, change as follows:
Chevrolet Sonic Sedan AT (12-19):
Restrictor (mm) & Type: "~~35 FPR~~"

Chevrolet Sonic Hatchback AT (12-19):
Restrictor (mm) & Type: "~~35 FPR~~"

Honda Fit MT (09-14):
Weight (lbs): "~~2525~~*2550*"
Honda Fit CVT (15-19):
Restrictor (mm) & Type: "~~33 FPR~~"

Mini Cooper Hatchback (R50) MT (02-06):
Weight (lbs): "~~2545~~*2525*"

Mini Cooper (R56) MT (07-10):
Restrictor (mm) & Type: "FPR ~~45~~*47* OE Catalyst"

Mini Cooper (R56) AT (07-10):
Restrictor (mm) & Type: "~~47 FPR (OE Catalyst) 42 FPR (Header)~~"

Mini Cooper Clubman (R55) (07-10):
Restrictor (mm) & Type: "FPR ~~45~~*47* OE Catalyst"

Mini Cooper (R56LCI) MT (11-13):
Restrictor (mm) & Type: "FPR ~~44~~*46*"

Mini Cooper (R56LCI) AT (11-13):
Restrictor (mm) & Type: "~~46 FPR (OE Catalyst) 41 FPR (Header)~~"

Mini Cooper Clubman (R55) (11-15):
Restrictor (mm) & Type: "~~FPR 44~~*46*"

Nissan Versa Sedan (2012-2019):
Min weight: "~~2450~~*2425*"

Nissan Versa Hatchback (2012-2019):
Min weight: "~~2450~~*2425*"

Nissan Versa (2020-):
Restrictor (mm) & Type: "~~38 FPR~~"

Toyota/Scion IA Sedan (16-20):
Restrictor (mm) & Type: "~~38 FPR~~"

3. #39582 (B-Spec/C-Spec Committee) Expire NLA Mazda 2 Headers
In B-Spec Spec Lines, Mazda2 (10-14), change Notes as follows:
"Exhaust Header (cat delete) ~~HB.EM 60-404-S-SS, HP-MZD001, allowed with a 50lb adder or~~ Mazda Motorsports PN 0000-06-2410 with no weight adder permitted."

Electric Vehicle
None.

Formula/Sports Racing
FA
1. #38223 (Ove Olsson) Alternate Intake Manifold for MZR
In FA, GCR section 9.1.1.2.d, modify as follows:
"9. Intake manifold must be unmodified Elan DP02-60-003 or Mazda Speed equivalent Elite USF2015AT, 1.882" maximum bore diameter at throttle plates. *Elan or Mazda Speed equivalent Elite intake manifold may be replaced with unmodified intake Noor P/N 0088-8-00 with intake runners AT Power P/N 13624.*"

"10. *Elan DP02-60-003 or Mazda Speed equivalent Elite USF2015AT intake manifold must use an* ~~A~~*a*luminum spacer ~~must be used~~ between *the* intake manifold and cylinder head castings; minimum spacer length *is* 2.200"."

2. #39302 (Reilly Harris) Engine Compression Rule Change Request
In FA Table 2, Formula 1000 spec line, change the Engine as follows:
"Motorcycle-based 4-cycle up to 1000cc~~, maximum compression ratio 14.5:1;~~. ~~o~~*O*therwise, current FA engine rules apply."

3. #39608 (Club Racing Board) Change Formula 1000 allowances
In FA Table 2, Formula 1000 spec line, change the Notes as follows:
"Car must comply with December 2019 GCR Formula 1000 (FB) Preparation Rules, https://www.scca.com/downloads/48184-gcr-december-2019/download, except as modified by this spec line. *The prohibition of using carbon fiber in any external panels or any panels licked by the airstream in Part 3.C of the December 2019 GCR F1000 (FB) Preparation Rules is removed, with the exception that the car's floor pan/undertray must comply with the requirements of Part 2.D of the December 2019 GCR F1000 (FB) Preparation Rules. The prohibition of forward-facing gaps or openings in the bodywork in Part 3.I of the December 2019 GCR F1000 (FB) Preparation Rules is removed. Part 3.D of the December 2019 GCR F1000 (FB) Preparation Rules is modified as follows: "Between the rear of the front tire and the front of the rear tire, no point on the lower surface of the car (the surface licked by the air stream) shall be more than 125mm above the plane determined by the reference area designated by the entrant and on a line perpendicular to that reference plane." Part 3.D of the December 2019 GCR F1000 (FB) Preparation Rules is also modified as follows: "A maximum of eight (8) rub blocks of maximum dimension 75mm by 125mm are allowed anywhere on the lower surface of the chassis and may extend below the reference plane." Part 3.E of the December 2019 GCR F1000 (FB) Preparation Rules is modified as follows: "The radius of transitions between the diffuser sides and adjacent horizontal structures*

may be up to 75mm. The width of the diffuser, as measured between its sides and above any radiused transitions, may not exceed 110cm in any lateral section." The CRB may require the use of Flat Plate Intake Restrictors at any time."

FC

1. #38927 (Rock Beauchamp) F2000 MZR Spec Line Clarity/Revision Requested
In FC Charts table, USF2000 Tube Frame spec line, add the following to the Notes:
"*Cars originally built with the Hewland LD200 4-speed H-pattern may use that transmission as an alternative to the Hewland JL-200 5-speed sequential transmission.*"

2. #39612 (Club Racing Board) Adjust F2000 Metrik ZF2 weight
In FC Charts table, F2000 Metrik ZF2 spec line, change the Weight as follows:
"~~1240~~*1220*"

FE

1. #39484 (Robey Clark) FE & FE2 Rule Updates
In FE, GCR section 9.1.1.G.2.G.a.1, add the following:
"NO MODIFICATIONS ARE ALLOWED EXCEPT WHERE SPECIFICALLY AUTHORIZED WITHIN THESE RULES. This includes all fuel injection and engine management components, including exhaust, cooling, electrical and lubrication systems. All systems are subject to test procedures and must conform to OEM */ SCCA Enterprises* specifications as stated and supplied by Enterprises. All fluids, except fuel, are unrestricted."

In FE, GCR section 9.1.1.G.2.T, add the following:
"If a competitor refuses to give their engine and/or unlabeled parts for testing per a request of the *Class Compliance Chief (CCC) or* Chief Steward, the following penalties will automatically be imposed:"

In FE, GCR section 9.1.1.G.2.T.d, add the following:
"The car and drivetrain are suspended from competition until the unit(s) specified by the *CCC or* Chief Steward are replaced."

In FE, GCR section 9.1.1.G.2.T, add a new section as follows:
"*g. Any drivetrain part found to be out of spec, during voluntary or involuntary inspection, will constitute a Drivetrain Violation. Penalties may be assessed post event.*"

FF

1. #39281 (Jay Messenger) Formula F Alternative Tire Rule Proposed Clarifications
In FF, GCR section 9.1.1.B.10.e, change as follows:
"Alternatively, Formula F cars ~~with rocker arm suspension (e.g., 1987-90 Reynard, Swift DB1,) and/or outboard suspension on at least one chassis end~~ *homologated in 1989 or earlier with any combination of rocker arm or outboard suspension on all four corners (e.g., 1987 – 1990 Reynard, Swift DB1)* may use the following alternative tires. *Note: This rule is intended to allow older cars with the described suspension design to use the alternative tires. It is not to be exploited by modifying cars with push-rods or pull-rods to meet the above requirements or by modifying either end of older cars to push- or pull-rod suspension to be eligible to run the alternative tires. Cars that were homologated in 1989 or earlier with push- or pull-rod suspension on no more than two corners may seek approval to run the alternative tire by utilizing the compliance process outlined in GCR section 8.1.4.*"

P

1. #39476 (Jeffrey Lederman) Request to Continue to Allow Carbon Brakes
In Prototype, GCR section 9.1.8.B.F.2, change as follows:
"Brake calipers may be ferrous or aluminum alloy. ~~Effective 1/1/2026, carbon-carbon and carbon-ceramic brake rotors are prohibited and rotors must be ferrous.~~*Brake rotor material is unrestricted*."

GCR

1. #39064 (Phil Croyle) Request to Add a Numbered Paragraph 9 to App. P
In Appendix P. Racing Room & Passing Guidelines, Part 1, add the following:
"Safe, successful passing is based on what drivers can see. An overtaking car bears the largest percentage of ~~responsibly~~*responsibility* for passing safely. *This responsibility is met and a pass is successfully completed when the overtaking car is completely, physically past the car being overtaken. Simply being ahead, while still alongside, does not absolve the driver of the overtaking car of the obligation to allow racing room to the overtaken car. At the same time, the overtaken driver must not impede or block the overtaking car but is not required to fall back as long as the driver provides racing room to the overtaking car.*"

General

None.

Grand Touring

GT1

1. #39311 (Taz Harvey) NSX Parity With Other GT3s Let Alone a GT1 Car
In GT1-ST, Acura NSX GT3 EVO 22, change Weight as follows:
"~~3100~~*3000*"

GT2

1. #39086 (Samuel Daniels) Additional Body Options to Replace Older Stock Car Bodies
In GCR, Section 4.8.4.2.1., add the following:
"Cars in the class must use 1997, through current year, commercially available stock car bodywork. The following make/model bodies are allowed:
1. Cadillac CTS
2. Chevrolet Impala
3. Chevrolet Malibu
4. Chevrolet Monte Carlo
5. Chevrolet SS
6. Dodge Intrepid
7. Ford Fusion
8. Ford Taurus
9. Lincoln MKS
10. Pontiac G8
11. Pontiac GTO
12. Pontiac Grand Prix
13. Toyota Camry

Gen late Model Stock Car Bodies are allows:
1. Chevrolet Camaro
2. Ford Mustang
3. Toyota Camry"

2. #39365 (Chris Edens) GT3 Turbo to GT2?
In GT2 Spec Lines, Engines - MAZDA, classify Engine Family BP as follows:

GT2 Engines - *MAZDA*								
Engine Family	Engine Type	Bore x Stroke (mm)	Disp. (CC)	Head Type	Valves / Cyl.	Fuel Induction	Weight (lbs)	Notes
BP	*DOHC*	*83x85*	*1839*	*Alum, Crossflow*	*4*	*46mm TIR*	*2250*	*EFR6258 or EFR7163 Turbo Charger allowed*

3. #39537 (Grand Touring Committee) Tech Bulletins for GT2 and GT2-ST
In GT2 Spec Lines, GT2 Cars – Porsche**,** classify 992.1 GT3 Cup as follows:

GT2 Cars – Porsche					
Model	**Year**	**Body Style**	**Driveline**	**Wheel Base**	**Notes**
992.1 GT3 Cup	*(22-25)*	*2 Dr*	*RWD*		*4.0L flat six. 3250lbs. w/60mm Throttle Body Restrictor (TBR). Cars must be prepared in accordance with the appropriate model/year Porsche factory 911 GT3 Cup parts catalog/service manual. Cars may not be altered in any way except as authorized below. Drivers must have the correct year manuals as they apply to their specific car in their possession. Safety, drivers comfort, driver control and instrumentation items may be modified per the GCR. Original factory installed Matter/ IMV roll cages are allowed. The stock unmodified fuel tank is allowed. Windshield clips must be installed per GCR 9.3 Windshield Clips/Rear Window Straps. All other SCCA safety standards apply. Tires per GCR 9.3 Tires. Lubricants, consumable fluids (brake fluid, coolant etc.) and oil filters are open free. Factory (OEM manufacturer) Lexan front windows allowed as delivered. ABS is allowed.*

In GT2 Spec Lines, GT2 Cars – Porsche, change Notes as follows:
991.1 GT3 Cup: "3.8L flat six. 3000lbs. ~~w/72mm Throttle Body Restrictor (TBR).~~ *Aftermarket header allowed.*"
991.2 GT3 Cup: "4.0L flat six. 3000lbs. w/~~65mm~~*70mm* Throttle Body Restrictor (TBR)."
997.2 GT3 Cup: "3.8L flat six. ~~2900~~*2800* lbs. *Aftermarket header allowed.*"

In GT2 Spec Lines, GT2 – ST, Chevy Corvette (-2013), change as follows:
5665:
Restrictor: "~~81~~*85*mm flat plate"
Notes: "GM LS1, LS6. LS1/LS6 C6 Corvettes using the OEM C6 intake manifold and 90 mm throttle body must use a ~~78mm~~ flat plate restrictor. OEM 75mm throttle body and manifold do not require a restrictor. ~~LS6 may reduce weight by 50 lbs.~~ LS1/LS6 alternate intake manifold, DORMAN part # 615-900."
LS2 5967 Restrictor: "~~83~~*85*mm "
L76 5967 Restrictor: "~~80~~*83*mm flat plate"
LS3 6162 Restrictor: "~~80~~*83*mm flat plate"
6162 GM LS3:
Weight: "~~3250~~*3150*"
Restrictor: "~~74~~*80*mm flat plate"
6162 GM LT1:
Weight: "~~3250~~*3150*"
Restrictor: "~~74~~*77*mm flat plate"

In GT2 Spec Lines, GT2 – ST, Chevy Corvette (14-19), change as follows:
5665:
Restrictor: "~~83~~*85*mm flat plate"
Notes: "GM LS1, LS6. LS1/LS6 C6 Corvettes using the OEM C6 intake manifold and 90 mm throttle body must use a ~~78mm~~ flat plate restrictor. OEM 75mm throttle body and manifold do not require a restrictor. ~~LS6 may reduce weight by 50 lbs.~~ LS1/LS6 alternate intake manifold, DORMAN part # 615-900."
LS2 5967:
Weight: "~~3100~~*3000*"
Restrictor: "~~83~~*85*mm flat plate"
L76 5967 Restrictor: "~~80~~*83*mm flat plate"
6162 Restrictor: "~~80~~*83*mm flat plate"
6162 LS3:
Weight: "~~3200~~*3100*"
Restrictor: "~~77~~*80*mm flat plate"
6162 LT1:
Weight: "3~~200~~*3100*"
Restrictor: "~~74~~*80*mm flat plate"

GT3
1. #39637 (Grand Touring Committee) GT3U Ride Height
In GCR, Section 9.1.2.F.3., add the following:
"10. All GT3 cars running in STU must meet the minimum ride height of 3.0" for the main frame rails not including rub blocks and a 2" minimum for the front spoiler and splitter."

GTX

1. #39470 (Peter Jankovskis) Please Consider Adding a Spec Line to GTX Table 4 for the RCR T70
In GTX-Misc. Table 4, classify RCR70 Coupe:

GTX – MISC. ***TABLE 4***					
Make	Homologation	Model	Restrictor (mm)	Weight (lbs)	Notes
RCR T70 Coupe				*2200*	

Improved Touring

ITR

1. #39105 (David Gomberg) Correct Response to Letter 38971 in October Tech Bulletin
In ITR Spec Lines, MW 325i/is (92-95, change Notes as follows:
"A NASA Spec3 BMW can run in SCCA ITR if it stays at the NASA specs. Competitor needs to provide current NASA rules for car *compliance* in SCCA. Weight is ~~2900~~*2825* pounds."

Legends Car

None.

Production

EP

1. #39363 (Tim Schreyer) Request to Update E30 BMW Throttle Body Diameter Verbiage
In EP Spec Line BMW 325i/is E30 (84-91), change Drivetrain Notes as follows:
"Fuel Injection*, TB: 60mm*"

HP

1. #39500 (Robert Bax) E/O: Improve Consistency of the Spec Lines
In HP Spec Line, Toyota MR-2 1.6L (85-89), change Comp. Ratio as follows:
"11*.0*:1"

2. #39567 (Jonathan Kinberg) Request to Reclassify BMW 2002 Into H Production
In HP Spec Lines, classify BMW 2002, as follows:

HP	Prep. Level	Weight (lbs)	Engine Type Mat'l Block/ Head	Displace-ment Bore x Stroke mm/ (in.)	Drivetrain Notes	Chassis Notes	Wheel-base mm/ (in.)	Track (F/R) mm/ (in.)
BMW 2002	*2*	*2350*	*4 cyl SOHC Iron/ Alum*	*1990 (121.39) 89.0x80.0 (3.50x3.15)*	*Carburetion (1) 40 DCNF w/32mm choke(s) Orientation of the alternate carburetor is unrestricted. The alternate carb adapter may not be thicker than 1.25". The adapter may have a bore larger than the throttle bore of the approved alternate carburetor. Valve Size: (I) 46.0/(1.81) (E) 38.0/(1.50) Comp. ratio 11.0:1, Valve lift .425" Trans. Speeds: 4*	*Wheels: 15x7 Brakes Std: Factory spec @ all 4 wheels.*	*2499 (98.4)*	*1430/1430 (56.3/56.3)*

Spec Mazda (SM/SMX)
None.

Super Production
None.

Super Touring
STL
1. #39579 (Super Touring Committee) Weight adjustment for STL
In GCR, Section 9.1.4.2.H.1. change Minimum Weight on chart as follows:
"1300: ~~1755~~*1950*
1350: ~~1823~~*2000*
1400: ~~1890~~*2050*
1450: ~~1958~~*2100*
1500: ~~2025~~*2150*
1550: ~~2093~~*2200*
1600: ~~2160~~*2250*
1650: ~~2228~~*2300*
1700: ~~2295~~*2350*
1750: ~~2363~~*2400*
1800: ~~2430~~*2450*
1850: 2498*2500*"

STU

1. #39529 (John Grim) Request for Permission on Aftermarket Turbo Kit and Intake
In STU Spec Lines, Table A: Alternate Vehicle and Engine Allowances, Mazda MZR (LF, L3, L5), change Notes as follows:
"Short blocks, heads, and intakes may be freely swapped within these engine designations. May use Goodwin Part # 61-2510 ~~or~~*,* Gato Performance Part # 31972 *or Jack Spania Racing 70 mm sheet-metal aluminum* Intake manifold. Must use stock throttle body or Acura part number 16400-PND-A17."

In STU Spec Lines, Table A: Alternate Vehicle and Engine Allowances, classify Mazda MZR (LF, L3, L5) Turbo as follows:

STU	Maximum Displacement (cc's)	Minimum Weight	Notes
Mazda MZR (LF, L3, L5) Turbo	*Varies*	*Chart*	*Short blocks, heads, and intakes may be freely swapped within these engine designations. May use Jack Spania Racing 70 mm sheet-metal aluminum Intake manifold. Must use stock throttle body or Acura part number 16400-PND-A17. Fab9 Tuning bottom-mount turbo kit approved with one of the STU approved Turbos.*

Touring

T1

1. #39520 (Touring Committee) additional T1 adjustment
In T1 Spec Line, Spec line # 1132, change Restrictor as follows:
"~~70mm - Flat Plate~~"

T2

1. #39426 (John Heinricy) Rebalance Blackwing Cadillac T2 for 2026
In T2 Spec Lines, Cadillac CT4-V Blackwing (2022-), change Weight as follows:
"~~3800~~*3750*"

2. #39472 (Brian LaCroix) C6 LS2 Corvette Parity Request
In T2 Spec Lines, Chevrolet Corvette C6 Coupe / Grand Sport (05-13), change Restrictor as follows:
"LS2: ~~67mm~~*80mm* FPR LS3: 56mm FPR"

3. #39490 (Scotty B White) T2 Tire Sizing
In T2 Spec Lines, Dodge Viper SRT10 incl. coupe (03-06), change Weight as follows:
"~~3675~~*3650*"

4. #39499 (Andrew Aquilante) Rear Spoiler for Mustang GT S550 (15-23)
In T2 Spec Lines, Ford Mustang GT 5.0L (2015-2023), add to Notes the following:
"*Ford* Track/Performance Package parts permitted. *Performance pack aero parts #M-16600-FP and #M-16601-MPP permitted.*"

T2-T4

1. #39370 (Aaron Stehly) Alternate Placement of Fuse Panel and Electronics Request
In GCR, Section 9.1.9.2.D.9.d, add the following:
"*8. Under-dash electronics including computers, modules and fuse boxes may be relocated so they can be easily accessed after roll cage installation.*"

1. #39503 (David Mead) Clarify T4 Brake Rotor Allowance
In GCR, Section 9.1.9.2.D.6.a.6., change as follows:
"In T2-Performance alternative rotors, including 2 piece rotors are permitted. Rotors must be within 5% of OE diameter or a maximum diameter of 360mm.

In T3- Performance alternative rotors, including 2 piece rotors are permitted with a maximum diameter of 360mm.

T4- Performance alternative *1-piece* rotors are permitted but rotors must meet the sizes listed in the spec line. *Spec lines showing alternate brake kits are also permitted to use 1-piece performance alternative rotors of the same size.*"

T3

1. #39196 (Roger Eagleton) Request to Allow Spec Mustang to Touring 3 in Appendix M Trim
In T3 Spec Lines, Ford Spec Mustang, change as follows:
Restrictor: "Two ~~44mm~~*45mm* holes"
Weight: "~~3450~~*3400*"

2. #39222 (Benjamin Phillips) Tire Help for Spec E9X in T3
In T3 Spec lines, BMW Spec 9X, change as follows:
Car: "~~BMW Spec 9X~~*BMW Spec E9X*"
Notes: "Must conform to all SpecE9X rules Version 2.10. Spec E9X spec tire permitted or any DOT permitted up to ~~225~~*255* permitted. No other touring allowances permitted. Engines may not be modified unless specified in the Spec E46 rules and must conform to touring tech procedures. Driver must possess a current copy of the rules. Dyno results do not ensure engine compliance. THIS SPEC LINE DOES NOT QUALIFY FOR SCCA RUNOFFS COMPETITION UNTIL IT HAS BEEN REPRESENTED IN 3 SCCA SUPER TOUR EVENTS."

3. #39292 (Rob Piekarczyk) SpecE46 Tire Sizing
In T3 Spec Lines, BMW SpecE46, change Notes as follows:
"Must conform to all SpecE46 rules Version 3.0. SpecE46 spec tire permitted or any DOT permitted up to ~~225~~*245* permitted. No other touring allowances permitted. Engines may not be modified unless specified in the Spec E46 rules and must conform to touring tech procedures. Driver must possess a current copy of the rules. Dyno results do not ensure engine compliance. SE46 HP limit does not apply."

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

CLUB RACING BOARD MINUTES | January 5, 2025

We appreciate the feedback and perspectives that our members provide, and we'd like to thank you for your outreach and being part of the process. Should you have any requests or feedback to share with the Club Racing Board or a class advisory committee, please visit https://crbscca.com/ to submit a letter.

The Club Racing Board met by teleconference on January 5, 2025. Participating were Dayle Frame, Chairman; David Arken, David Locke, Jim Goughary, Peter Keane, Sam Henry, Tom Start, Tony Ave and Shelly Pritchett, secretary. Also participating were: Michael Cobb, President / CEO, Bob Crawford, BoD Chairman, David Brown, Mark Weber and Sam Fouse, BoD liaisons; Eric Prill, Vice President, Road Racing, Sydney Davis Yagel, Senior Manager of Race Operations, Scott Schmidt, Road Racing Technical Manager, Scott Dobler, Road Racing Series Manager. The following decisions were made:

Member Advisory
None.

No Action Required
B-Spec
1. #39551 (Richard Hromin) Mini Coupe Needs Help
We will continue to monitor the results and data for this vehicle.

FC
1. #39658 (Paul MacFarlane) Objection to the Proposed Reclassification of the FMzR into FC
Please see the response to letter #39161 in the current Fastrack.

2. #39659 (Andrew Gamble) No FA cars into FC
Please see the response to letter #39161 in the current Fastrack.

3. #39660 (Trevor Williams) Concerns Regarding the Proposed Reclassification of the Formula M
Please see the response to letter #39161 in the current Fastrack.

4. #39661 (Robert Wright) FMzR Application
Please see the response to letter #39161 in the current Fastrack.

5. #39662 (John Spinello) Concerns Regarding the Proposed Reclassification of the Formula M
Please see the response to letter #39161 in the current Fastrack.

6. #39663 (Dave Weitzenhof) Do not let FMzR into Formula Continental
Please see the response to letter #39161 in the current Fastrack.

7. #39664 (Dave Weitzenhof) FMzR int FC proposal
Please see the response to letter #39161 in the current Fastrack.

8. #39665 (Miles Crabbe) FMzR addition to FC
Please see the response to letter #39161 in the current Fastrack.

9. #39666 (Carmelo Crisafulli) Proposed Reclassification of the Formula Mazda (FMzR) into FC
Please see the response to letter #39161 in the current Fastrack.

10. #39667 (Barbara Crisafulli) Proposed Reclassification of the Formula Mazda (FMzR) into FC
Please see the response to letter #39161 in the current Fastrack.

11. #39668 (Terry Hanushek) Oppose FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

12. #39670 (Dane Babkirk) Rule Change/Class Addition
Please see the response to letter #39161 in the current Fastrack.

13. #39672 (Brian Tomasi) Memo to the Competition Board on FC
Please see the response to letter #39161 in the current Fastrack.

14. #39673 (Brendan Puderbach) FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

15. #39674 (Joseph Atkinson) Objections Regarding the Reclassification of the FMzR To FC
Please see the response to letter #39161 in the current Fastrack.

16. #39677 (Joe Fisher) Do not Allow FMzR Cars in FC
Please see the response to letter #39161 in the current Fastrack.

17. #39681 (Taylor Stein) FMzR Inclusion in FC
Please see the response to letter #39161 in the current Fastrack.

18. #39682 (Jeremy Swank) Oppose Reclassification of FMzR from FA to FC
Please see the response to letter #39161 in the current Fastrack.

19. #39683 (Tim Minor) FMzR to FC
Please see the response to letter #39161 in the current Fastrack.

20. #39685 (Rick Silver) Opposed to FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

21. #39686 (Jerry Weida) FMzR Cars in FC
Please see the response to letter #39161 in the current Fastrack.

22. #39687 (Connor Loughead) Against Inclusion of FMzR with FC
Please see the response to letter #39161 in the current Fastrack.

23. #39688 (Wren Keith) Do Not Allow the FMzR into FC
Please see the response to letter #39161 in the current Fastrack.

24. #39689 (Mark Defer) Allowing FMzR into FC
Please see the response to letter #39161 in the current Fastrack.

25. #39690 (Brian Styczynski) "Formula" Should Mean Something
Please see the response to letter #39161 in the current Fastrack.

26. #39692 (Rockford Beauchamp) Letter Against Putting the FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

27. #39693 (Dave Weitzenhof) Again, Classifying FMzR in FC Will Cause a LOT of Issues - Below
Please see the response to letter #39161 in the current Fastrack.

28. #39696 (Jim Roberts) FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

29. #39697 (Megan Sauce) Concern for Reclassification of FMzR into FC
Please see the response to letter #39161 in the current Fastrack.

30. #39698 (Kevin Kopecky) FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

31. #39700 (Alex Tollefsen) Concerns Regarding the Proposed Reclassification of Formula Mazda
Please see the response to letter #39161 in the current Fastrack.

32. #39703 (Robert Verenna) Objection to FMzR being added to FC
Please see the response to letter #39161 in the current Fastrack.

33. #39704 (Stanley Hallock) Opposed to FMzR Being in FC Class
Please see the response to letter #39161 in the current Fastrack.

34. #39705 (Steven Litsky) FC. re FMzR
Please see the response to letter #39161 in the current Fastrack.

35. #39707 (Ethan Mackey) No to FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

36. #39708 (Jonathan Lee) No FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

37. #39709 (James Lee) NO FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

38. #39710 (Matt Boian) FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

39. #39712 (Curtis Easterling) FMzR in FC
Please see the response to letter #39161 in the current Fastrack.

40. #39714 (John LaRue) FMzR into FC
Please see the response to letter #39161 in the current Fastrack.

41. #39718 (Philip Creighton) Mazda FMzR proposed for FC
Please see the response to letter #39161 in the current Fastrack.

42. #39733 (Sam Collier) Letter Re: FC Class Rules
Please see the response to letter #39161 in the current Fastrack.

P2
1. #39533 (TIMOTHY DAY) P2 Achieving Parity In Class
Please see the response to letter #39528 in the current Fastrack.

2. #39534 (Eric O'Brien) Support of Letter 39528
Please see the response to letter #39528 in the current Fastrack.

3. #39535 (Brian Lindstrand) I Support Letter 39528
Please see the response to letter #39528 in the current Fastrack.

4. #39536 (William Niemeyer Jr) Parity for P2
Please see the response to letter #39528 in the current Fastrack.

5. #39538 (John MacIntyre) Balance of Power
Please see the response to letter #39528 in the current Fastrack.

GCR
1. #39599 (Thomas Jackson) Request for Professional Editing of the General Competition Rules
The CRB and National Staff recognize that the GCR has arrived in its current form in primarily two ways:

1. The tens of thousands of suggestions for rules modification that come from the membership over the years.
2. The fact that hundreds of volunteer members have been the editors through their service on the CRB as well as the various Advisory Committees (ACs).

With these two groups of authors comes inconsistent language and technical document structure that continues to shift as we move forward in a digital age. The first sentence of *GCR 1.2.3 Interpreting and Applying the GCR* covers tortured interpretations and prevents creative members from using the inconsistent wording in unintended ways. *GCR 8.1.4 Compliance Review Rule Clarification* provides avenues of interpretation and clarification for members.

While a full rewrite and design may seem easy to some, it will be an incredibly difficult and huge undertaking. It's currently beyond what the Club management feels is a best use of time and resources. That said, plans and research are underway to find a more user-friendly solution that may also solve some of these issues mentioned above. This is scheduled to be rolled out in 2027.

In the meantime, the Club continues to welcome members to use the Letter Log System to suggest changes to these language and technical structure issues.

GT2
1. #39562 (Tom Scarpello) Weight for C7 Corvette with LS7
With the information that you have provided, 3300 lbs. with a 71mm flat plate restrictor as shown in the December 2025 GCR is listed. Your 3500 lbs. weight question cannot be found.

FP
1. #39606 (Craig Chima) Proposed Adjustments to FP Miata
The adjustments that were recently made in FP are going to remain for the start of the 2026 season. The impact of those changes on the overall competition balance of the class will be closely monitored, and additional adjustments could be made if necessary.

2. #39756 (James Bell) Allow 13X7 Wheels
Per Appendix G.2.3, the indicated wheel width and diameter on a spec line "are absolute maximums". Therefore, if the spec line says "Wheel: 15x7" then that is the maximum size wheel that is allowed, so a 13x7 wheel would already be legal within that limit.

T2
1. #39609 (Harley Kaplan) 240i Tuning
The rules currently require the car "must be as homologated from BMW Motorsports." This homologation includes ECU programming. It is not legal to change it.

T4
1. #39585 (Scotty B White) 4.0L T4 Mustang E & O
The Tremec transmission originally equipped in the 2005 Mustang base had the gear ratios shown in the spec line.

<u>Not Recommended</u>
B-Spec
1. #38895 (James Rogerson) Allow Two Pedal Delete for Honda Fit 2015-
We were unable to confirm that this was the correct procedure to disable the two pedal shut down for this car.

2. #39565 (James Rogerson) Adjustable Throttle Restrictor Plates
The BSAC does not recommend this change.

FC
1. #39161 (Moses Smith) Reclassify FMzR to FC Updated
The Club Racing Board does not recommend this change because the FMzR uses a number of major components that fall outside the general FC rules. In situations where a disparity in performance exists within a class for a particular car, competitors have sometimes organized an unofficial championship for that car type within their class and/or recognized individual competitors' performance by awarding separate trophies and taking their own podium photos. This has worked well both regionally and nationally but does require organization on the racers' part.

2. #39350 (John Janssen) Request to Adjust Classification of the USF2000 MZR Package
The Club Racing Board does not recommend this change. FC is a restricted class. The MZR is not an approved engine under the general FC rules, and neither is a 5-speed an approved transmission. This combination has been allowed in a spec line only in the

USF2000 tube frame chassis based on that package's specific performance level. To separate the MZR engine and its 5-speed transmission from the USF2000 chassis spec line would require the creation of a new spec line, which is expressly disfavored under the FC rules.

3. #39376 (Steve Thomson) Proposed Rule Change
The Club Racing Board does not recommend this change. FC is a restricted class. The combination of the MZR engine with a 5-speed transmission has been allowed in a spec line only in the USF2000 tube frame chassis based on that package's specific performance level. The relative parity between the Zetec engine and the MZR engine with the current restrictor is just one component. The 5-speed transmission in that combination remains outside the FC ruleset and would require the creation of a new spec line, which is expressly disfavored under the FC rules.

P2
1. #39528 (Jason Hohmann) P2 Achieving Parity In Class
The Club Racing Board does not recommend these changes at this time. The CRB is aware of concerns about the performance levels of these platforms and will gather data during the 2026 season to determine if adjustments are warranted.

General
1. #39378 (Stephen Blethen) Request to Make SCCA National Championship More Competitive
At this time, the 115% rule will be used for the Hoosier Tire SCCA Super Tour and the SCCA National Championship Runoffs competitions to ensure that drivers are on pace with the front runners. The Race Directors and Clerks of the Course for both HSTs and the Runoffs will be keeping an eye on drivers who are failing to meet the 115% requirement, and provisions are being considered for inclusion in the supplemental regulations. Our goal is to allow maximum, safe, and fair participation for all SCCA eligible drivers.

2. #39379 (Stephen Blethen) Request to Make SCCA National Championship More Competitive #2
Please see letter # 39378 in current Fastrack.

3. #39532 (Roy Lipner) Runoff Rules Placing T1 Class on Probation-National Championship
The Runoffs probation rules were established to ensure that a driver winning a class that experiences a one-year dip in Runoffs event participation would not be penalized for a potential anomaly. A second year below the 10-car threshold is indicative of a trend or more significant issue. The CRB believes that adjustments made to Touring 1 set it up for success in 2026, where it will again be included at the Runoffs in a combined group with GT-1. The GCR stipulates that if the class reaches 10+ cars at the Runoffs, it will move off of probation and crown a National Champion.

SMX5
1. #39588 (Marc Cefalo) Allow Penske T4 shock in SMX
SMAC does not recommend this change at this time. SMAC believes that keeping all competitors on the same (not similar) equipment is the best path moving forward for overall success and growth of the class. Penske does offer a path to take the T4 non-adjustable shock and convert it to a sealed SMX adjustable shock for those wishing to convert.
T2-T4
1. #39200 (Barry Borgschatz Jr) Roll Cage Dash Bar
The rules currently require a cross-dash bar in T3 and T2. It is an option in T4. Making it a requirement would be a severe hinderance to T4 cars that don't have one currently.

2. #39610 (Harley Kaplan) Shocks on the T2 BMW M2 CSR
The car was slowed due to its performance at the Runoffs. We do not wish to change the BOP or the Spec car nature of the spec line.

T4
1. #39254 (Raymond Blethen) Allow 60mm Restrictor Plate on Mazda RX8
The Runoffs are the primary focus of the committees. It is the event that provides the best data and it is the only race involved in crowning the national champion. Mid-season BOP is overshadowed by the goal of achieving parity by the Runoffs. In 2024, the T4 RX8 claimed the top 7 grid positions in a 15 car field. The TAC and CRB were confident that, even if minor, something had to be done to encourage participation from other spec lines. The committee does not feel that it would be appropriate to put the RX8 back in such a dominant position.

2. #39401 (Luis Goncalves) Request to Allow the 2022+ Toyota GR86/Subaru BRZ into T4
The 2022+BRZ is not recommended for T4.

3. #39420 (Alex Lozano) RX8 Weight Request Back to 3125
Please see letter #39254 in current Fastrack.

<u>Recommended Items</u>
The following subjects will be referred to the Board of Directors for approval. Address all comments, both for and against, to the Club Racing Board. It is the BoD's policy to withhold voting on a rules change until there has been input from the membership on the presented rules. Member input is suggested and encouraged. Please send your comments via the form at www.clubracingboard.com.
B-Spec
1. #39651 (Erick Zanner) Sunroof Delete Panel
In GCR, Section 9.1.10.E.28., change as follows:
"~~Sunroofs, Targa tops, and T-tops are only permitted if installed by the manufacturer of the vehicle. If installed they must be retained in the closed position and securely bolted in place unless the operating rails adequately secure the panel. Glass panels are permitted. Glass panels may be replaced with a ferrous metal panel. Components (motors, cables, rails) may be removed provided the panel is securely retained.~~*Sunroofs are only permitted if installed by the manufacturer of the vehicle. If installed, they must be run in the closed position and securely bolted in place unless the operating rails adequately secure the panel. Glass panels are permitted. The glass sunroof may be replaced with a metal panel and all its associated mechanical components may be removed. The panel must retain the shape of the glass sunroof.*"

GCR
1. #39511 (Tim O'Donoghue) GCR Change Regarding Double Yellow / Full Course Yellow
In Meaning of Each Flag, GCR section 6.1.1.B, change as follows effective 2/1/26:
"DOUBLE YELLOW, DISPLAYED AT ALL STATIONS – Indicates the entire course is under yellow (full course yellow). All stations will display double yellow flags for all pace and safety car laps. SLOW DOWN, NO PASSING. *Flagging station(s) in the emergency area(s) will display either a standing or waved yellow as appropriate. Once a flagging station clears its incident/emergency, it will display double yellow flags.* ~~However, c~~*C*ars may carefully pass emergency vehicles and other cars that are disabled or off pace (see 6.6.2.)."

2. #39513 (Bill Skibbe) GCR 6.10 Rewrites
In Provisional Results, GCR section 5.10.4.A, change as follows effective 2/1/26:
"A ~~lap chart or a~~ printout *or online report* showing the order of finish and number of laps completed for each car shall be titled as Provisional Results and posted as soon as possible. The time of posting will be on the Provisional Results with the Chief of T&S's initials or signature, and an announcement will be made. When there is a pending action for a particular race group, Provisional Results for that group may be distributed to officials and competitors in lieu of Official Results, with a notation printed stating the reason (i.e., pending outcome of action involving X class)."

In Official Results, GCR section 5.10.4.B.3, change as follows effective 2/1/26:
"The timing and scoring information shall include: total number of entries, DNFs, DNSs, the overall and class finishing positions for all starters, the number of laps completed for all starters, the overall time of the race, the winner's margin of victory, the winner's average speed, the fastest lap time for all starters*,* and any new course records.

All drivers listed ~~on~~*in* the final race results shall be consistent with the numbers included in the event audit.
~~A DNF (Did Not Finish) is defined as a car that did not complete the required number of laps to be a finisher (half the number of laps counted by the overall leader, rounded down to the nearest whole integer). A starter is defined in Section 6.10.2. A DNS (Did Not Start) is defined as any car that turned a wheel on the track during practice or qualifying but did not start the race.~~*Refer to GCR sections 6.10.2 and 6.10.3 for the definitions of Starters, Finishers, DNF, and DNS.*"

In Race Starter, GCR section 6.10.2, add a new section as follows effective 2/1/26:
"*F. A car that does not meet the above criteria but has been on track in any session covered under the event sanction number is classified as DNS.*"

In Race Finisher, GCR section 6.10.3, change as follows effective 2/1/26:
"A. A race finisher is a car that completes *at least* half *of* the laps of the overall race winner ~~for either a numbered lap event or a timed event. Enduro events should define the awarding of points in the enduro supplemental regulations. If the race is an uneven number of laps, divide the overall winner's laps in half and~~ round*ed* down to the nearest whole integer. A car has 5 minutes after the ~~checkered flag~~*overall winner crosses the finish line* to complete its current lap.
B. A DNF (Did Not Finish) is a car that does not meet the conditions of section A.
~~B.~~*C.* A car may complete a lap by being driven across the control line in the pit lane only using on-board power (such as the starter motor), but it may not be pushed across the line ~~by its crew or any officials~~."

3. #39636 (Mike Smith) Drivers School 3.1.3 and App B
In Drivers' Schools, GCR section 3.1.3.A, change as follows effective 2/1/26:
"*When production and formula cars are entered,* ~~T~~*t*he entered cars will be divided into at least open and closed wheel groups, which will run separately from one another. *SRF or SRF3 cars may be grouped with small bore production cars.* Sports Racing*/Prototype* cars may be grouped with Formula cars. (See AppB.1.4.2.)"

In Drivers' Schools, GCR section 3.1.3, add a new section as follows effective 2/1/26:
"*D. The organizing region may limit participating classes and may include eligible Club Race Experience vehicles.*"

In Appendix B, GCR section 1.4.2.E, change as follows effective 2/1/26:
"SRF *or SRF3* may be combined with F *Production,* ~~and~~ H Production*,* ~~and~~ GTL*, or similar small bore production cars*."

T1
1. #38962 (Drew Delmonico) Change to Weight, Power and Torque Settings Due to Exhaust Change
In GCR, Section 9.1.9.1.A.R.3., add the following:
"Mufflers may be substituted with performance alternative options."

T2-T4
1. #38505 (Josh Swanberg) Driveshaft Safety Loop Provision Clarification
In GCR, Section 9.1.9.2.D.4.b.7., add the following:
"*RWD cars may install a driveshaft safety loop. This includes Spec cars.*"

Taken Care Of
B-Spec
1. #39555 (Alex Ratcliffe) Objection to Sunsetting the Mini Cooper Header
Please see response to letter #39321 in the January Fastrack, OBX #10-2101-2S Header Availability and Competitive Parity.

2. #39556 (Alex Ratcliffe) Objection to Sunsetting Mini Headers
Please see response to letter #39321 in January Fastrack, OBX #10-2101-2S Header Availability and Competitive Parity.

GT2
1. #38023 (Andrew Aquilante) Balance of horsepower in the class (Ignore Letter 38019)
Please see letter #39537 in January Fastrack.

FP
1. #39591 (Brian Linn) Miata Compression Ratio Change - Rescind
Please see response to Letter #39606 in the current Fastrack.

2. #39611 (Daniel Snow) FP Miata Competition Adjustments
Please see response to Letter #39606 in the current Fastrack.

3. #39616 (Mark Carpenter) Reverse Compression Ratio & Valve Lift Increases Given to Miata
Please see response to Letter #39606 in the current Fastrack.

4. #39648 (Chris Bovis) F Production Rule Change Response
Please see response to Letter #39606 in the current Fastrack.

T2
1. #36872 (Johnny Cooper) Like to Determine if We Can Establish Class Placement,
Please see letter # 39702 in current Fastrack.

T3
1. #39605 (William Bolt) 350Z - Brake Rotor Size Request
Please see the category rules section for the rotor/caliper allowances that affect the class as a whole.

T4

1. #39341 (Richard Mooney) Support for Letters 39228 and 39227
Please see recent changes that have been made in letters #39251 in November Fastrack and #39230 in current Fastrack.

2. #39343 (David Mead) Suggestions for T4 BOP
Please see recent changes that have been made in letter #39251 in November Fastrack. 4.0 liter Mustang changes are shown in letter # 39489 in current Fastrack.

3. #39366 (Raymond Blethen) Request Removal of 3.7L Mustang from T4
Please see letter #39230 in current Fastrack.

4. #39367 (John McLendon) Please Remove the 3.7 Mustang
Please see letter #39230 in current Fastrack.

5. #39368 (Mitchel Sexton) Concern Regarding Ford Mustang 3.7 V6 Performance in Touring 4
Please see letter #39230 in current Fastrack.

6. #39402 (Luis Goncalves) Request to Remove the 3.7L Mustang in its Entirety from T4
Please see letter #39230 in current Fastrack.

7. #39564 (Matthew Miller) 2005-2010 4 Liter Mustang Gear Changes
Please see response to letter # 39489 in current Fastrack.

8. #39583 (Scotty B White) 4.0L T4 Mustang
Please see response to letter # 39489 in current Fastrack.

What Do You Think

None.

Resumes

None.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

DATE: January 20, 2026
NUMBER: TB 26-02
FROM: Club Racing Board
TO: Competitors, Stewards, and Scrutineers
SUBJECT: Errors and Omissions, Competition Adjustments, Clarifications, and Classifications

All changes are effective 2/1/2026 unless otherwise noted. If any day of a race event falls on the first day of the month, the previous month's rules will be in effect for that event only. The new rules will become effective at the conclusion of the race event, unless otherwise noted.

American Sedan
None.

B-Spec/C-Spec
1. #39652 (B-Spec/C-Spec Committee) C-Spec Rear Sway Bars
In C-Spec Spec Lines, change Notes as follows:
Chevrolet Cruze (2010-16):
"~~Allow BC Racing Q-06-BR suspension kit or RedShift Q-06-CSPEC. Allow Babyface Fabrication brake caliper piston SNC-SS.~~*Approved parts: BC Racing Q-06-BR or RedShift Q-06-CSPEC suspension kit, Babyface Fabrication brake caliper piston SNC-SS, ZZ Performance ZZ-SNCRSB or Whiteline BHR93 rear sway bar.*

Dodge Dart (2014-16):
"~~Allow BC Racing or RedShift Z-06-CSPEC kit.~~*Approved parts: BC Racing Z-06-BR or RedShift Z-06-CSPEC kit, Progress rear sway bar 62.0606.*"

Ford Focus Hatchback/Sedan (2011-18):
"~~Allow BC Racing E-21-BR or RedShift E-21-CSPEC kit. Allow Corksport Axl-3-318-Black adjustable rear camber arms.~~*Approved parts: BC Racing E-21-BR or RedShift E-21-CSPEC suspension kit, Corksport Axl-3-318-Black adjustable rear camber arms, Corksport Axl-3-071-12, Eibach 35134.312, or Whiteline BMR78XZ rear sway bar.*"

Honda Civic Coupe/Sedan (2012-15):
"~~Allow BC Racing A-58-BR or RedShift A-18-CSPEC kit.~~*Approved parts: BC Racing A-58-BR or RedShift A-18-CSPEC suspension kit, Progress 62.1026 or Megan Racing MRS-HA-0791 rear sway bar.*"

Honda Civic Coupe/Sedan (2006-11):
"~~Allow BC Racing A-18-BR or RedShift A-58-CSPEC kit.~~*Approved parts: BC Racing A-58-BR or RedShift A-18-CSPEC suspension kit, Progress 62.1026 or Megan Racing MRS-HA-0791 rear sway bar.*"

Mazda3i SKYACTIV (2012-13):
"~~Allow BC Racing N-03-BR or RedShift N-03-CSPEC kit. Allow Corksport Axl-3-318-Black adjustable rear camber arms.~~*Approved parts: BC Racing N-03-BR or RedShift N-03-CSPEC suspension kit, Corksport Axl-3-318-Black adjustable rear camber arms, Corksport Axl-3-071-12, Eibach 35134.312, or Whiteline BMR78XZ rear sway bar.*"

Mazda 3i MZR (2010-13):
"~~Allow BC Racing N-03-BR or RedShift N-03-CSPEC kit. Allow Corksport Axl-3-318-Black adjustable rear camber arms.~~*Approved parts: BC Racing N-03-BR or RedShift N-03-CSPEC suspension kit, Corksport Axl-3-318-Black adjustable rear camber arms, Corksport Axl-3-071-12, Eibach 35134.312, or Whiteline BMR78XZ rear sway bar.*"

Mazda 3i (2004-09):
"~~Allow Corksport Axl-3-318-Black adjustable rear camber arms.~~*Approved parts: BC Racing N-03-BR or RedShift N-03-CSPEC suspension kit, Corksport Axl-3-318-Black adjustable rear camber arms, Corksport Axl-3-071-12, Eibach 35134.312, or Whiteline BMR78XZ rear sway bar.*"

Toyota Corolla (2007-12):
"~~Allow BC Racing C-02-BR or RedShift C-02-CSPEC kit.~~*Approved parts: BC Racing C-02-BR or RedShift C-02-CSPEC suspension kit, TRD PTR11-12080 or Megan Racing MRS-TY-1710 rear sway bar.*"

Toyota Corolla (2013-18):
"~~Allow BC Racing C-02-BR or RedShift C-02-CSPEC kit.~~*Approved parts: BC Racing C-02-BR or RedShift C-02-CSPEC suspension kit, TRD PTR11-12080 or Megan Racing MRS-TY-1710 rear sway bar.*"

Electric Vehicle
None.

Formula/Sports Racing
FA
1. #39411 (Stephen Lamana) Pro Mazda Classification and Performance Enhancement Proposal
In FA Table 2, Pro Formula Mazda spec line, change the notes as follows:
"All current FA rules apply to areas not covered by this spec line. Apex seals unrestricted. Street port or bridge port allowed. ~~Unmodified OEM l~~*L*ower intake manifold ~~required~~*unrestricted*, upper *intake* manifold unrestricted. Balance tube not permitted. Fuel injection only. *Maximum* ~~70~~*80*mm ~~T~~*t*hrottle ~~B~~*b*ody. The maximum height of the wing and/or endplates ~~shall~~*must* not exceed 99cm (38.98 inches). The overall maximum width of the bodywork behind the front wheels ~~shall~~*must* not exceed 132cm (51.97 inches)."

GCR
None.

General
None.

Grand Touring
GT1
1. #39322 (Erik Madsen) Request for Addition of Porsche 992.1 GT3 Cup into GT1
In 9.1.2. GT1 Spec Lines, add the following:
"*992.1 GT3 Cup (2022-2025)*
OEM ABS and Traction Control allowed. Porsche OEM RSR bumper and canards allowed. Any exhaust system may be utilized."

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

GT2

1. #39249 (Justin Erion) Allow Larger Air Cooled Engines in Porsche 911 GT2

In GT Spec Lines, create GT Cars - PORSCHE and classify SC as follows:

GT Cars - ***PORSCHE***					
Model	Years	Body Style	Drive- line	Wheel- base (in)	Notes
SC	*1978*	*2 Dr.*	*Rear engine/RWD*	*89.45*	*May use alternate engine bore. 4.0L 2V @2275 lbs. 4.0L 4V @ 2350 lbs.*

2. #39408 (Jared Lendrum) Classify T1 BMW in GT2

In GT Spec Lines, classify M3 E92 in GT Cars - BMW as follows:

GT Cars - *BMW*					
Model	Years	Body Style	Drive-line	Wheel-base (in)	Notes
M3 E92	*(08-13)*	*2 Dr.*	*RWD*	*108.7*	*Cannot be built to any other rule set.*

In GT Spec Lines, classify M3 E92 in GT Engines - BMW - BMW as follows:

GT Engines - *BMW*								
Engine Family	Engine Type	Bore x Stroke (mm)	Disp. (CC)	Head Type	Valves / Cyl.	Fuel Induction	Weight (lbs)	Notes
E92	*V8*	*92m X 75.2mm*	*3999*	*DOHC*	*32*	*35mm diameter hole inlet restrictor plate*	*3300*	*Factory DCT transmission allowed. Carbon Dash allowed with 25 lb penalty. Cannot be built to any other rule set.*

Improved Touring

IT General

1. #39691 (Greg Amy) E&O: Turbo Cars in IT

In GCR, Section 9.1.3.A Purpose, add the following:

"Turbocharged/Super charged cars are not eligible for Improved Touring competition *unless explicitly listed*."

Legends Car
None.

Production
FP
1. #38208 (Scott Schick) Request Toyota 5E Series Engines
In FP Appendix N, add spec line for the Toyota 5E engine to the "Engines - TOYOTA" section:

Engines - TOYOTA								
Engine Family	Engine Type	Bore x Stroke (mm)	Disp. (cc)	Head Type	Valves/ Cyl.	Fuel Induction	Weight (lbs)	Notes
5E	*DOHC*	*74.0 x 87.0*	*1497*	*Alum, Crossflow*	*4*	*23mm SIR*	*1900*	

2. #38209 (Scott Schick) Request for Toyota 4E Series Engines
In FP Appendix N, add spec line for the Toyota 4E engine to the "Engines - TOYOTA" section:

Engines - TOYOTA								
Engine Family	Engine Type	Bore x Stroke (mm)	Disp. (cc)	Head Type	Valves/ Cyl.	Fuel Induction	Weight (lbs)	Notes
4E	*DOHC*	*74.0 x 77.4*	*1331*	*Alum, Crossflow*	*4*	*Unrestricted*	*1900*	

3. #39593 (Daniel Snow) Dual Carbs for the Fiat X1/9
In FP Spec Lines, change as follows:
Fiat X-1/9 & Bertone 1300:
"(1) Weber 32 DMTR or DATRA/100 w/32mm bores
(1) 40 DCNF w/32mm choke(s)
(2) auto-type side-draft w/28mm choke(s) on I.R. manifold
Orientation of the alternate carburetor is unrestricted. The alternate carb adapter may not be thicker than 1.25”. The adapter may have a bore larger than the throttle bore of the approved alternate carburetor.
Valve Size: (I) 35.5/(1.40) (E) *31.3/(1.23)*~~30.5/(1.20) (E) 1.23~~
Trans. Speeds: 5"

Fiat X-1/9 & Bertone:
"Fuel Injection
(1) 34 DMTR~~, (1) 36 DCNF w/34mm choke(s), or (1) 40DCNF w/34mm choke(s)~~
(1) 36 or 40 DCNF w/34mm choke(s)
(2) auto-type side-draft w/28mm choke(s) on I.R. manifold
Orientation of the alternate carburetor is unrestricted. The alternate carb adapter may not be thicker than 1.25”. The adapter may have a bore larger than the throttle bore of the approved alternate carburetor.
Valve Size: (I) 35.5/(1.40) (E) 33.0/(1.30)

Trans. Speeds: 5 or 4"

HP

1. #39589 (Neil Verity) Triumph Spitfire 1296cc Compression Ratio Increase to 12:1

In HP Spec Lines, make the following spec line changes:

Triumph Spitfire:

Carburetion

"Valves: (I) 33.0/(1.30) (E) 29.7/(1.17)

Comp. ratio ~~11.0~~*12.0*:1, Valve lift .450”

Trans. Speeds: 4"

Triumph Spitfire Mk. III & IV 1500:

Carburetion

"1300 Valves: (I) 33.0/(1.30) (E) 29.7/(1.17)

1500 Valves: (I) 36.6/(1.44) (E) 29.7/(1.17)

1300: Comp. ratio 12.0:1, Valve lift .450”

1500: Comp. ratio 11.0:1, Valve lift .450”

Trans. Speeds: 4"

Spec Mazda (SM/SMX)

None.

Super Production

None.

Super Touring

None.

Touring

T1

1. #39716 (Danny Kellermeyerhttps://crbscca.com/secu) LS1 into Corvette C6 Spec Line Request

In T1 Spec Lines, reinstate Spec Line # 1139, Chevrolet Corvette C6 (05-13) Includes Z51, GrandSport, Z06, Z06 Carbon, as follows:

Max Displ: "*LS1, LS6 OEM*"

Min Weight: "*3200*"

Required Restrictor: "*70mm*"

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

T2

1. #38991 (Jimmy Cabrera) Request to Add 2014-2017 435i to T2
In T2 Spec Lines, classify as follows BMW 435I (2014-2017):

T2	Bore x Stroke(mm)/ Disp. (cc)	Required Restrictor	Wheel Size(in.)	Tire Size (max)	Gear Ratios	Final Drive	Brakes (mm)	Weight (lbs)	Notes:
BMW 435i (2014-2017)	*84.0 x 89.6 2 2979*	*40mm*	*18 x 10*	*275*	*.71, 3.14, 2.11, 1.67, 1.29, 1.00, 0.90,*	*3.23*	*340mm (f) 330mm (r)*	*3400*	*Sway Bars permitted 32mm (f), 22mm (r).*

In T2 Spec Lines, BMW M235i (-2016), change as follows:
Required Restrictor: "*40mm TIR*"
Notes: "~~40mm Turbo Inlet Restrictor required.~~"

2. #39296 (Greg Nelson) Consideration for Nissan Z & NISMO Z to Touring 2 Class
In T2 Spec Lines, classify Nissan Z incl. Nismo as follows:

T2	Bore x Stroke(mm)/ Disp. (cc)	Required Restrictor	Wheel Size(in.)	Tire Size (max)	Gear Ratios	Final Drive	Brakes (mm)	Weight (lbs)	Notes:
Nissan Z incl. Nismo	*86mm x 86mm 2997*	*38mm TIR*	*19 x 9.5 (f) 19 x 10.5 (r)*	*295 (f) 315 (r)*	*Base (MT) 3.79, 2.32,1.62, 1.27, 1, .79* *Nismo (AT) 4.92, 3.19, 2.04, 1.41, 1, .86, .77*	*3.36*	*Base 355* *Nismo 381*	*Base 3600* *Nismo 3650*	*Springs allowed 1000lb max.* *Sway bars allowed 35mm (f), 29mm (r)* *Must participate in 3 Super Tour events before this car is elligible for the Runoffs.*

3. #39702 (Vito Jin) Request for Classification of MG6 TCR in T2-TCR Class
In T2-TCR Spec Lines, classify Link & Co 03 TCR (2019-2025) and MG6 TCR (2019-2022) as follows:

T2-TCR	Transmission	Power Level	Weight(lbs)	Notes
Link & Co 03 TCR (2019-2025)	*SEQ*	*90%*	*3000*	*DOT approved tires with maximum section width of 275. T2-TCR splitter and valance must comply with 9.1.4.D.3.f. T2-TCR chassis ride height must comply with 9.1.4.1.A.1*
MG6 TCR (2019-2022)	*SEQ*	*90%*	*3000*	*DOT approved tires with maximum section width of 275. T2-TCR splitter and valance must comply with 9.1.4.D.3.f. T2-TCR chassis ride height must comply with 9.1.4.1.A.1*

T2-T4
1. #39607 (David Mead) Allow Alt Bushing Material in Toe Links
In GCR, Section 9.1.9.D.5.a.1., change as follows:
"T2-T4: A maximum of 3.5 degrees of negative camber is allowed on front and rear suspensions. Spec line part(s) may not be modified to increase caster and camber. Strut suspensions may adjust camber and caster by the use of eccentric bushings, eccentric bolts (crash bolts) at the strut-to-spindle, and/or by use of slotted adjustment plates at the top of the strut mounting plate. If upper strut slotted adjustment plates are used, they shall be located on existing chassis structure, utilizing the unmodified manufacturer's original bolt holes and may not serve as reinforcement for that structure. Slotted adjustment plates (strut camber plates) may incorporate a single spherical bearing (spherical bushing) and a ball thrust bearing per strut tower. On other forms of suspension, camber and caster adjustment may be achieved by the use of shims and/or eccentric bushings. ~~Adjustable toe links with spherical bearings are permitted and may serve no purpose other than adjusting toe angle.~~*Adjustable toe links are permitted. They are allowed to have performance alternative bushings and spherical bearings. They may serve no purpose other than adjusting toe angle.* Spherical bearings/bushings are not permitted in T2-T4 except for the specific examples listed in the class rules or vehicle spec line."

T3
1. #39558 (Matthew Miller) Please change 2011-2014 Mustang V6 Spec Line to 2005-2014
In T3 Spec Lines, Ford Mustang V6 (11-14) , add to Notes the following:
"*2005-2010 chassis/body permitted.*"

2. #39598 (David Muramoto) Nissan 350Z Weight Request
In T3 Spec Lines, Nissan 350Z Track/ Touring/Standard/ Nismo (03-08), change Weight as follows:
DE Motor: "~~3125~~*3100*"
HR Motor: "~~3275~~*3250*"

T4
1. #39230 (Tim Myers) T4 and T3 Feedback
In T4 Spec Lines, remove Ford Mustang V6 (05-14) in its entirety.

2. #39489 (Scotty B White) T4 Mustang 4.0
In T4 Spec Lines, Ford Mustang V6 (05-10), change as follows:
Tire: "~~245~~*255*"
Notes: "ABS (option code 552) allowed. FR3 Handling Pack #M-2007-FR3V6 allowed (kit does not need to be run in its entirety). The kit includes: Dampers M-18000-A, Lowering Springs M-5300-N, Sway Bars M- 5490-C, Strut Tower Brace M-20201-F. Ford Positraction LSD part #M-4204-C75 is allowed. Any springs max F: 500 and R: 400 permitted. Any sway bar up to F: 35mm and R: 28mm permitted. Aftermarket Shocks conforming to T4 rules allowed. Panhard bar, part # BAR-M-4264-A permitted, or any pan hard bar permitted must be set at same length as a stock bar, center mounting hole to center mounting hole +/- 0.25 inch. An alternative steel drive shaft is permitted; this drive shaft is otherwise unrestricted, but no modifications to other components are permitted to facilitate its installation. An Aluminum driveshaft is allowed. Any LSD permitted. Ford brake kit M-2300-D allowed. Aftermarket header allowed. GT 8.8 rear axle assembly allowed. ~~3.45 or 3.55~~ *Alternate* final drive ratio allowed. 7.5 rear axle assembly ~~with 3.45:1 final drive~~ allowed. Cold Air Intake allowed. Koni part numbers 8741-1494SPORT (front) and 8241-1240SPORT (rear). Spec clutch #SF661 and flywheel #SF66A permitted. 14” Brembo Brake Kit#M-2300-S permitted."

Fastrack® news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

ROAD RACING COMPETITION COMMITTEE MINUTES | February 3, 2025

We appreciate the feedback and perspectives that our members provide, and we'd like to thank you for your outreach and being part of the process. Should you have any requests or feedback to share with the Road Racing Competition Committee or a class advisory committee, please visit https://crbscca.com/ to submit a letter.

The Road Racing Competition Committee met by teleconference on February 3, 2025. Participating were Dayle Frame, Chairman; David Arken, David Locke, Jim Goughary, Peter Keane, Sam Henry, Tom Start, Tony Ave and Shelly Pritchett, secretary. Also participating were: Bob Crawford, BoD Chairman, David Brown, Mark Weber and Sam Fouse, BoD liaisons; Eric Prill, Vice President, Road Racing, Sydney Davis Yagel, Senior Manager of SCCA Road Racing, Scott Schmidt, Road Racing Technical Manager, Scott Dobler, Road Racing Series Manager. The following decisions were made:

Member Advisory
None.

No Action Required
AS
1. #39719 (Andrew Kuhn) Follow up on LM7 1 7/8 Header Recommendation
The ASAC contacted Mr. Kuhn and provided part numbers for 1 3/4" headers available for the LM7 engine.

2. #39784 (Andrew Kuhn) Cubic Inch Weight Change Recommendation
The ASAC contacted Mr. Kuhn and explained that modifications above the standard LM7 build, as delineated in the AS build sheet, enable the engine to have equivalent horsepower and torque to a standard build of a small block Chevrolet engine/carburetor combination.

P2
1. #39435 (Brian Lindstrand) Allowance of Paddle Shifters for P2 cars
Thank you for your feedback. Please see the response to letter #39776 in the current Fastrack.

General
1. #39460 (Jason Stine) Runoffs Entry Fees for Conference Champions
With the Road Racing Program's goal of promoting access and participation, adding an additional fee to Conference participants' Majors & Super Tour entry fees to assist with covering a Conference Champion's Runoffs entry fee is not something we are interested in doing at this time.

2. #39753 (Anthony Stefanelli) Change to 1.4.2 in Appendix B, January Fastrack
The change to Appendix B 1.4.2 in the January Fastrack was made to remove redundancy.

3. #39771 (Dave Weitzenhof) Transparency in Letter Submission Process
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

5. #39772 (Anthony Stefanelli) I support Letters 39970 and 39971
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

5. #39773 (Stevan Davis) Support For Letter #39770
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

6. #39781 (Brian Tomasi) Runoffs Change
We appreciate your feedback on Letters 39778 & 39779 regarding the Runoffs format. It is still being discussed at this time.

7. #39783 (Daniel Piperato) RE: 39770 John LaRue in Regards to Confidentiality of CRB Letters
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

8. #39786 (Todd Butler) Support for Letter 39770
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

9. #39791 (Jay Messenger) Support for 39770
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

10. #39793 (Oscar Jackson) Oppose 39778 39779 - Too Much AI Thought.
We appreciate your feedback on Letters 39778 & 39779 regarding the Runoffs format. It is still being discussed at this time.

11. #39805 (Anthony Stefanelli) SCCA Website Revision Idea
The idea of giving each Road Racing class its own web page is intriguing. The prospect of a central information hub that would allow existing and interested drivers to find out more about the class would assist with lowering some entry barriers that have been identified in the past. As the Marketing Department continues to develop the new website design for the Club, we will share this idea as a next step once the new site is launched.

12. #39806 (Dave Weitzenhof) Support for Letter 39778 Heat Race Concept for Runoffs
We appreciate your feedback on Letters 39778 & 39779 regarding the Runoffs format. It is still being discussed at this time.

13. #39815 (Paul Morrison) Support of Letter 39770 on Submission and Review of Letters.
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

14. #39816 (Greg Amy) Re: Letter #39770
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

15. #39828 (Peter Olivola) Response to Letter #39599
The use of AI in processes and procedures is an ever-evolving discussion. Your recommendation of utilizing an AI program to assist with GCR edits and format changes will be shared with the Road Racing staff and BOD for further consideration.

16. #39835 (Taylor Stein) In support of #39770
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

17. #39842 (Chuck Moran) Request Transparency
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

18. #39844 (Glen Thielke) Support for Letters 39778 & 39779 Runoffs Format Changes
We appreciate your feedback on Letters 39778 & 39779 regarding the Runoffs format. It is still being discussed at this time.

19. #39847 (Andrew Gamble) Support for Letters 39770 and 39778
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack. Your feedback on Letters 39778 & 39779 regarding the Runoffs format is noted as well. It is still being discussed at this time.

20. #39855 (Peter LeSueur) Letter System
Thank you for your feedback on letter 39770. Please see the response in the current Fastrack.

21. #39868 (Jay Messenger) Support for 39867
We appreciate your feedback on Letter 39867 on the Technical & Race Bulletin process and philosophy. It is still being discussed at this time.

22. #39884 (Peter LeSueur) 90-Day Parallel Path
We appreciate your feedback on Letter 39867 on the Technical & Race Bulletin process and philosophy. It is still being discussed at this time.

STU
1. #39821 (Jorge A Nazario) Allow RX8 hubs and Transaxle on Miata NC for Safety Reasons
Suspension components in your request are currently legal in STU. Please see 9.1.4.1.D.7. If you are requesting a Diff, please submit a letter with that request.

<u>Not Recommended</u>
AS
1. #39745 (Michael Kamalian) Rear Spoiler for 2018+ mustang
American Sedan rules allow spoilers found on the base model of a car classified in American Sedan. The requested spoiler does not meet this requirement.

B-Spec
1. #39728 (Charles Davis) Radiator Replacement
The committee does not recommend allowing alternative radiators that bolt directly into the core support without any modification at this time.

FA
1. #39540 (Ryan Szyjakowski) 2.1 MZR Liter Engine
The Road Racing Competition Committee does not recommend this change at this time. The RRCC has reviewed performance data from prior events as well as session and race results from the 2026 U.S. Majors events at Homestead and Sebring and at this point does not see a performance disparity between the Swift 014–2.0L MZR and other FA platforms. The RRCC will continue to monitor class performance and will collect comparative data during the 2026 season to determine whether adjustments are warranted.

2. #39757 (Mirl Swan) Weight Adjustment To Toyota Powered FA
The Road Racing Competition Committee does not recommend this change at this time. The RRCC has received no information which indicates that the referenced Toyota-powered cars have a performance disadvantage to other cars in the class. If competitors with Toyota-powered cars believe their cars have such a deficit and are interested in seeking a BoP adjustment, it is incumbent upon them to enter their cars in U.S. Majors Tour / Hoosier Super Tour events during the 2026 season to allow the RRCC an opportunity to gather comparative data and determine whether such an adjustment is warranted.

FC
1. #39162 (Moses Smith) Reclassify FM to FC
The Road Racing Competition Committee does not recommend this change because the FM uses a number of major components that fall outside the general FC rules. While two cars that are reasonably close to the class concept have been allowed into FC as "spec line" cars, the rules state that additional spec line cars are disfavored. Creating an additional spec line for a car that uses several major components that do not comply with the general rules is outside the scope and intention for the class. To the extent that a performance disparity between the FM and other cars in the FX class is a concern, the RRCC notes that competitors facing this situation in other classes have sometimes organized an unofficial championship for that car type within their class and/or recognized individual competitors' performance by awarding separate trophies and taking their own podium photos. This has worked well both regionally and nationally but does require organization on the racers' part.

2. #39746 (Paul MacFarlane) FC Spec Tire Grooving Clarification
The Road Racing Competition Committee does not recommend this change. GCR section 1.2.3.C.2 states that "Specific class rules in the Category Section of the GCR shall take precedence over . . . the General Technical Specifications" (such as section 9.3.47). The FC rules state the following in section 9.1.1.B.1.d: "Formula F and Formula Continental are restricted classes. Therefore, any allowable modifications, changes, or additions are as stated herein. There are no exceptions. IF IN DOUBT, DON'T." The requirements for FC spec tires are provided in sections 9.1.1.B.10.g and 9.1.1.B.10.h, and these rules do not authorize modifications or changes. The RRCC does not believe it is in the best interests of the class to authorize modifications or changes to spec tires.

P2
1. #39776 (Brian Lindstrand) Allowance of Paddle Shifters for P2 cars
The Road Racing Competition Committee does not recommend the underlying request to allow assisted shifting systems on P2 cars that were not originally built with them. To be clear, the P2 rules do not disallow paddle shifters themselves, nor do they disallow flat shifters that use vacuum-activated throttle blippers. The class rules state that "[d]evices that interact with the throttle, ignition, or fuel system during a shift operation (for example: ignitions cuts, flat shifters, blippers) are permitted, but no such devices shall remove the driver's control of the gear change initiation, gear selection or completion." A vacuum-activated blipper interacts with the throttle, not the transmission; it does not "remove the driver's control of the gear change initiation, gear selection or completion." The Flatshifter Max system described, however, is an assisted shifting system that actuates gear changes by electronic (and not mechanical) means. The P2 rules state that "[o]nly mechanical gearshifting mechanisms are allowed except as permitted by Table 1 Spec Line Cars. This may include cables, rods, or other mechanical linkage systems." The class rules go on to note that "[t]his prohibition is intended to eliminate the use of electric solenoid shifters . . . and other devices not mechanically actuated and controlled completely by the driver." Based upon information obtained by the advisory committee, the RRCC believes that the Flatshifter Max system could be converted to a P2-compliant system by purchasing a wiring harness and load sensor for the original mechanical linkage and reprogramming the Flatshifter control box. As the rules state, P2 is intended to be a relatively low-cost sports racing class, and given the relatively low cost of converting the Flatshifter Max system to a P2-compliant system, the RRCC does not recommend allowing high-cost assisted shifting systems and adding a

weight penalty to offset their advantage, because such a change would likely lead other drivers to believe they need a similar system to be competitive and would thereby increase the cost to race in P2.

FP
1. #39792 (George Cichon) GT3 Mazda RX-7
The Road Racing Competition Committee has no desire to add GT3 cars and/or rotary prep into the GTL/FP classifications at this time. The RX7 has a GTL classification (see Appendix N), and any examples that wish to race as such would need to be prepped to that ruleset.

STU
1. #39813 (Edwin Soto-Quinones) Boxster Brake Rotor
The 340mm brake rotor is beyond the size allowed in STU and not consistent with class formula.

T4
1. #39765 (Tony Kiratsous) Touring 4 Parity Adjustment – Scion FR-S / Subaru BRZ (2013–2016)
The BRZs and FRSs were given a 50lb decrease to adjust for the coming year, and the Road Racing Competition Committee doesn't recommend the increase in tire and wheel width that you proposed. The similar-weight cars that you cited with the larger tire are FWD and not a fair comparison.

Recommended Items
The following subjects will be referred to the Board of Directors for approval. Address all comments, both for and against, to the Road Racing Competition Committee. It is the BoD's policy to withhold voting on a rules change until there has been input from the membership on the presented rules. Member input is suggested and encouraged. Please send your comments via the form at www.clubracingboard.com.

B-Spec
1. #39656 (B-Spec/C-Spec Committee) Delete rule #39
In GCR, Section 9.1.10.E. delete the following and re-number the rules that follow:
"*(Effective 3/1/2026)* ~~39. Automatic and cvt transmissions versions of all legal cars are legal for competition in B-Spec and C-Spec meeting their spec line. Models with OEM paddle shifters are acceptable. Auxiliary transmission coolers may be approved on a case by case basis. Part numbers must be submitted and added to the cars spec line.~~"

GT2
1. #39863 (Grand Touring Committee) remove 9.1.2.7.l GCR Page 332
In GCR, Section 9.1.2.F.7.l, change as follows and re-letter:
"*(Effective 3/1/2026)* ~~l. GT2 Rules Concerning Alternate Weights and SIRs 1. Traditional GT2 cars that are currently required to run an SIR may run unrestricted induction with a 350 lb. weight penalty. This weight penalty is to be added prior to any "add-on" penalties, such as sequential shifting, IRS, etc.~~"

STU
1. #39812 (Super Touring Committee) Brake vacuum regulators
In GCR, Section 9.1.4.1.E.8., add the following:
"*(Effective 3/1/2026) Brake booster vacuum regulator allowed, cannot be in-car adjustable.*"

Taken Care Of

General

1. #39770 (John LaRue) Letter System

The Road Racing Competition Committee recognizes the confusion that some letter responses cause when there is no context to the request. Moving forward, the RRCC and its Advisory Committees will be striving to provide more transparency in answers to non-recommended letters. Our goal is to allow readers to understand what was asked, what was decided, and why it was decided. There are multiple options for letter writers to make the contents of their letters visible to the membership, should they choose to do so. The newly created SCCA Road Racing Facebook Group is a perfect example of a two-way platform to discuss topics. Members of the RRCC and their ACs have additional collaboration with BOD members and staff, all with the common goal of providing a safe, fun, racing experience to as many drivers as possible. Collectively, we hope that these new developments will provide the additional transparency you are requesting.

T4

1. #39734 (Chris Braunlich) Removal of 3.7L V6 Mustang from T4
See letter #39230 in February Fastrack.

2. #39735 (Christian Braunlich) Removal of 3.7L V6 Mustang from T4
See letter #39230 in February Fastrack.

3. #39737 (Oscar Jackson) T3 Mustang out of T4. Redux.
See letter #39230 in February Fastrack.

4. #39738 (Raymond Blethen) Support letter #39734 Petition for CRB to remove 3.7L V6 Mustang
See letter #39230 in February Fastrack.

5. #39739 (Stephen Blethen) Support letter #39734
See letter #39230 in February Fastrack.

6. #39740 (Richard Mooney) Support for Letter #39734
See letter #39230 in February Fastrack.

7. #39743 (Nathan Pring) Mustang V6 Classing
See letter #39230 in February Fastrack.

8. #39747 (Luis Goncalves) Please Remove 3.7L v6 Mustang from T4
See letter #39230 in February Fastrack.

9. #39755 (Ethan Barker) Please Remove the 3.7 Mustang from T4
See letter #39230 in February Fastrack.

10. #39764 (Owen Schefer) Support for Letter #39734
See letter #39230 in February Fastrack.

11. #39766 (Tony Kiratsous) Remove 3.7L V6 Mustang from T4
See letter #39230 in February Fastrack.

What Do You Think
None.

Resumes
None.

Fastrack news
official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

DATE: February 20, 2026
NUMBER: TB 26-03
FROM: Road Racing Competition Committee
TO: Competitors, Stewards, and Scrutineers
SUBJECT: Errors and Omissions, Competition Adjustments, Clarifications, and Classifications

All changes are effective 3/1/2026 unless otherwise noted. If any day of a race event falls on the first day of the month, the previous month's rules will be in effect for that event only. The new rules will become effective at the conclusion of the race event, unless otherwise noted.

American Sedan
AS
1. #39887 (American Sedan Committee) Re-Organization of AS Spec lines for 2026
This AS Spec Lines re-organization simplifies the Spec Lines for all drivers. This version gives the chassis information on what engines can be put in their cars. It removes information that is now repeated in the ruleset and adds engine/weight combos as well as wheelbase/tire size information. The Notes in the Spec Lines have been reviewed to remove information now listed in the engine build sheets and retain information pertinent to the chassis selected. Where there is nothing in the notes, it is not an error. It just means everything a driver needs is now in the main rules or the build sheets.

In AS Spec Lines, delete current Spec Line in its entirety as follows:

~~AS~~	~~Wheel-base~~	~~Brakes (Max) (in/mm)~~	~~Weight (lbs.) (tire sizes are max)~~	~~Flat Plate Restrictor Size~~	~~Notes:~~
~~Cadillac CTS-V (04-07) Restricted Prep. 5.7L V8 (Aluminum block, Aluminum heads), LS6, 2 valves/cylinder~~ ~~Restricted Prep. 6.0L V8 (Aluminum block, Aluminum heads), LS2, 2 valves/cylinder~~	~~113.4~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire: 3400~~	~~N/A~~	~~Either engine may be used in any car in this specification line, at the appropriate weight. ARE dry sump kit consisting of pump #3021S, Pan 1005M and oil tank 7007-2 or Aviaid dry sump kit #008-10001 consisting of pump 13110-1187, pan 52504-10001 and oil tank 57525 are allowed. Pumps may be driven by a crank mounted, toothed style pulley and belt. Plumbing, hardware, brackets, hoses, and fittings to install above kits are free. Alternate OEM/replacement part 5-lug wheel bearing allowed. SKF bearing p/n BR930081 (or equivalent) rear bearing, used on front and rear positions. Hub pilot may be machined down (up to 3mm) to allow fitment of Camaro SS brake rotors 92245928 (front, 13.9" diameter) and 92245929 (rear,14.3" diameter). OEM Driveshaft may be replaced by Driveshaft Shop P/N – GMCTSV2-C (1-piece carbon fiber.)~~
~~Chevrolet Camaro, Pontiac Firebird (70-81) Full Prep~~	~~108.0~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire 3400 Over 313 CID 3600~~	~~N/A~~	~~Inner fenders are not required. VSE 52800 or UMI 2664 sub-frame mounts allowed, VSE 52706 front structure kit permitted, OEM-style ball joints with taller than stock stud lengths, +1/2" taller are permitted. Adjustable front upper control arms permitted including SPC 94340 or 97130 and UMI 2656-1. Knuckles are free to allow for brake conversion. Coil over shocks permitted in the front suspension along with lower control reinforcement for mounting. Rear suspension type must be maintained along with mounting location, front and rear spring eye height may be adjusted providing ride height adjustment.~~
~~Chevrolet Camaro, Pontiac Firebird (70-81)~~ ~~Restricted Prep. 6.2L V8 (Aluminum Block, Aluminum Heads), 2 valves per cylinder~~	~~108.0~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire 3600~~	~~LS3-65mm~~	~~Inner fenders are not required. VSE 52800 or UMI 2664 sub-frame mounts allowed, VSE 52706 front structure kit per- mitted, OEM-style ball joints with taller than stock stud lengths, +1/2" taller are permitted. Adjustable front upper control arms permitted including SPC 94340 or 97130 and UMI 2656-1. Knuckles are free to allow for brake conversion. Coil over shocks permitted in the front suspension along with lower control reinforcement for mounting. Rear suspension type must be maintained along with mounting location, front and rear spring eye height may be adjusted providing ride height adjustment.~~
~~Chevrolet/Pontiac Camaro & Firebird (82-92)~~	~~101.0~~	~~14.18 x 1.5 Vented Discc~~	~~275 Tire 3300~~ ~~Over 313 CID 3500~~	~~N/A~~	~~Camaro only: To aid cooling, the center of the grill opening (license plate area), absorbing material, metal bumper in the resulting open area, and bumper backing may be removed. OEM-style ball joints with taller than stock stud lengths are permitted.~~
~~Chevrolet/Pontiac Camaro & Firebird (82-92)~~ ~~5.7L V-8 LS1 (Aluminum Block, Aluminum Heads) 2 valves per cylinder~~	~~101.0~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire 3200~~	~~N/A~~	~~Camaro only:To aid cooling, the center of the grill opening (license plate area), absorbing material, metal bumper in the resulting open area, and bumper backing may be removed. OEM-style ball joints with taller than stock stud lengths are permitted. 5.7L LS1: GM Performance Parts camshaft Kit P/N 19355738 is permitted. 1-3/4 headers allowed~~

~~Chevrolet/Pontiac Camaro & Firebird (93-02) Full Prep~~	~~101.1~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire: 3300 Over 313 CID 3500~~	~~N/A~~	~~Underside of cowl may be modified to facilitate carb installation. The cowl and shock tower sheet metal may be modified to allow the instal-lation of an 82-92 F-body brake booster and master cylinder. Engine/transmission installation procedure as provided by SCCA Road Racing Technical Department shall be utilized. BMR AA004 or UMI 2310 adjustable front upper control arm may be installed.~~
~~Chevrolet/Pontiac Camaro & Firebird (93-02) (Restricted Prep.) 5.7L V-8 LT1 (Iron Block, Aluminum Heads) 2 valves per cylinder 5.7L V-8 LS1 (Aluminum Block, Aluminum Heads) 2 valves per cylinder~~	~~101.1~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire: 3200~~	~~N/A~~	~~98-02 stock brakes and/or spindles/knuckles may be used on all cars. Either engine/trans may be used as an assembly. Max compression ratio, 10.6:1, Parts specific to the SS Camaro and Firehawk/WS6 Firebird in the drivetrain/exhaust manifolds/headers/intake manifolds/intake components are not classified in American Sedan. Drivetrain/exhaust manifolds/headers/intake manifolds/intake components manufactured by, but not limited to Street Legal Performance (SLP), Inc., are not permitted unless specified. BMR AA004 or UMI 2310 adjustable front upper control arm may be installed. 5.7L LT1: GM Performance Parts camshaft Kit P/N 12480002 is permitted. Cylinder Bore, 101.6 mm; Stroke, 88.39 mm; Intake Valve Diameter, 49.3; Exhaust Valve Diameter, 38.1 mm; Throttle Body Bore, 48 mm (twin bore). The 5.7L LT1 engine has a 100 lb. weight reduction. 5.7L LS1: GM Performance Parts camshaft Kit P/N 19355738 is permitted. 1-3/4 headers allowed. For the LS1connecting rods Callies p/n CSC6100DS6A2AH, Scat rods p/n 2-1CR6100-944, GM performance rods p/n 12649190.~~
~~Chevrolet Camaro SS (V8) (10-15) (Restricted Prep.) 6.2L V8 Aluminum Block, Aluminum Heads, 2 valves per cylinder~~	~~112.3~~	~~14.18 x 1.5 Vented Disce~~	~~275 Tire: 3600~~	~~LS3-65mm~~	~~Max wheel Dia, 20.0 inches. ARE Dry Sump Kit #LS3-3Y permitted. Belt tensioner part number GM 12569301 allowed. ZL1 Front Facia and grill is permitted.~~
~~Chevrolet Camaro (10-15) Full Prep~~	~~112.3~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire 3400 Over 313 CID 3600~~	~~N/A~~	~~Engine/transmission installation procedure as provided by SCCA Road Racing Technical Department shall be utilized. ZL1 Front Facia and grill is permitted.~~
~~Chevrolet Camaro (16-) Full Prep~~	~~110. 6~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire 3400 Over 313 CID 3600~~	~~N/A~~	
~~Chevrolet Camaro, 1LE (16-)~~	~~110. 6~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire: 3600~~	~~60mm~~	~~Dry Sump Kit permitted.~~
~~Dodge Challenger (08-20) (Restricted Prep) 5.7L, 6.1L, or 6.4L V8 (Iron block, Alumi-num heads), 2 valves/cylinder~~	~~116.0~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire: 5.7,6.1 3600 295 Tire: 6.4L 3700~~	~~5.7L-N/A 6.1L-N/A 6.4L-80mm~~	~~Max. Wheel Size Dia. 20.0 inches. Minimum ride height, 4.00 inches. Dodge 1GL20TZZAB and 82211606 rear spoilers permitted. Dodge 68043390AA air dam permitted. Mopar Performance Parts camshaft stage2 Kit P/N 77072313AB is permitted on the 5.7l engine. 1-3/4" headers are permitted on the 5.7L and the 6.1L. All engine displacements are eligible in all model years, with each engine being used as a complete assembly. Alternate front upper control arms are permitted.~~
~~Ford Mustang Incl. Cobra & Cobra R (79-93) and Mercury Capri (79-86)~~	~~100.4~~	~~14.18 x 1.5 Vented Disc~~	~~3200 Over 313 CID 3400~~	~~N/A~~	~~OEM-style ball joints with taller than stock stud lengths are permitted.~~
~~Ford Mustang Incl. Cobra & Cobra R (79-93) and Mercury Capri (79-86) with (Restricted Prep Engine)~~	~~100.4~~	~~14.18 x 1.5 Vented Disc~~	~~275 tire: 3400~~	~~Gen1-67mm Gen 2-61mm~~	~~Engine/transmission installation procedure as provided by SCCA Road Racing Technical Department shall be utilized. harge Motion Control Valves can be blocked off and removed for firewall clearance. Suspension must remain in the stock location. MMR Secondary Timing Chain Tensioner Bracket #467893 is permitted.~~
~~Ford Mustang Including Cobra (94-04) Full Prep~~	~~101.3~~	~~14.18 x 1.5 Vented Disc~~	~~3300 Over 313 CID 3500~~	~~N/A~~	~~Hydro Boost braking system, Cobra R body work, and independent rear suspension are not permitted. OEM style ball joints with taller than stock stud lengths are permitted. Any stock Ford Mustang K-member 94-04 may be used.~~
~~Ford Mustang GT (94-04) with (Restricted Prep Engine)~~	~~107.1~~	~~14.18 x 1.5 Vented Disc~~	~~275 tire: 3400~~	~~Gen1-67mm Gen2-61mm~~	~~Engine/transmission installation procedure as provided by SCCA Road Racing Technical Department shall be utilized. Charge Motion Control Valves can be blocked off and removed for firewall clearance.Suspension must remain in the stock location. MMR Secondary Timing Chain Tensioner Bracket #467893 is permitted.~~

Fastrack news official SCCA member notification

EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

~~Ford Mustang Cobra and GT 94-95 5.0 and 5.8 motor (Restricted Prep)~~	~~101.3~~	~~14.18 x 1.5 Vented Disc~~	~~3150 Over 313 CID 3250~~	~~N/A~~	~~Max compression ratio 9.2 : 1. 5.0 motor max lift at valve = .45" For the 5.8 motor, max lift at valve = .48" Ford Motorsport #M-6250-F303 camshaft is permitted. Full prep clutch, flywheel, headers, and OEM style balljoints with taller than stock stud lengths allowed. Updating and backdating within spec line is allowable. MMR Secondary Timing Chain Tensioner Bracket #467893 is permitted.~~
~~Ford Mustang including Cobra 96-04 (Restricted Prep) 4.6L 2v and 4v motor~~	~~101.3~~	~~14.18 x 1.5 Vented Disc~~	~~3150~~	~~N/A~~	~~Supercharged motor is not allowed. OEM style balljoints with taller than stock stud lengths allowed. Trick flow engine kit TFS-K519-390-375 may be installed on two valve motors. Max valve lift with trick flow engine kit = .55" MMR Secondary Timing Chain Tensioner Bracket #467893 is permitted.~~
~~Ford Mustang GT (05-14)~~	~~107.1~~	~~14.18 x 1.5 Vented Disc~~	~~275 tire 3400: Over 313 CID 3600~~	~~N/A~~	~~Engine/transmission installation procedure as provided by SCCA Road Racing Technical Department shall be utilized.~~
~~Ford Mustang Coupe GT (05-14) Restricted Prep. (Aluminum Block, Aluminum Heads) 4.6L/5spd 3 valves per cylinder 5.0L/6spd 4 valves per cylinder~~	~~107.1~~	~~14.18 x 1.5 Vented Disc~~	~~5.0L 275 tire: 3400 4.6L 295 tire: 3100~~	~~4.6L- N/A 5.0L- Gen 1- 67mm Gen 2- 61mm~~	~~Tremec Magnum transmission may be used as a replacement assembly for the OEM transmission. P/N-TUKT16901.MMR Secondary Timing Chain Tensioner Bracket #467893 is permitted. MT82 6 speed is permitted. 4.6L engine: Replacement exhaust manifolds, or "headers," as specified in the Full Prep American Sedan rules may be used. Ford Performance camshaft kit P/N M-6550-3V may be used. The 4.6L engine assembly has a weight reduction of 300 lbs. Track pack front and rear spoiler allowed. 5.0L/6spd engine/trans:~~
~~Ford Mustang GT 5.0 (15-17) (Restricted Prep)~~	~~107.0~~	~~14.18 x 1.5 Vented Disc~~	~~275 tire: 3600~~	~~Gen 3- 60mm~~	~~MMR Secondary Timing Chain Tensioner Bracket #467893 is permitted.~~
~~Ford Mustang GT 5.0L (2018-)~~	~~107.0~~	~~14.18 x 1.5 Vented Disc~~	~~275 Tire 3525~~	~~60 mm~~	~~Package Brembo front BBK and 380mm rotors permitted (Ford PN M-2300-V) at no weight penalty. 2014 Mustang GT exhaust manifolds permitted. Ford Racing oil pan #M-6675-M50BR permitted. Performance pack front and rear spoiler, body kit allowed.MMR Secondary Timing Chain Tensioner Bracket #467893 is permitted.~~
~~Pontiac GTO (04-06) Restricted Prep. 2004, 5.7L V8(Aluminum Block, Aluminum heads), LS1, 2 valves per cylinder 05-06, 6.0L V8 (Aluminum Block, Aluminum heads), LS2, 2 valves per cylinder~~	~~109.8~~	~~14.18 x 1.5 Vented Disc~~	~~275 tire: LS1: 3300 LS2: 3350~~	~~N/A~~	~~Either engine listed permitted for any car classified in this specification line. ARE dry sump kit consisting of pump #3021S, Pan 1005M and oil tank 7007-2 or Aviaid dry sump kit #008-10001 consisting of pump 13110-1187, pan 52504-10001 and oil tank 57525 are allowed. Pumps may be driven by a crank mounted, toothed style pulley and belt. Plumbing, hardware, brackets, hoses, and fittings to install above kits are free. For the LS1connecting rods Callies p/n CSC6100DS6A2AH, Scat rods p/n 2-1CR6100-944, GM performance rods p/n 12649190. Either engine may be used in any car in this specification line. Camshaft lift tolerance is .076 mm.~~
~~Spec Mustang (SMG) (Restricted Prep.)~~	~~107.1~~		~~3400~~	~~N/A~~	~~Must meet all requirements of Spec Mustang rules located in Appendix M. No other AS allowances may be used if the car is running under the SMG ruleset.~~

In AS Spec Lines, add updated Spec Line in its entirety as follows:

AS	Wheelbase (in.)/Tire	Engine/Weight (lbs.)	Flat Plate Restrictor Size	Notes
Cadillac CTS-V	113.4/275	Full Prep-up to 313/3400	N/A	Alternate OEM/replacement part 5-lug wheel bearing allowed. SKF bearing p/n BR930081 (or equivalent) rear bearing, used on front and rear positions. OEM Driveshaft may be replaced by Driveshaft Shop P/N– GMCTSV2-C (1-piece carbon fiber.)
		Full Prep >313/3600	N/A	
		Crate/3400	N/A	
		LM7/3400	N/A	
		LS1/3350	N/A	
		LS2/3400	N/A	
		LS6/3400	N/A	
		LS3/3600	65 mm	
		LT1/3600	60 mm	
Chevrolet Camaro,Pontiac Firebird (70-81)	108.0/275	Full Prep-up to 313/3400	N/A	Inner fenders are not required. VSE 52800 or UMI 2664 sub-frame mounts allowed, VSE 52706 front structure kit permitted, OEM-style ball joints with taller than stock stud lengths, +1/2" taller are permitted. Adjustable front upper control arms permitted including SPC 94340 or 97130 and UMI 2656-1. Knuckles are free to allow for brake conversion. Coil over shocks permitted in the front suspension along with lower control reinforcement for mounting. Rear suspension type must be maintained along with mounting location, front and rear spring eye height may be adjusted providing ride height adjustment.
		Full Prep>313/3600	N/A	
		Crate/3400	N/A	
		LM7/3400	N/A	
		LS1/3350	N/A	
		LS2/3450	N/A	
		LS6/3450	N/A	
		LS3/3600	65 mm	
		LT1/3600	60 mm	
Chevrolet Camaro,Pontiac Firebird (82-92)	101/275	Full Prep-up to 313/3300	N/A	Camaro only: To aid cooling, the center of the grill opening (license plate area), absorbing material, metal bumper in the resulting open area, and bumper backing may be removed. OEM-style ball joints with taller than stock stud lengths are permitted.
		Full Prep >313/3500	N/A	
		Crate/3300	N/A	
		LM7/3300	N/A	
		LS1/3200	N/A	
		LS2/3400	N/A	
		LS6/3400	N/A	
		LS3/3500	65 mm	
		LT1/3600	60 mm	
Chevrolet Camaro, Pontiac Firebird (93-02)	101.1/275	Full Prep-up to 313/3300	N/A	Full Prep: Underside of cowl may be modified to facilitate carb installation. The cowl and shock tower sheet metal may be modified to all the installation of an 82-92 F-body brake booster and master cylinder. Engine/transmission installation procedure as provided by SCCA Road Racing Technical Department shall be utilized. BMR AA004 or UMI 2310 adjustable front upper control arm may be installed. Parts specific to the SS Camaro and Firehawk/WS6 Firebird in the drivetrain/exhaust manifolds/headers/intake manifolds/intake components are not classified in American Sedan.
		Full Prep>313/3500	N/A	
		Crate/3300	N/A	
		LM7/3300	N/A	
		LS1/3200	N/A	
		LS2/3400	N/A	

		LS6/3400	N/A	
		LS3/3500	65 mm	
		LT1/3600	60 mm	
Chevrolet Camaro (10-15)	112.3/275	Full Prep-up to 313/3400	N/A	Max wheel Dia, 20.0 inches. ZL1 Front Fascia and grill is permitted . Cowl maybe modified for clearence. Belt tensioner part number GM 12569301 allowed. Full/prep:Engine/transmission installation procedure as provided by SCCA Road Racing Technical Department shall be utilized. Passenger side head must be 2-5/8 min from the firewall.
		Full Prep>313/3600	N/A	
		Crate/3400	N/A	
		LM7/3400	N/A	
		LS1/3350	N/A	
		LS2/3450	N/A	
		LS6/3450	N/A	
		LS3/3600	65 mm	
		LT1/3600	60 mm	
Chevrolet Camaro (16-	110.6/275	Full Prep-up to 313/3400	N/A	Max wheel Dia, 20.0 inches. ZL1 Front Fascia and grill is permitted . Belt tensioner part number GM 12569301 allowed. Full prep: Engine/transmission installation procedure as provided by SCCA Road Racing Technical Department shall be utilized. Passenger side head must be 2-5/8 min from the firewall.
		Full Prep>313/3600	N/A	
		Crate/3400	N/A	
		LM7/3400	N/A	
		LS1/3350	N/A	
		LS2/3450	N/A	
		LS6/3450	N/A	
		LS3/3600	65 mm	
		LT1/3600	60 mm	
Dodge Challenger (08-20)	116.0/275	5.7L/3600	N/A	Max. Wheel Size Dia. 20.0 inches. Minimum ride height, 4.00 inches. Dodge 1GL20TZZAB and 82211606 rear spoilers permitted. Dodge 68043390AA air dam permitted. Mopar Performance Parts camshaft stage2 Kit P/N-77072313AB is permitted on the 5.7l engine. All engine displacements are eligible in all model years, with each engine being used as a complete assembly. Alternate front upper control arms are permitted.
Restricted Prep Engine		6.1/3600	N/A	
Iron Block, AL heads, 2 valves	116.0/295	6.4L/3700	80 mm	
per cylinder				
Ford Mustang Incl. Cobra & Cobra R (79-93) and Mercury Capri (79-86)	100.4/275	Full Prep-up to 313/3200	N/A	OEM-style ball joints with taller than stock stud lengths are permitted. Engine/transmission installation procedure as provided by SCCA Road Racing Technical Department shall be utilized. Charge Motion Control Valves can be blocked off and removed for firewall clearance. Suspension must remain in the stock location.
		Full Prep>313/3400	N/A	
		Crate/3200	N/A	
		Gen1Coyote/3400	67mm	
		Gen2Coyote/3400	61 mm	
		Gen3Coyote/3400	60 mm	
	100.4/295	4.6L 2 or 3 valve/3200	N/A	
Ford Mustang GT (94-04)	107.1/275	Full Prep-up to 313/3300	N/A	Engine/transmission installation procedure as provided by SCCA Road Racing Technical Department shall be utilized. Charge Motion Control Valves can be blocked off and removed for firewall clearance. Suspension must remain in the stock location. Cobra R body work, and independent rear suspension are not permitted. Supercharged motor is not allowed. OEM style ball joints taller than stock stud lengths allowed.
		Full Prep>313/3500	N/A	
		Crate/3300	N/A	

		Gen1Coyote/3400	67mm	
		Gen2Coyote/3400	61 mm	
		Gen3Coyote/3400	60 mm	
	107.1/295	4.6L 2 or 3 valve/3200	N/A	
Ford Mustang Cobra & GT 94-95 Restricted Prep Engine 5.0L&5.8L	101.3/275	up to 313/3150	N/A	Max compression ratio 9.2 : 5.0 motor max lift at valve = .45" For the 5.8 motor, max lift at valve = .48" Full prep clutch, flywheel, headers, and OEM style balljoints with taller than stock stud lengths allowed. Updating and backdating within spec line is allowable. Ford Motorsport #M-6250-F303 camshaft is permitted.
		>313/3250	N/A	
Ford Mustang Coupe GT (05-14)	107.1/275	Full Prep-up to 313/3400	N/A	Charge Motion Control Valves can be blocked off and removed for firewall clearance. Track pack front and rear spoiler allowed.
		Full Prep>313/3600	N/A	
		Crate/3400	N/A	
		Gen1Coyote/3400	67mm	
		Gen2Coyote/3400	61 mm	
		Gen3Coyote/3400	60 mm	
	107.1/295	4.6L 2 or 3 valve/3100	N/A	
Ford Mustang GT 5.0L (15-23)	107.0/275	Full Prep-up to 313/3400	N/A	Charge Motion Control Valves can be blocked off and removed for firewall clearance. Performance pack front and rear spoiler, body kit allowed. Package Brembo front BBK and 380 mm rotors permitted (Ford PN M-23200-V) at no weight penalty. 2014 Mustang GT exhaust manifolds permitted.
		Full Prep>313/3600	N/A	
		Crate/3400	N/A	
		Gen1Coyote/3600	67mm	
		Gen2Coyote/3600	61 mm	
		Gen3Coyote/3600	60 mm	
	107.0/295	4.6L 2 or 3 valve/3100	N/A	
Ford Mustang GT 5.0L (2024-)	107.0/275	Full Prep-up to 313/3400	N/A	2014 Mustang GT exhaust manifolds permitted. Performance pack front and rear spoiler, body kit allowed.
		Full Prep>313/3600	N/A	
		Crate/3400	N/A	
		Gen1Coyote/3600	67mm	
		Gen2Coyote/3600	61 mm	
		Gen3Coyote/3600	60 mm	
	107.0/295	4.6L 2 or 3 valve/3300	N/A	
Pontiac GTO (04-06)	109.8	Full Prep-up to 313/3400	N/A	
		Full Prep>313/3600	N/A	
		Crate/3400	N/A	
		LM7/3400	N/A	
		LS1/3350	N/A	
		LS2/3450	N/A	
		LS6/3450	N/A	

		LS3/3600	*65 mm*	
		LT1/3600	*60 mm*	
Spec Mustang (SMG) Rest. Prep.	*107.1*	*3400*	*N/A*	*Must meet all requirements of Spec Mustang rules located in Appendix M. No other AS allowances may be used if the car is running under the SMG ruleset.*

B-Spec

1. #39416 (Alex Ratcliffe) Add Getrag GS5BG Transmisson Ratios for Mini R50
In B-Spec Spec Lines, Mini Cooper Hatchback (R50) MT (02-06), change as follows:
Gear Ratios: "*Midland:* 4.10, 2.37, 1.56, 1.17, 1.00 *Getrag: 3.308, 1.913, 1.258, 0.943, 0.806*"

Final drive: "*Midland:* 3.51 *Getrag: 4.352*"

Notes: "Approved parts: Progress rear sway bar 62.0210, Mevotech lateral link CMK100003. Ride height measured from the metal underneath the bottom of the plastic door rocker molding shall be no less than 5 inches. *Vehicles originally equipped with a Midland transmission assembly may update to a Getrag transmission assembly.*"

2. #39477 (B-Spec/C-Spec Committee) Expire OBX Header for the R56 Mini Cooper
In B-Spec Spec Lines, Mini Cooper (R56) MT (07-10), add to Notes the following:
"OBX header #10-2101-2S will expire *effective 1/1/2027*."

In B-Spec Spec Lines, Mini Cooper Clubman (R55) (07-10), add to Notes the following:
"OBX header #10-2101-2S will expire *effective 1/1/2027*."

3. #39669 (B-Spec/C-Spec Committee) Exhaust Rules Update
In GCR, Section 9.1.10.E, change as follows:
"25. OEM *or approved* primary/upstream catalysts are required unless a vehicle's spec line ~~has~~ *lists* an approved header ~~listed~~ or ~~is~~ specifically permit~~ted~~*s* ~~to~~ remove*ing* the catalyst. The primary/upstream oxygen sensor must be installed and functional. Secondary oxygen sensors *and catalysts* may be removed. The exhaust system downstream of the primary catalyst/approved header ~~may be replaced~~ *is free* provided the system retains the original routing and exits the body in the approximate location(s) as the OEM system. Single exhaust systems that are cosmetically split into dual outlets may use a single outlet. OEM heat shields and/or exhaust heat wrap may be used."

4. #39727 (Aaron Fitzsimmons) Please reinstate KW suspension for R56
In B-Spec Spec Lines, add to notes the following:
Mini Cooper (R56) MT (07-10):
"*World Challenge suspension kit permitted.*"

Mini Cooper (R56LCI) MT (11-13):
"*World Challenge suspension kit permitted.*"

5. #39817 (B-Spec/C-Spec Committee) Add approved replacement catalysts
In B-Spec Spec Lines, add to Notes the following:
Sonic (All): "*WALKER 16657*"

Fiesta (All): "*WALKER 16610*"

Fit (09-14): "*WALKER 16706*"

Fit (15-19): "*WALKER 16947*"

Accent (All): "*WALKER 16680*"

Rio (All): "*WALKER 16680*"

Mini R50 (02-05): "*WALKER 14716*"

Mini (All R56, R56 LCI, Coupe, and Clubman): "*WALKER 16650*"

6. #39818 (B-Spec/C-Spec Committee) Yaris/Versa catalyst removal
In B-Spec Spec Lines, add to Notes the following:
Nissan Versa Sedan (2012-2019):
"*OEM exhaust manifold required. Primary catalyst may be removed.*"

Nissan Versa Hatchback (2012-2019):
"*OEM exhaust manifold required. Primary catalyst may be removed.*"

Toyota Yaris Hatchback (07-11):
"*OEM exhaust manifold required. Primary catalyst may be removed.*"

Toyota Yaris Hatchback (12-18):
"*OEM exhaust manifold required. Primary catalyst may be removed.*"

Toyota Yaris Sedan (07-12): Approved parts:
"*OEM exhaust manifold required. Primary catalyst may be removed.*"

C-Spec
1. #39653 (B-Spec/C-Spec Committee) Remove VW Jetta (2011-15) from C-Spec
In C-Spec Spec Lines, remove VW Jetta (2011-15) spec line in its entirety.

2. #39654 (B-Spec/C-Spec Committee) Update C-Spec Minimum Weights
In C-Spec Spec Lines, change Minimum Weights as follows:
Chevrolet Cruze (2010-16): "~~2500~~*2700*"

Ford Focus Hatchback/Sedan (2012-18): "~~2905~~*2900*"

Honda Civic Coupe/Sedan (2012-15): "~~2545~~*2650*"

Honda Civic Coupe/Sedan (2006-11): "~~2545~~*2650*"

Mazda 3i MZR (2010-2013): "~~2690~~*2750*"

Mazda 3i (2004-09): "~~2690~~*2750*"

Toyota Corolla (2007-12): "~~2475~~*2550*"

Toyota Corolla (2013-18): "~~2630~~*2650*"

Electric Vehicle
None.

Formula/Sports Racing
SRF3
1. #39899 (Robey Clark) SRF3 Spark Plugs
In SRF, GCR section 9.1.8.D.2.H.18, add the following:
"Spark Plugs: P/N G301041 ONLY NGK LTR7IX-11 */ Washers or sealing rings are not allowed for any purpose.*"

GCR
1. #39504 (Sydney Yagel) Updates Regarding Incident Reporting Changes
In Observer's Reports, GCR section 5.12.1.B.1, change as follows and re-letter the following sections accordingly:
"~~f. Full details of any incidents,~~"

In Assistant Chief Steward – Safety, GCR section 5.12.4.A, change as follows:
"Investigate accidents and ~~forward the originals or scanned pdf by electronic filing of all reports, including original releases,~~ *submit reports and releases via SCCA Member Account Portal or email* to the Sanction/Insurance Department of the SCCA."

In Assistant Chief Steward – Safety, GCR section 5.12.4.C, change as follows:

"~~Mail or e~~*E*mail copies of the material sent to the SCCA Sanction/Insurance Department to the Divisional Safety Administrator *(if applicable)*."

General

None.

Grand Touring

GT General

1. #39862 (SCCA Staff) Remove GT3U from GCR as it is now in STU

In GCR, change as follows:

9.1.2 Page 68: "~~GT-3U (GT3U)~~"

9.1.2.F page 320: "9.1.2.F. GT-2, 3, ~~3U~~ LITE CATEGORY SPECIFICATIONS"

9.1.3.9 Page 320: "~~9. All GT3U (Majors and Runoffs) cars using up to 15”x7” wheels limited to 225 section width tires shall run at current GT3 race weight plus 225lbs. All Gt3U cars shall run a DOT approved tire with a maximum section width of 245. GT3U cars are allowed optional 15”x9” wheels with a 1.5% weight addition or up to 18”x9” wheels with a 3.0% weight addition to the total weight including the 225 lbs. TCR cars are ineligible for GT3/GT3U.~~

Table B: Alternate Vehicle and Engine Allowances Page 461:

“*Increase the minimum weight of all GT3/GT3U 2.0 liter unrestricted engines to +75 lbs. All GT3 cars running in STU must meet the minimum ride height of 3.0” for the main frame rails not including rub blocks and a 2” minimum for the front spoiler and splitter."*

GT1

1. #39713 (Cameron Wagner) Reduce Weight for GM 275ci Carbureted V6s

In GCR, Section 9.1.2.D.E.b., V-6 - up to 275 (4.5), change as follows:

"~~2345~~*2295*"

GT2

1. #39625 (Kevin Park) Classification Request - Ginetta G56 GT4 (V8)

In GT2 Spec Lines, GT Cars - GINETTA, classify Ginetta G56 GT4 (V8) as follows:

GT Cars - GINETTA					
Model	Years	Body Style	Drive-line	Wheel-base (in)	Notes
Ginetta G56 GT4 (V8)	*N/A*	*2 dr.*	*RWD*	*N\A*	

In GT2 Spec Lines, GT Engines, classify GM LS as follows:

GT Engines - Ginetta

Engine Family	Engine Type	Bore x Stroke (mm)	Disp. (CC)	Head Type	Valves / Cyl.	Fuel Induction	Weight (lbs)	Notes
GM LS	*V8 OHV*	*103.25mm x 92mm*	*6.2L*	*Alum.*	*2*	*72mm FPR*	*3300*	

2. #39864 (Grand Touring Committee) Audi R8 GT4 remove spec line notes
In GT2/ST Spec Lines, AUDI R8 GT4, change Notes as follows:
"~~Must have GT4 rules in possession at all race events.~~*Please see note at top of GT2-ST Header.*"

Improved Touring
None.

Legends Car
None.

Production
FP
1. #39850 (DANIEL SNOW) Correct Valve Sizes on FP Fiat x19 1300 and 1500
In FP Spec Lines, change Drivetrain Notes as follows:
Fiat X-1/9 & Bertone 1300:
Valve Size: "~~(I) 35.5/(1.40) (E) 31.3/(1.23)~~ *(I) 36.3/(1.43) (E) 31.2/(1.23)*"

Fiat X-1/9 & Bertone:
Valve Size: "~~(I) 35.5/(1.40) (E) 33.0/(1.30)~~ *(I) 36.3/(1.43) (E) 33.3/(1.31)*"

2. #39851 (DANIEL SNOW) Dual Carburetor Adjustments
In FP Spec Lines, Fiat X-1/9 & Bertone, change Drivetrain Notes as follows:
"(2) auto-type side-draft w/~~28~~*30*mm choke(s) on I.R. manifold"

HP
1. #39604 (Chuck Allard) Clarification On Oil Cooler Ducting
In GCR, Section 9.1.5.E.6.g.4, add the following:
"*On mid and rear engine cars, a single inlet hole may be cut in the front bodywork and a single outlet hole may be cut in the front trunk floor or a wheel well, for the sole purpose of ducting air to a single engine oil cooler. The size of these holes may be no larger than the area of the oil cooler itself.*"

2. #39853 (Jose Fabian) Honda Fit 2015-19 Error in Engine Classification
In HP Spec Lines, Honda Fit (15-19), change Engine Type Mat'l Block/Head as follows:
"4 Cyl. ~~SOHC~~*DOHC*"

Spec Mazda (SM/SMX)
None.

Super Production
None.

Super Touring
STU
1. #39767 (Marc Hoover) Fab 9 Racing Intake Manifold in STU
In STU Spec Lines, Table A: Alternate Vehicle and Engine Requirements, Mazda MZR (LF, L3, L5), add to Notes as follows:
"Short blocks, heads, and intakes may be freely swapped within these engine designations. May use Goodwin Part # 61-2510, Gato Performance Part # 31972*,* ~~or~~ Jack Spania Racing 70 mm sheet-metal aluminum *or Fab 9 Elite NC MX5 Performance* Intake manifold. Must use stock throttle body or Acura part number 16400-PND-A17."

Touring
T1
1. #39542 (Roy Lipner) Replace OEM Heat Exchanger (Intercooler) With Aftermarket
In T1 GT4 Spec Lines, Spec Line 4030-, add to Chassis Notes the following:
"*Wagner Tuning # 200001124 Intercooler allowed.*"

T2
1. #39861 (Harley Kaplan) BMW 240i Permitted Tune
In T2 Spec Lines, BMW M235iR (-2016), change Notes as follows:
"~~Alternative tune permitted.~~"

T3
1. #39701 (Nicolas Hammann) Nissan 370Z Tire Size
In T3 Spec Lines, Nissan 350Z Track/ Touring/Standard/ Nismo (03-08), change Max Tire Size as follows:
"~~255~~*275*"

In T3 Spec Lines, Nissan 370Z, incl. Nismo (2009-2022), change Max Tire Size as follows:
"~~255~~*275*"

2. #39819 (Clayton Cavell) 986 Boxster S Wheel Width
In T3 Spec Lines, Porsche Boxster/ Boxster S (00-04), change Max Wheel Size as follows:
"18 x ~~8~~*9*"

3. #39839 (Scott Bolster) Request Update to T3 Camaro V6 (10-15) Spec Line
In T3 Spec Lines, Chevrolet Camaro V6 (10-15), change as follows:
Max Wheel Size: "~~18~~*20* x 9"

Notes: "800lb max spring F&R. SS front fascia, spoiler allowed. ~~1LE SS Track Pack permitted part #23123398 .~~ Tower Brace 22756880, red. TPR rear upper shock mount #22122, Pfadt lower control arm reinforcement # 1410135, # 009-92200, ~~Brake Kit SS (p/n 23120542)~~ For 2011 cars adaptor kit p/n (23484*878). AC Delco Part #: 1750637 SS Master Cylinder permitted*. *Rear rotors up to 366mm permitted. 28mm Sway bars permitted Front and rear.*"

4. #39870 (Touring Committee) Audi S4
In T3 Spec Lines, classify Audi S4 (12-14) as follows:

T3	Bore x Stroke(mm)/ Disp. (cc)	restrictor	Max Wheel Size (inch)	Tire Size (max)	Gear Ratios	Final Drive	Brakes (mm)	Weight (lbs)	Notes:
Audi S4 (12-14)	*84.5 X 89.0 2995*	*55 mm FPR*	*18x9*	*255*	*3.68 2.16 1.52 1.13 0.92 0.78* *S-Tronic 3.88, 2.24, 1.56, 1.18, 0.92, 0.75, 0.62.*	*2.85*	*(F) 345 Vented (R) 330*	*3800*	*Max spring rate 1100#/in. front and rear. F sway bar 30mm, rear sway bar 24mm SPC front upper arms 81360. Separate coolant reservoir for the water to air intercooler permitted.* ****Must compete in 3 Hoosier Super Tour races to qualify for the Runoffs****

T4
1. #39802 (Josh Smith) ND MX-5 Spec Line Rewrite Request
In T4 Spec Lines, Mazda MX5 Miata/Club/ RF (19-24), change as follows:
Weight: "~~2750~~*2650*"

Notes: "Factory bolt-in roll bar/ cross member may be removed to facilitate roll cage installation. The following item(s) must remain stock: transmission differential unless specified below. Retractable hardtop option permitted but must be disabled from moving action and positively fastened. Any OEM or aftermarket hardtop is permitted that retains the OEM roof silhouette, including Mazda hardtop part #0000-07-5902-ND. ~~29mm (f) 16mm (r) sway bars allowed. 3rd and 4th gear may be replaced with the following parts- (0000-02- 5803-02, 0000-02-5803-01, 0000-02-5804-02, 0000-02-5804-01). Suspension package permitted with a 100 lbs. weight increase that includes the following parts: front springs #0000-04-9700-08, s~~ *Suspension Permitted: S*prings up to 500lb front and 300lb rear allowed. *29mm (f) 16mm (r) sway bars allowed.* Mazda tower brace 0000-

04-5626 allowed. Mazda header 0000-06-5410 allowed. Gear kit Kit PT#- 0000-02-6100. *3rd and 4th gear may be replaced with the following parts- (0000-02- 5803-02, 0000-02-5803-01, 0000-02-5804-02, 0000-02-5804-01). OEM Club Package Brembo calipers permitted. 2016-2018 chassis/body permitted.*"

In T4 Spec Lines, Mazda MX-5 Miata/ Club (16-18), change as follows:
Weight: "~~2575~~2550"

Notes: "~~Factory bolt-in roll bar/ cross member may be removed to facilitate roll cage installation. Retractable hardtop option permitted but must be disabled from moving action and positively fastened. Any OEM or aftermarket hardtop is permitted that retains the OEM roof silhouette, including Mazda hardtop part #0000-07-5902-ND 29mm (f) 16mm (r) sway bars allowed. Up to 500lb front and 300lb rear springs allowed. Mazda Motorsports Header part #0000-06-5410 allowed. Mazda tower brace 0000-04-5626 allowed. 3rd and 4th gear may be replaced with the following parts- (0000-02-5803-02, 0000-02-5803-01, 0000-02-5804-02, 0000-02-5804- 01). Gear kit Kit PT#- 0000-02-6100~~*Factory bolt-in roll bar/ cross member may be removed to facilitate roll cage installation. The following item(s) must remain stock: transmission differential unless specified below. Retractable hardtop option permitted but must be disabled from moving action and positively fastened. Any OEM or aftermarket hardtop is permitted that retains the OEM roof silhouette, including Mazda hardtop part #0000-07-5902-ND. Suspension Permitted: Springs up to 500lb front and 300lb rear allowed. 29mm (f) 16mm (r) sway bars allowed. Mazda tower brace 0000-04-5626 allowed. Mazda header 0000-06-5410 allowed. Gear kit Kit PT#- 0000-02-6100. 3rd and 4th gear may be replaced with the following parts- (0000-02- 5803-02, 0000-02-5803-01, 0000-02-5804-02, 0000-02-5804-01). OEM Club Package Brembo calipers permitted.*"

2. #39831 (David Mead) 4.0 Mustang spec line cleanup
In T4 Spec Lines, Ford Mustang V6 (05-10), change Notes as follows:
"~~ABS (option code 552) allowed. FR3 Handling Pack #M-2007-FR3V6 allowed (kit does not need to be run in its entirety). The kit includes: Dampers M-18000-A, Lowering Springs M-5300-N, Sway Bars M- 5490-C, Strut Tower Brace M-20201-F. Ford Positraction LSD part #M-4204-C75 is allowed. Any springs max F: 500 and R: 400 permitted. Any sway bar up to F: 35mm and R: 28mm permitted. Aftermarket Shocks conforming to T4 rules allowed. Panhard bar, part # BAR-M-4264-A permitted or any pan hard bar permitted must be set at same length as a stock bar, center mounting hole to center mounting hole +/- 0.25 inch. An alternative steel drive shaft is permitted; this drive shaft is otherwise unrestricted, but no modifications to other components are permitted to facilitate its installation. An Aluminum driveshaft is allowed. Any LSD permitted. Ford brake kit M-2300-D allowed. Aftermarket header allowed. GT 8.8 rear axle assembly allowed. 3.45 or 3.55 final drive ratio allowed. 7.5 rear axle assembly with 3.45:1 final drive allowed. Cold Air Intake allowed. Koni part numbers 8741-1494SPORT (front) and 8241-1240SPORT (rear). Spec clutch #SF661 and flywheel #SF66A permitted. 14" Brembo Brake Kit#M-2300-S permitted~~*Any springs max F: 500 and R: 400 permitted, Any sway bar up to F: 35mm and R: 28mm permitted. Any pan hard bar permitted must be set at same length as a stock bar, center mounting hole to center mounting hole +/- 0.25 inch. Any alternate metal driveshaft is allowed. Ford brake kit M-2300-D allowed. 14" Brembo Brake Kit#M-2300-S permitted with OEM 355mm rotors allowed. Aftermarket header allowed. Cold Air Intake allowed. S197 Mustang 8.8 or 7.5 rear axle allowed with any ratio. Spec clutch #SF661 and flywheel #SF66A permitted.*"

Fastrack news
official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Michael Cooke vs. SOM COA Ref. No. 25-18-SE
February 6, 2026

FACTS IN BRIEF

On Saturday, November 1, 2025, following Race 1 for Group 3 at the 32nd American Road Race of Champions held at Michelin Raceway Road Atlanta, Chief Steward Russ Gardner filed a Request for Action (RFA) seeking investigation of contact between Super Production Under (SPU) #119, driven by Ricky Sanders, and E Production (EP) #17, driven by Michael Cooke, and unrelated infractions by Mr. Sanders.

The Stewards of the Meeting (SOM) Barry Morton, Peter Olivola, Candace Osborne, and Robert Mayes, Chair, met, reviewed the available evidence, and concluded regarding the contact Mr. Cooke violated General Competition Rules (GCR) 6.11.1.A. (Avoidable Contact) by contacting Car #119 at Turn 10A. The SOM penalized Mr. Cooke with a reprimand and assessed one penalty point on his competition license.

Mr. Cooke appealed the portion of the decision of the SOM that applied to him.

DATES OF THE COURT

The SCCA Court of Appeals (COA), Lee Hill, Laurie Sheppard, and Jack Kish (Chair) met on November 21, 2025, and January 22, 2026, to review, hear, and render a decision on the appeal.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Appeal letter from Mr. Cooke, submitted November 10, 2025.
2. Official Observer's Report, video, and related documents, received November 17, 2025.
3. SOM statement, received November 17, 2025.
4. Additional evidence gathered by the new SOM, received January 13, 2026.
5. Hearing & Decision form submitted by the new SOM, received January 13, 2026.

FINDINGS

In his appeal, Mr. Cooke asserted only GCR 6.11.1.A. (Avoid physical contact between cars) applied in this situation as he fully complied with the remaining sub-sections of GCR 6.11.1. (Rules of the Road). He further stated the contact occurred because Mr. Sanders (EP #119) altered his line under braking and removed Mr. Cooke's racing room.

The COA was unable to provide a fair analysis of the process and substance of the initial SOM decision due to technical issues noted during the original first court's investigation and limited documentation. Accordingly, the COA invoked GCR 8.4.5.A.2. and requested the Chair of the Stewards Program appoint a new SOM court to rehear the original action. The COA tabled Mr. Cooke's appeal and set aside the assigned penalty pending a ruling from the new SOM court.

The new SOM court Bill Johnson, Julie Riggen, and Matias Bonnier (Chair) met, heard witnesses, reviewed witness statements and video, and reached a decision on the original RFA. Regarding the contact, the SOM concluded Mr. Cooke violated GCR 6.11.1.A. On January 12, 2026 the new SOM court informed Mr. Cooke of their decision. He was penalized with a reprimand and one penalty point on his competition license. All parties named in the RFA were notified on this date of the full decision, and of their rights to appeal the decision.

Mr. Cooke was offered the option to withdraw or continue his original appeal. He chose to continue his appeal of the new decision on the same grounds.

The COA examined the evidence gathered by both the original and the new SOM related to the contact, including video not available to the original court. Mr. Cooke was taking a tight inside line into Turn 10A. Mr. Sanders completed a pass on Mr. Cooke prior to reaching the corner and then turned to the apex of Turn 10A. Mr. Cooke was unable to slow sufficiently to avoid light contact with SPU #119.

The COA finds the new SOM properly heard the RFA, including all evidence and witness testimony. Mr. Cooke provided no additional evidence in support of the continuation of his appeal. The COA finds the SOM made a thoughtful and reasoned decision based on the testimony and video evidence available and applied a measured penalty which was within their purview.

DECISION
The COA upholds the SOM decision in its entirety. Mr. Cooke's appeal is well founded and his appeal fee, less the administrative portion retained by SCCA, will be returned.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Mike Tabernero vs. SOM COA Ref. No. 26-01-SE
January 30, 2026

FACTS IN BRIEF

On Saturday, January 3, 2026, following Race 1 for Group 7 at the Palm Tree Winter Majors held at Homestead-Miami Speedway, Assistant Chief Steward Joe Stadelmann filed a Request for Action (RFA) seeking investigation of contact between Super Touring Lite (STL) #2, driven by Noel Saks, STL #49, driven by Tom Ghan, and Improved Touring A (ITA) #4, driven by Mike Tabernero, on the front straight at the start of the race.

The Stewards of the Meeting (SOM) Peggie Barten, Sherri Croyle, and Phil Croyle (Chair) met, heard witnesses, reviewed video, and concluded Mr. Tabernero violated General Competition Rules (GCR) 6.11.1.A., B., and D. (Avoidable Contact and Racing Room) by contacting Car #2 on the straight. The SOM penalized Mr. Tabernero with three race weekends probation which incurred three penalty points on his competition license.

Mr. Tabernero appealed the SOM decision.

DATES OF THE COURT

The Court of Appeals (COA) Jack Kish, Lee Hill, and Costa Dunias (Chairman) met on January 22, 2026, to review, hear, and render a decision.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Request to appeal from Mr. Tabernero, submitted on January 11, 2026.
2. Notification of Appeal, received January 14, 2026.
3. Official Observer's Report, in-car videos, and related documents, received January 14, 2026.
4. E-mail comments from Phil Croyle, received January 20, 2026.

FINDINGS

In his Appeal, Mr. Tabernero asserted that the penalty of probation for 3 race weekends plus 3 points against his license seemed excessive for the alleged infraction. He also stated a Miata was pushing and bumping into another Miata, and that car contacted the left rear quarter panel of his car as he started moving down on the track.

The SOM based their decision on the in-car videos and witness statements from several sources. Mr. Croyle explained that given the speed of Car #4's left movement along with Mr. Tabernero's acknowledgement of being unaware of Car #2's existence either before or after the contact, the SOM determined Car #4 was the "primary proximate cause of Car #2's spin into the inside concrete wall." At all times Car #4 had ample room to its right to avoid contact with Car #2 and to provide Car #2 racing room.

The COA reviewed the available videos which showed Car #4 was in the right lane on the right side of the track approaching the start. Car #64 was in the same row on Mr. Tabernero's left, followed by Car #2, on the left in the next row. Car #64 moved quickly past Car #4 and Car #2 began pulling alongside the rear of Car #4. Mr. Tabernero in Car #4, who has stated he was unaware Car #2 had achieved overlap, abruptly moved left trying to follow Car #64. Car #4's left rear contacted Car #2's right front, causing it to spin to the left and into the concrete barrier.

The COA finds the SOM properly heard the RFA, including all evidence and witness testimony. Mr. Tabernero provided no new evidence in support of his appeal. The COA finds insufficient grounds to overturn the SOM's decision. The COA finds the SOM made a thoughtful and reasoned decision based on the testimony and video evidence available and applied a measured penalty which was within their purview.

DECISION
The COA upholds the SOM decision in its entirety. Mr. Tabernero's appeal is not well founded, and his entire appeal fee is retained by SCCA.

Fastrack news
official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Thomas Kaufman vs. SOM COA Ref. No. 26-02-SE
February 6, 2026

FACTS IN BRIEF

On January 4, 2026, following Race 2 for Group 5 at the Palm Tree Winter Majors held at Homestead-Miami Speedway, Chief Steward Stu Cowitt filed a Request For Action (RFA) seeking investigation of contact between Thomas Kaufman, driver of Prototype 2 (P2) #20, and John Goeden, driver of Prototype (P) #29, on the front straight causing both cars to retire.

The Stewards of the Meeting (SOM), Pattie Barten, Sherri Croyle, and Phil Croyle (Chair) met, heard witnesses, and reviewed the evidence. The SOM determined Mr. Kaufman violated General Competition Rules (GCR) 6.11.1.A. (Avoidable Contact), B. (Racing Room), and C. (Blocking) by moving to the right on the front straight resulting in contact and depriving Mr. Goeden of racing room. The SOM penalized Mr. Kaufman with three race weekends probation, which incurred three penalty points on his competition license.

Mr. Kaufman appealed the decision of the SOM.

DATES OF THE COURT

The SCCA Court of Appeals (COA) Costa Dunias, Lee Hill, and Laurie Sheppard (Chair) met on January 29, 2026, to review, hear, and render a decision on the appeal.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Request to Appeal from Thomas Kaufman, submitted January 12, 2026.
2. Official Observers Report and related documents, received January 20, 2026.
3. SOM Video from Car #29, Car #20, and “Drivers Eye” broadcast, received January 20, 2026.
4. Appellant’s (Front-facing) Video, received January 20, 2026.
5. Additional witness statement from C. Bryant, received January 21, 2026.
6. Chair SOM’s Response to Appeal, received January 21, 2026.
7. Screen shot (photos) of Driver’s Eye broadcast, received January 21, 2026.

FINDINGS

In his appeal, Mr. Kaufman asserted he was not responsible for the contact as he was driving his normal predictable race line giving racing room on either side for a safe pass. He stated Car #29 was running parallel to his car while attempting a pass, but Car #29

"began to move left across my path before completing the pass." He further states there was ample room to the right of Car #29 for him to complete a safe pass.

The SOM interviewed both drivers, collected their witness statements, and reviewed the in-car video from both cars as well as the Drivers Eye broadcast video providing a long view down the front straight. Mr. Kaufman was unable to retrieve his front-facing video but did provide video facing to the rear. The SOM applied Appendix P., Section 5 (Passing on Straights) and concluded Mr. Kaufman continued an incremental movement to the right after exiting NASCAR Turn 4 while Mr. Goeden was alongside, thereby causing the contact.

The COA reviewed all videos submitted including Mr. Kaufman's recovered front-facing video, as well as the documentation provided by the SOM including witness statements and all other evidence. Video from all sources show the pass was initiated while both cars were on the oval approaching NASCAR turn 4. Car #20 and Car #29 were close alongside as they approached the front straight where Mr. Goeden, who was still overlapped but partially ahead, was the first to straighten his vehicle. Mr. Kaufman (Car #20) was still exiting the turn and continuing to move slightly up-track. At the point of contact, Car #29 had more than a car-width of open track to his right and had not yet fully cleared Car #20.

The COA notes the January 2026 GCR contains an update in Appendix P. Section 1. (Racing Room and Passing Guidelines) offering expanded guidance on the intent of GCR 6.11.1.D. (Passing). It says, "… a pass is successfully completed when the over-taking car is completely, physically past the car being overtaken. Simply being ahead, while still alongside, does not absolve the driver of the overtaking car of the obligation to allow racing room to the overtaken car." The COA finds both drivers were responsible to provide racing room to the other from the time Car #29 achieved overlap on Car #20 until Car #29 had fully cleared Car #20. Both Car #29 and Car #20 had sufficient available open track to allow safe, side-by-side racing room to the other.

The COA finds both drivers shared responsibility for the race-ending contact. While the GCR places the largest percentage of responsibility for a safe passing attempt on the overtaking driver, an overtaken driver must also exercise control over their own placement on the track. The COA disagrees Mr. Kaufman is solely responsible for this incident and overturns the ruling of the SOM. Mr. Kaufman's full competition privileges are restored and the three penalty points assessed as a result of the initial action are to be removed from Mr. Kaufman's license.

DECISION

The Court of Appeals overturns the decision of the SOM in its entirety. Mr. Kaufman's appeal is well founded, and his appeal fee, less the amount retained by SCCA, will be returned.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Scott Sewell vs. SOM COA Ref. No. 26-03-SW
February 13, 2026

FACTS IN BRIEF

On January 18, 2026, following Race 2 for Group 6 at the Polar Prix Majors held at MSR Cresson, Assistant Chief Steward Bob Neff filed a Request For Action (RFA) seeking investigation of contact between Scott Sewell, driver of Touring 2 (T2) #114, and CJ Cramm, driver of Grand Touring 2 (GT2) #04, in turn 1 causing Car #04 to retire.

The Stewards of the Meeting (SOM), Jessica Althoff, James Rogerson, and Nadja Pollard (Chair) met, heard witnesses, and reviewed the evidence. The SOM determined Mr. Sewell violated General Competition Rules (GCR) 6.11.1.A. (Avoidable Contact), B. (Racing Room), C. (Blocking), and D. (Pass responsibilities) by turning in at turn 1 resulting in side-to-side contact and depriving Mr. Cramm of racing room. Mr. Sewell was also cited for violating GCR 6.11.1.E. and Supplemental Regulations (Supps) V.D. (Required to report after contact) and GCR 9.3.11.A. (Failure to provide video). The SOM penalized Mr. Sewell with three race weekends probation, which incurred three penalty points on his competition license.

Mr. Sewell appealed the decision of the SOM.

DATES OF THE COURT

The SCCA Court of Appeals (COA) Jack Kish, Laurie Sheppard, and Lee Hill (Chair) met on February 5, 2026, to review, hear, and render a decision on the appeal.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Request to Appeal from Scott Sewell, submitted January 27, 2026.
2. Official Observers Report and related documents, received January 30, 2026.
3. SOM Video from Car #04, Car #94, and spectator video, received January 30, 2026.
4. Additional video from Car #07 and Car #94 provided by the appellant, received January 30, 2026.

FINDINGS

In his appeal, Mr. Sewell asserted he was not responsible for the contact as he was aware of the approaching cars, held his line on the right side of the track, and left room for the following cars to safely pass on his left.

The SOM interviewed both drivers, reviewed the in-car video from both Mr. Cramm's car and trailing Car #94, a spectator video providing a view of the incident from the right, and a witness statement from a Marshal on the start stand. The SOM determined Mr. Sewell did not allow racing room to Car #04 resulting in side-to-side contact. Car #04 spun to driver left, came to a stop off track, and was unable to continue.

The COA reviewed all videos submitted including additional video from trailing Car #07 provided by Mr. Sewell, as well as the documentation provided by the SOM. Video from all sources show the leaders, Car #07 and Car #04, gaining ground and about to lap Car #114, who was right of center track for the entire length of the straight. Cars #07 and #94 were approaching on the left side of the track while Car #04 was to their right alongside Car #07. Car #04's video shows the brake lights illuminating on Car #114 as it reached the brake zone for turn 1. At that time Car #04 was approximately 2 car lengths behind Car #114. Car #04 moved right and dove towards the apex as Car #114 began to turn in to turn 1. Car #04 was unable to complete the pass before the contact between the left side of Car #04 and the right side of Car #114 occurred.

The COA notes the January 2026 GCR 6.11.1.D. states, "*The overtaking driver is responsible for the decision to pass another car and to accomplish it safely. The overtaken driver is responsible to be aware that they are being passed and not to impede or block the overtaking car*".

The COA finds Mr. Cramm was primarily responsible for the race-ending contact. Mr. Sewell was aware of the approaching cars, selected a reasonable line that allowed safe passing to his left, and behaved in a predictable manner. Mr. Cramm made a late decision to pass on Mr. Sewell's right. Car #04 was not fully alongside Car #114 before Car #114 began to turn in and therefore Car #04 had not established a right to racing room. The COA disagrees Mr. Sewell was responsible for this incident and overturns the portion of the ruling by the SOM pertaining to GCR 6.11.1.A.-D. As Mr. Sewell did not provide in-car video, the COA finds no evidence to contradict the violations of GCR 6.11.1.E., Supps V.D., and GCR 9.3.11.A. The COA modifies the penalty against Mr. Sewell to a Reprimand, which incurs one point against his competition license. Mr. Sewell's full competition privileges are restored and the three penalty points assessed as a result of the initial action are to be modified as stated.

DECISION

The Court of Appeals overturns the portion of the decision of the SOM regarding violation of GCR 6.11.1.A.-D. and modifies the penalty. Mr. Sewell's appeal is well founded, and his appeal fee, less the amount retained by SCCA, will be returned.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

RACING COMPETITION COMMITTEE MINUTES | March 3, 2026

We appreciate the feedback and perspectives that our members provide, and we'd like to thank you for your outreach and being part of the process. Should you have any requests or feedback to share with the Road Racing Competition Committee or a class advisory committee, please visit https://crbscca.com/ to submit a letter.

The Road Racing Competition Committee met by teleconference on March 3, 2026. Participating were Dayle Frame, Chairman; David Arken, David Locke, Jim Goughary, Sam Henry, Tom Start and Shelly Pritchett, secretary. Also participating were: Bob Crawford, BoD Chairman, David Brown, Mark Weber and Sam Fouse, BoD liaisons; Eric Prill, Vice President, Road Racing, Sydney Davis Yagel, Senior Manager of SCCA Road Racing, Scott Schmidt, Road Racing Technical Manager, Scott Dobler, Road Racing Series Manager. The following decisions were made:

Member Advisory
None.

No Action Required
General
1. #39966 (David Gomberg) Response to Letter #39770 in Preliminary Minutes
While not all members utilize Facebook as a social media platform to communicate, that is currently the only option we have for members to have two-way conversations. As our new website gets up and running, it's something we will look into and see if adding a comment/chat function is in our purview.

GT2
1. #39811 (Mitchell Durham) GT2 Class Engine Restrictions
The RRCC feels this car is a GT2-ST classification car and GT2-ST rules do not allow for de-stroking an engine. The GT2 class rules primary apply to a tube frame built construction race car and de-stroking is also not allowed unless addressed on the cars Spec Line "Notes". Please re-submit a letter requesting that your car be classified into GT2-ST.

HP
1. #39917 (TIM LINERUD) DCOE 40 vs DCOE 45 Weber Carb
To clarify your question, the only legal DCOE size will be specified on the spec line. For example, if use of a "40 DCOE" is what's specified, then using a 45 DCOE with 40mm chokes would not be considered legal.

Not Recommended
GCR
1. #39286 (Fred Brinkel) Request for Review
The Road Racing Competition Committee does not recommend changing "Protest" to "Request for Review" at this time. The consensus is that the change could be incorporated in a more general and comprehensive update of the GCR and associated SCCA forms at a later date.

2. #39288 (Fred Brinkel) Change to 8.4.3.B.3.
The Road Racing Competition Committee does not recommend making changes to the wording associated with the appeals process and monetary fines associated with appeals at this time.

3. #39878 (Tobin Schuster) Clarification for Proposed #39513 Changes
For a car to touch the track during an SCCA event, the car must be entered in the event. Classification as a DNS is appropriate even if the car only turns a hardship lap.

T2
1. #39359 (Rylan Hazelton) Additional Option for TCR cars
The addition of a second spec line for every TCR car to allow higher power with higher weight would require double the BOP monitoring, and the TAC does not wish to attempt it at this time.

2. #39742 (John Heinricy) RE Letter #394426 Rebalance Cadillac Blackwing for 2026
Mr. Heinricy, this is the 7th letter you have written requesting non-OEM allowances for the Blackwing and this will be the 7th time you have received the same answer regarding tires and other performance enhancements. The car has previously been allowed alternate rear springs, and adjustable anti roll bars. Contrary to the statement in your letter that you are making a reasonable request, since you are aware of the requirements for HP control, this letter-writing campaign is not reasonable.

The original classification discussed between SCCA and GM representatives (covered in letters 32266 and 32535 in 2022) were clear and unequivocal that until a method that is detectable, enforceable, and reliable to reduce the HP of the Blackwing is provided to and tested by SCCA the Blackwing will not be allowed modification to improve handling and on track performance; the GM representatives agreed to this limitation on performance enhancements. Additionally, GM's stated objective in the conversations with the SCCA representatives is to race the Blackwing without modifications as a sales gimmick, SCCA has received no official communication from a GM representative that this objective has changed. No HP reduction/control methodology has been provided by GM or any competitor racing the platform. The option to race the car in the T1 class, where it already has a spec line, continues to be an option available to you. The Blackwing is already an HP overdog in T2, to allow any performance enhancements would be detrimental to the other competitors in T2. The RRCC suggests you work with GM on the methodology to restrict the HP, alternately run the car in T1 with appropriate T1 competition allowances.

T3
1. #39919 (Aaron Stehly) Camber Adjustable Ball Joints for 2015-2018 VW Golf R
The camber limit rule was recently removed from T2-T4. The intent of this change was to prevent frustrating compliance issues at large events, not to create an arms race to achieve increased camber. Please utilize existing allowances to achieve adequate camber.

Recommended Items
The following subjects will be referred to the Board of Directors for approval. Address all comments, both for and against, to the Club Racing Board. It is the BoD's policy to withhold voting on a rules change until there has been input from the membership on the presented rules. Member input is suggested and encouraged. Please send your comments via the form at www.clubracingboard.com.
None.

Taken Care Of
STL
1. #39723 (Christopher Childs) Weight Changes
Please see the response to letter # 39885 in the current Fastrack.

2. #39725 (Jesse Prather) Unintended Consequences of New Weight Table
Please see the response to letter # 39885 in the current Fastrack.

3. #39726 (Charles Mathes) Request Review of Weight Adjustment in STL
Please see the response to letter # 39885 in the current Fastrack.

STU
1. #39880 (Marc Hoover) Addendum to Letter 39767
Please see the response to letter # 39767 in the March 2026 Fastrack.

T2
1. #39127 (Eric Heinrich) STU-TCR Chart - Huge Loophole Needs Emergency E&O Before Runoffs
Please see letter # 40002 in current Fastrack.

T3
1. #39925 (Ben Slechta) 350Z Spec-line Considerations
Please see letter # 39843 in current Fastrack.

<u>What Do You Think</u>
GT2
1. #39729 (Chris Edens) LS3 Crate Engine in GT2
The Grand Touring Advisory Committee is submitting the following rule change through crbscca.com for your review and suggestions. Please reply with suggestions regarding the following:

In GT2 Spec Lines, (page 344) above GT2 TA2 Cars, insert the following:
"*Any GT2 classification may use a LS3 crate engine regardless of body manufacturer @2800 lbs.*
No changes to the listed specifications or part numbers may be made!

Part Number	*19432414/19434636*
Car Type:	*Any current SCCA GT-2 car*
Weight:	*2,800 LBS with driver*
Engine Type:	*LS Series Gen IV Small Block Chevy*
Displacement:	*376 CI (6.2Liters)*
Bore & Stroke:	*4.065 x 3.622 (103.25 x 92mm)*
Block:	*P/N 12729604 Cast Aluminum 6-Bolt, cross-bolted main caps*
Crankshaft:	*P/N 12736808 Nodular Iron*
Connecting Rods:	*P/N 12649190 Powdered Metal*
Pistons:	*P/N 19207287 Hypereutectic Aluminum*
Camshaft:	*P/N 12623063 Hydraulic Roller*
Valve Lift:	*.551 Intake / .522 Exhaust*
Camshaft Duration:	*@.050In 204 Degree Intake / 211 Degree Exhaust*
Cylinder Heads:	*P/N 12675871 Aluminum L92-Style Port 68cc Chambers*
Valve Size:	*2.165 Intake / 1.590 Exhaust*
Compression:	*10.7:1*

Rocker Arms:	*P/N 12966105 Intake / Roller Trunnion*
Rocker Arms:	*P/N 12681275 Exhaust / Roller Trunnion*
Throttle Body:	*P/N 19420707 90mm ETC*
Intake Manifold:	*P/N 19418261*
Fuel Injectors:	*P/N 12576341*
Fuel:	*92 Octane*
Exhaust-Header:	*Open*"

Resumes
None.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

DATE: March 20, 2026
NUMBER: TB 26-04
FROM: Road Racing Competition Committee
TO: Competitors, Stewards, and Scrutineers
SUBJECT: Errors and Omissions, Competition Adjustments, Clarifications, and Classifications

All changes are effective 4/1/2026 unless otherwise noted. If any day of a race event falls on the first day of the month, the previous month's rules will be in effect for that event only. The new rules will become effective at the conclusion of the race event, unless otherwise noted.

American Sedan
AS
1. #39886 (American Sedan Committee) Header Information Update for EFI Engine Build Sheets
In AS EFI Engine Build Sheets, add to notes as follows:
GM LS1, LS2, LS6: "*Any three stage dry sump is permitted. 1-3/4" diameter headers permitted.*"

GM LS3, LT1: "*Any three stage dry sump is permitted.*"

Ford 4.6L 2V and Ford 4.6L 3V: "*Headers as specified in the Full Prep American Sedan rules may be used. Ford Performance camshaft kit P/N M-6550-3V may be used.*"

Ford Gen 1, 2, and 3 5.0L: "*MMR Secondary Timing Chain Tensioner Bracket #467893 is permitted.*"

Mopar 5. 7L and 6.1L: "*1-3/4" diameter headers permitted.*"

2. #39933 (American Sedan Committee) Errors and Omissions
In GCR, Section 9.1.6.D.5.b.1, change as follows:
"Full Preparation *All cars* ~~only~~:"

In AS Spec Lines, Chevrolet/Pontiac Camaro & Firebird (93-02), change as follows:
Spec Line Engine/Weight (lbs.): "*(1992-1997) LT1 5.7L/3200*"
Flat Plate Restrictor Size Column: "*N/A*"

In GCR Section 9.1.6.F., add Build Sheet as follows:

Engine GM LT1 5.7L (1992-97)	
OEM engine as manufactured for General Motors 93-97 Camaro	
Engine Block Casting	*10125327*
Cylinder Head Casting	*10128374,12551561, 10207643*
Port Volume	
Bore	*4.040in*
Stroke	*3.480in*
Max Rod Length	*5.7"*
Valve Size	*Int.1.940" / Ex.1.60"*

Cam Lift	*.460 Intake / .460 Exhaust*
Cam Timing/Duration	*C/L 117deg Duration @.05 Lift*
Deck Height	*9.00*
Compression Ratio	*10.4:1*
Rocker Arm Ratio	*1.5:1*
Intake Part #'S	*-*
Throttle Body Bore	*48mm (twin)*
Restrictor Plate	*-*
Fuel Injector Part#	*17087325, 354119*
Headers	*1-3/4*

In AS Spec Lines, GM Spec Lines (Cadillac, Chevrolet, Pontiac) change Spec Lines Engine/Weight (lbs.) as follows:
"LT1/*6.2L*/3600"

In GCR, Section 9.1.6.D.1.i. Oiling system, change as follows:
"6. Oil catch tanks are ~~permitted~~ *required. All catch cans must be ventilated to the outside.* All engine breathers or vapor recirculation lines, if disconnected, shall vent to a catch tank of one (1) quart minimum capacity. Such catch tanks shall not be mounted in the driver/passenger compartment."

In AS Spec Lines, Pontiac GTO (04- 06), change Wheelbase (in.)/Tire Column:
"109.8/*275*"

In AS Spec Lines, Ford Mustang GT 5.0L (15-23), Engine/Weight (lbs.) Column:
"Gen3Coyote/~~3600~~*3525*"

B-Spec/C-Spec
None.

Electric Vehicle
None.

Formula/Sports Racing
None.
GCR
1. #39758 (ROBERT WOOLSTON) Feedback on Appendix B rewrite et al
In Production Category Specifications, GCR section 9.1.5.E.9.n, change as follows:
"~~6. The "Trans. Speeds" number listed in a car's specification line indicates the maximum number of forward gears that may be operable by the driver from the normal seated position (e.g. a 6 speed transmission with 1 forward gear removed/disabled is considered a 5 speed transmission).~~"

In Appendix B, Required Contents of Supplemental Regulations, GCR section 1.4.1.I, change as follows:
"The names of the Chief Steward and *if applicable* the Chair of the SOM. For Super Tour events, add the Race Director and the Series Administrator."

In Appendix B, Results, GCR section 1.5.2, change as follows:
"Organizers must distribute Official Race Results to all participants ~~in a timely manner~~ within 7 days of the event~~, or within 7 days of any protest or~~ *unless a* Court of Appeals decision ~~affecting results, whichever occurs first~~*is pending*. Results must be made available by one or more of the following methods:"

2. #39891 (Mike Smith) 9.3.11.A Camera and Mountings
In Camera and Camera Mounts, GCR section 9.3.11.A, change as follows:
"All cars competing at Regionals, Conference Majors, Super Tour events, and the SCCA Runoffs must have a forward-facing camera that is recording at all times while on track and provides a clear horizontal field of view of the cars and track ahead. The camera~~s~~ may be mounted ~~either~~ inside the car, ~~or~~ on the ~~body~~*exterior of the car, or on the roll cage*. *Helmet-mounted cameras do not satisfy the forward-facing camera rule.* If video is needed as part of an investigation *or appeal* of an incident, a competitor's video of the full unedited session may be requested by race officials regardless of whether or not said competitor was involved in the incident. Altering the video in any way or failing to provide such video may result in penalties. Forward-facing cameras are recommended at all other SCCA-sanctioned events. The video format must be a digital file ~~so it can be viewed in an MS Windows compatible viewer~~*provided on a removable USB flash drive or SD card media chip and must be viewable using the VideoLAN VLC media player*."

General
None.

Grand Touring
GT2
1. #39838 (Andrew AQUILANTE) Corvette C7 (14-19) L76 Specline Errors/Missing Changes
In GT2-ST Spec Lines, Chevrolet Corvette (14-19), change as follows:
Minimum Weight: "~~3100~~*3000*"
Restrictor "~~80~~*83*mm FPR"

2. #39936 (Grand Touring Committee) GT2 Porsche 997.2 GT3 Cup
In GT2 Cars - PORSCHE, 997.2 GT3 Cup, change Notes as follows:
"3.8L flat six. 2800 lbs. Aftermarket header allowed. Cars must be prepared in accordance with the appropriate model/year Porsche factory 911 GT3 Cup parts catalog/service manual. Cars may not be altered in any way except as authorized below. Drivers must have the correct year manuals as they apply to their specific car in their possession. Safety, drivers comfort, driver control and instrumentation items may be modified per the GCR. Original factory installed Matter/IMV roll cages are allowed. The stock unmodified fuel tank is allowed. Windshield clips must be installed per GCR 9.3 Windshield Clips/Rear Window Straps. All other SCCA safety standards apply. The following additional modifications are authorized: Alternate hood provided it is a facsimile of the stock part. Any wheel, including 5 bolt (and the required 5 bolt modification to the hubs). Tires per GCR 9.3 Tires. Battery size and location is unrestricted. Shocks are unrestricted but they shall be installed in the stock locations with the stock, unmodified pick up points. Any suspension settings are allowed provided they are achieved without modifications. Machining of suspension components and pick up points to achieve caster/camber/toe is not allowed. Lubricants, consumable fluids (brake fluid, coolant etc.) and oil filters are open free. Modifications listed in Grand Am, IMSA Cup, World Challenge *may be used.* ~~or any other rules, except those listed above, are specifically not allowed. Factory (OEM manufacturer) Lexan front windows allowed as delivered. ABS is allowed.~~"

GTX
1. #39873 (Demetrio Bilbatua) Ferrari 296 GT3 Classification Request
In GTX-MISC Spec Lines, classify Ferrari as follows:

GTX - MISC					
Make	Homologation	Model	Restrictor (mm)	Weight (lbs)	Notes
Ferrari		*296 GT3*	*N/A*	*3000*	

Improved Touring
None.

Legends Car
None.

Planning
None.

Production
None.

Spec Mazda (SM/SMX)
1. #39914 (Josh Smith) Part Number Change Request
In GCR, Section 9.1.7.C.1.j.1.c., change as follows:
"~~0000-10-6900~~*0000-06-5016-KT*"

Super Production
None.

Super Touring
STL
1. #39885 (Jesse Prather) Classifications
In STL, Table A: Alternate Vehicle and Engine Requirements, add the following:
Model: "*Mazda BP 1.6*"
Maximum Displacement: "*1600cc*"
Minimum Weight: "*2160*"

STU
1. #39785 (Kyle Bolden) Mazda Rx-8 Renesis - Streetported Variant & Added Weight
In STU Table B: Alternate Vehicle and Engine Allowances, add the following:
Model: "*Mazda Renesis Street Port*"
Maximum Displacement (cc's): "*N/A*"
Minimum Weight: "*2450*"
Notes: "*Street porting allowed. Alternate 70mm choke throttle body from the following list allowed: OE from 1996- 2004 Mustang 4.6 liter V8; BBK #1700 (e.g., Summit #BBK-1700); Summit #227204; Trickflow #24070 1" thickness max manifold adapter allowed.*"

2. #39872 (Super Touring Committee) Eliminate 33 and 34 mm TIRs
In STU, GCR Section 9.1.4.H.3., change chart as follows:
Inlet Restrictor (mm): "~~33~~"
Minimum Weight (lbs): "~~2380~~"

Inlet Restrictor (mm): "~~34~~"
Minimum Weight (lbs): "~~2525~~"

Touring
T1
1. #39922 (Danny Kellermeyer) Spec line #1139 Restrictor Change Request
In T1 Spec Lines, Spec line 1139, change Required Restrictor as follows:
"~~70mm~~"

T2
1. #39910 (Jimmy Cabrera) 14-17 BMW 435i Brake Approval Request
In T2 Spec Lines, BMW 435i (2014- 2017), Brakes (mm):
"~~(F)340mm (R) 330mm~~*(F)370mm (R) 345mm*"

2. #39947 (Gary D'Abate) Porsche Cayman S Spec Lines Needed for Atlanta HST
In T2 Spec Lines, Porsche Cayman S (06-09), change as follows:
"~~(06-09)~~*(06-08)*"

In T2 Spec Lines, Porsche Cayman S, Spyder (10-12), change as follows:
Year: "~~(10-12)~~*(09-12)*"
Bore x Stroke(mm)/ Displ.: "~~96.0 x 78.0 3387~~*97 x 77.4 3436*"
In T2 Spec Lines, Porsche Cayman S/ GTS (13-15), change as follows:
Year: "~~(13-15)~~*(14-16)"*
Bore x Stroke(mm)/ Displ.: "97 x 77.5 ~~3400~~*3436*"

3. #40002 (Touring Committee) Please address loopholes in T2 TCR
In all T2-TCR Spec Lines, add to Notes the following verbiage to each car:
"*Must conform to "2024 TCR Technical Regulations" prepared by WSC.*"

In GCR, Section 9.1.9.2.E. Car Classification, change as follows:
"These classifications shall be reviewed on an annual basis, and shall be effective as of January 1. Once these classifications have been officially published, models and or specified OEM parts not available to the public or valid SCCA club members by March 1 of the calendar year will not be classified for *Runoffs* competition until the following calendar year.

Touring Category
Classes are as follows: T2, T3, and T4.
1. Weight *and Ballast*
a. The weight is defined by the automobile's specification line. *The weight requirement in the following spec lines supersedes those represented in AS and TCR rules. Weight may be changed mid-season to adjust performance.*
~~2. Ballast~~
~~a.~~ *b. Ballast* - Automobiles may carry ballast to achieve their specification's minimum weight. Refer to GCR section 9.3 Ballast. *Each segment shall be fastened with a minimum of two (2) one-half (1/2) inch bolts and positive lock nuts of SAE Grade 5/Metric 8.8 or better, and shall utilize large-diameter, load distributing washers.*
~~1. Each segment shall be fastened with a minimum of two (2) one-half (1/2) inch bolts and positive lock nuts of SAE Grade 5/Metric 8.8 or better, and shall utilize large-diameter, load distributing washers.~~

2. Touring 2 (T2) includes cars that cross over from American Sedan (AS) and TCR.
a. These cars are required to display "T2" according to GCR 9.3.29.
b. TCR cars in T2
1. TCR cars competing in T2 are required to conform to "2024 TCR Technical Regulations" as prepared by WSC World Sporting Consulting Limited .
2. TCR cars are allowed a maximum wheel size of 10" x 18".
3. TCR cars are permitted any DOT approved tire, 275 max."

T3
1. #39843 (Ian Poshka) 350Z
In T3 Spec Lines, Nissan 350Z Track/ Touring/Standard/ Nismo (03-08), change Restrictor as follows:
"HR Engine: (2) ~~49mm FPR~~*53mm FPR*"

T4
1. #39934 (Touring Committee) 16-24 ND MX5 T4
In T4 Spec Lines, Mazda MX-5 Miata/ Club (16-18), change Notes as follows:
"~~29mm~~*32mm*(f) 16mm (r) sway bars allowed."

In T4 Spec Lines, Mazda MX5 Miata/Club/ RF (19-24), change Notes as follows:
"~~29mm~~*32mm*(f) 16mm (r) sway bars allowed."

Fastrack® news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

ROAD RACING COMPETITION COMMITTEE MINUTES | April 7, 2026

We appreciate the feedback and perspectives that our members provide, and we'd like to thank you for your outreach and being part of the process. Should you have any requests or feedback to share with the Road Racing Competition Committee or a class advisory committee, please visit https://crbscca.com/ to submit a letter.

The Road Racing Competition Committee met by teleconference on April 7, 2026. Participating were Dayle Frame, Chairman; David Arken, David Locke, Jared Lendrum, Jim Goughary, Sam Henry, Tony Ave and Shelly Pritchett, secretary. Also participating were: Bob Crawford, BoD Chairman, David Brown, Mark Weber and Sam Fouse, BoD liaisons; Eric Prill, Vice President, Road Racing, Sydney Davis Yagel, Senior Manager of SCCA Road Racing, Scott Schmidt, Road Racing Technical Manager, Scott Dobler, Road Racing Series Manager. The following decisions were made:

Member Advisory
None.

No Action Required
General
1. #40043 (Hasan Ahmed) Rush SR Interest
Rush SR are allowed to run in SCCA under GCR Section 9.1.8.J.

2. #40046 (Darius Garcia) RUSH SR in SCCA
Please see response to letter # 40044 in current Fastrack.

3. #40047 (Tracen Gardner) Rush SR ATL
Please see response to letter # 40044 in current Fastrack.

4. #40048 (Aristotle B Allen) Rush SR Approvals
Please see response to letter # 40044 in current Fastrack.

5. #40049 (Ellis Spiezia) RUSH Class
Please see response to letter # 40044 in current Fastrack.

6. #40050 (john long) Rush SR FT3
Please see response to letter # 40044 in current Fastrack.

7. #40052 (Scott Donaghue) Rush SR Homologation Inquiry
Please see response to letter # 40044 in current Fastrack.

8. #40053 (Brian Tompkins) Rush SR Allowance
Please see response to letter # 40044 in current Fastrack.

9. #40054 (Ryan Kircher) Re-Consider Rule About Side Pod Fuel Tank to Go Racing in Rush SR
Please see response to letter # 40044 in current Fastrack.

10. #40055 (Darren Webster) Reconsideration Request for RUSH SR Side Pod Fuel Tank Approval
Please see response to letter # 40044 in current Fastrack.

11. #40056 (Jeff Hardesty) Rush SR Fuel Tank
Please see response to letter # 40044 in current Fastrack.

12. #40057 (Brent Kaufman) Rush SR Owner
Please see response to letter # 40044 in current Fastrack.

13. #40058 (Colin Clayton) Rush SR SCCA Approval
Please see response to letter # 40044 in current Fastrack.

14. #40060 (Scot Dietz) Reconsideration for Side Pod Gas Tank
Please see response to letter # 40044 in current Fastrack.

15. #40062 (Benjamin Qian) Reconsideration Request for RUSH SR Side Pod Fuel Tank Approval
Please see response to letter # 40044 in current Fastrack.

16. #40068 (Bradley Vincent) Reconsideration Request for RUSH SR Side Pod Fuel Tank Approval
Please see response to letter # 40044 in current Fastrack.

17. #40071 (John Grim) Rush SR Fuel Tank Rule Change
Please see response to letter # 40044 in current Fastrack.

18. #40073 (Jeff Schneider) Rush SR Fuel Cell Request
Please see response to letter # 40044 in current Fastrack.

19. #40074 (Tom Kersting) Rush SR Fuel Tank Approval
Please see response to letter # 40044 in current Fastrack.

20. #40075 (ALEX CHANG) Let us race with SCCA!
Please see response to letter # 40044 in current Fastrack.

21. #40076 (Sam Kim) Rush SR - Fuel tank
Please see response to letter # 40044 in current Fastrack.

22. #40077 (Jared Anderson) Rush SR Eligibility Request
Please see response to letter # 40044 in current Fastrack.

23. #40078 (Jared Anderson) Rush SR Eligibility Request
Please see response to letter # 40044 in current Fastrack.

24. #40079 (Evan Pecore) Request to Approve Rush SR Plastic Fuel Cell
Please see response to letter # 40044 in current Fastrack.

25. #40080 (Omar Kaayal) Reconsideration request for RUSH SR side pod fuel tank approval
Please see response to letter # 40044 in current Fastrack.

26. #40081 (Ivy Stowe) Please Allow Rush SR Cars to compete Unmodified
Please see response to letter # 40044 in current Fastrack.

27. #40082 (Jeffrey PHANG) Rush SR Fuel Cells
Please see response to letter # 40044 in current Fastrack.

28. #40083 (Josh Laughman) Tanks Response
Please see response to letter # 40044 in current Fastrack.

29. #40084 (John Beale) Rush SR Requesting the Original Blue Tank
Please see response to letter # 40044 in current Fastrack.

30. #40088 (Andor Tobelem) RUSH SR - FUEL CELL REQUEST
Please see response to letter # 40044 in current Fastrack.

31. #40090 (Luke Krepsky) Rush SR Spec
Please see response to letter # 40044 in current Fastrack.

32. #40091 (Ben Bulkley) Rush SR Series
Please see response to letter # 40044 in current Fastrack.

33. #40093 (Jason Bemis) Rush SR Fuel Tanks
Please see response to letter # 40044 in current Fastrack.

34. #40095 (Michael Ruggiero) RUSH SR in NERSCCA
Please see response to letter # 40043 in current Fastrack.

35. #40096 (Michael Ruggiero) RUSH SR With SCCA
Please see response to letter # 40043 in current Fastrack.

36. #40100 (John Howe) Rush SR in SCCA
Please see response to letter # 40043 in current Fastrack.

37. #40104 (David Schwarz) Rush SR Blue Rotoformed Tank
Please see response to letter # 40044 in current Fastrack.

38. #40112 (Keegan Bosch) Rush SR - Make the Blue Rotoformed Tank Eligible for Competition
Please see response to letter # 40044 in current Fastrack.

39. #40115 (Dan Fouts) Reconsideration Request for RUSH SR Side Pod Fuel Tank Approval
Please see response to letter # 40044 in current Fastrack.

40. #40145 (John Robinson) RUSH SR Fuel Cell Request
Please see response to letter # 40044 in current Fastrack.

GT2
1. #39961 (Dennis Troemel) Porsche Windshield Clips
The Cars "Spec Line" takes precedence over what may be written in the GCR.

IT General
1. #39982 (John McFarland) Convertible Variants
The specific models do not need to be called out specifically to include convertible models within the spec line. "Convertible model cars are permitted provided they meet 9.3.18 and 9.4 requirements."

EP
1. #39972 (Dean Ladd) Rule Clarification
The rule states "Cars equipped with power steering as standard equipment can modify, substitute, disable and/or remove the power pump, related hoses and mounting brackets."

Any changes made to the power steering system would have to be defended within this rule as written. If you have a more specific or detailed question, please submit another letter.

STL
1. #40065 (Rich Grunenwald) Feedback on 1.6L Miata Weight
Thank you for your comments. We're glad to hear that a 1.6L competitor feels the weight adjustment was successful in increasing parity.

<u>Not Recommended</u>
FV
1. #39269 (Brian Farnham) FV Transmission Rules
The Road Racing Competition Committee does not recommend this change. The advisory committee has carefully researched and reconsidered the author's request to allow competitors to polish transmission internal parts in FV, and the findings are similar to those regarding the author's prior letter #37100 submitted in October 2024. The RRCC therefore reiterates its previous determination: "Polishing that is not required to effectively clean a part and is not performed by the original manufacturer or called out in the service manual for a part constitutes a modification of the part, and the rules state that components of the powertrain (such as components within the transmission) may not be modified unless specifically authorized by the rules."

Whether some competitors have polished their transmissions and tech inspectors have elected not to inspect transmissions at the Runoffs in the past does not constitute a reason to now allow this modification. To do so would be unfair to competitors who have chosen not to polish their transmissions in accordance with the GCR's FV rules, as they would need to incur significant costs to make this modification. Regarding the author's questions, the RRCC has determined the following: 1) tech inspectors have the ability to recognize the difference between a worn part and a polished part; 2) tech inspectors may have the tools to disassemble a transmission on site, but disassembly is not required to determine whether its components have been polished; 3) if a transmission is disassembled, an appropriately cleaned part should look like a new gear, which to a trained eye does not look like a polished gear.

General
1. #40044 (Sheldon Rosenbaum) Rush SR Interest
While SCCA would welcome the increase in participation from the Rush community, the Rush Fuel Cell in question does not meet the SCCA requirements, and an exemption would be significantly beyond the scope of the rules in GCR section 9.3.26. Additionally, the Rush manufacturer has a rules compliant solution that meets SCCA requirements. We ask that Rush owners convert their cars to the compliant solution and join us at their local SCCA Road Race.

IT General
1. #40101 (Ricardo Velez) Request to Allow Ignition Timing Conversions
It is not allowed for the ignition timing to be converted to a non-distributor conversion as it goes against the IT philosophy of remaining basically stock.

EP
1. #40099 (Anthony Parker) Triumph GT6 Adjustments
Thank you for your request, but the PAC would like to see this car run some under its current configuration before additional changes will be considered.

SM
1. #39220 (Tom Sager) 1994 - 1997 Request #1 2025
Thank you for your letter and corresponding data files. SMAC does not believe this request would improve the balance of performance for the class.

After logging temperature data with the turn signal light in and out at 2 different tracks on a well prepared national front running car, we have found that the average intake temperature reduction is 10-15 degrees F. Utilizing industry standard corrections for hp, removing the turn signal assembly would net roughly 2 hp. Based on the 2025 Runoffs deep dive analysis AIM performed for us, the NA8 does not show it needs any additional horsepower but could benefit from a slight weight reduction. Acceleration rates were measured in six separate 5 mph increments from roughly 55-95 mph. In 4 out of the 6 increments that NA8 was the fastest accelerating car. See letter # 39387 for the weight reduction request.

T2
1. #39834 (Scotty B White) FP350S Mustang
Given some classing errors in the recent past, we can't suggest this change at this time.

T3
1. #40006 (Marshall Mast) 11-14 V6 Mustang
Based on data collected at the Runoffs, the car was very competitive. We did remove 25 lbs for the 2026 season. Please race so data can be collected.

<u>Recommended Items</u>
The following subjects will be referred to the Board of Directors for approval. Address all comments, both for and against, to the Road Racing Competition Committee. It is the BoD's policy to withhold voting on a rules change until there has been input from the membership on the presented rules. Member input is suggested and encouraged. Please send your comments via the form at www.clubracingboard.com.

F6

1. #39929 (Carl Wassersleben) F6 Exhaust Length Limits for F6 in Road Race and Solo
In F6, GCR section 9.1.1.D.14.B, change as follows:
"Any exhaust pipe(s) may be used (unless otherwise specified). *It is the intent of this rule that the exhaust pipe includes the exhaust manifold. The* ~~M~~*m*aximum exhaust length behind the rear axle centerline *without a sound control device or muffler* is twenty-four (24) inches. ~~It is the intent of this rule that the exhaust pipe includes the exhaust manifold.~~ *The addition of a sound control device or muffler is allowed. If a sound control device or muffler is used, the total length must not exceed thirty-six (36) inches behind the rear axle centerline when combined with the exhaust pipe.*"

GCR

1. #39854 (Jon Krolewicz) Allow IMSA/FIA Medical Forms
Effective 5/1/26, in Appendix C, GCR section 2.1.A, change as follows:
"Everyone who applies for an SCCA Competition License or Permit must submit a completed SCCA Physician's Examination and Medical History Form, a valid Federal Aviation Authority Class 1, Class 2, or Class 3 Medical Certificate or a completed FAA BasicMed Form (FAA 8700-2 Comprehensive Medical Examination Checklist), ~~or~~ a complete*d* NASA-approved Medical Evaluation form*, or a completed FIA member-club medical evaluation form that specifically notes a medical sign-off for motor racing (e.g., an IMSA medical form)*. For the purposes of SCCA competition licensing, the term "form" refers to any of these. The form must be submitted every 5 years for applicants ages 14-39; every 3 years for applicants ages 40-49; every 2 years for applicants ages 50-69; and every year for applicants' age 70 and over. The examination date cannot be more than 6 months before the Competition License or Permit application date. A new ~~F~~*f*orm is not required for a 14 year-old Novice Permit holder or *for a* Novice Permit holder applying for a Full Competition or Vintage License, provided the current ~~F~~*f*orm is within the specified term for the ~~M~~*m*inor's age group."

2. #40157 (TODD BUTLER) E&O - GCR Clean Up
In Actions Against Cars, GCR section 8.3.3.A.3, change as follows effective 5/1/2026:
"The bond must be paid before the inspection can begin~~, and must be cash, check, or credit card (Visa, Mastercard, or Discover only)~~. *The bond may be paid by cash, check, or credit card. If a credit card is used, the fee must be paid online through the SCCA Member Account Portal (proof of payment is required).*"

In Appendix F, add the following effective 5/1/2026:
"*Teardown – Partial or complete disassembly of the protested item(s) or component(s).*"

In Actions Against Cars, GCR section 8.3.3, change as follows effective 5/1/2026:
"The protestor may request that the car be disassembled, inspected, or any other test made, provided they post a ~~tear down~~*teardown* bond (also referred to as "bond") with the SOM sufficient to cover the total expenses of disassembly, inspection, reassembly, and other costs associated with the protest."

In Actions Against Cars, GCR section 8.3.3.E, change as follows effective 5/1/2026:
"The ~~tear down~~*teardown* bond shall be sent to the Road Racing Department to hold it in escrow until the time limit to Appeal expires, an Appeal has been rejected, or an Appeal has been decided by the Court of Appeals."
In Judgment of the Court of Appeals, GCR section 8.4.5.E, change as follows effective 5/1/2026:
"The Court may or may not return appeal fees; and it will determine the disposition of protest fees and ~~tear down~~*teardown* bonds, if any, in cases where the decision being appealed is nullified or otherwise changed."
In Sealed Engines and Transmissions, GCR section 9.3.42, change as follows:

"Race cars with sealed engines and/or transmissions are not subject to ~~tear down~~*teardown* either through post-race inspection or mechanical protest if:

1. The car engine and/or transmission units have each been homologated as a unit (engine and transmission are separate units) by an SCCA-recognized organization, manufacturer, or sanctioning body.
2. The competitor has provided dated documentation from the homologating organization, manufacturer, or sanctioning body to identify the seals and their unaltered condition.
3. The seals are in their original location and unaltered condition.

Competitors who cannot meet all three of these criteria are subject to ~~tear down~~*teardown* in post-race impound and mechanical protest. Competitors who refuse to comply with a ~~tear down~~*teardown* are subject to penalties, including disqualification."

In Penalty Points, GCR section 7.4.D table, change as follows effective 5/1/2026:
In Condition column, remove "Invalid Statement of Facts Affidavit" cell

In Automatic Penalty column, remove "Event disqualification, 60 day suspension of competition privileges, and 6 penalty points" cell

SM

1. #39387 (Tom Sager) Request for Weight Reduction 2026
In SM Spec Lines, Mazda MX-5 / Miata (94-97), change Weight (lbs) as follows effective 5/1/2026:
"~~2400~~*2385* or ~~2415~~*2400* with alternate bore"

SMX5

1. #40001 (Spec Mazda (SM/SMX) Committee) Cleanup Data Language
Effective 5/1/26, in GCR, Section 9.1.7.1.D.20., change as follows:
"20. Data Acquisition

1 A technical evaluation process for cars is available. Part of this process *for any car that attempts to start an official timed session* is the required download *and submission* of AiM Data files after each *official* timed session (*All* Qualifying 1 & 2, *and* Races 1 & 2). Within 60 minutes of each timed session end, all Series Competitors MUST send the AiM Data file (.XRK *or .XRZ*) for all timed laps of that session to the secure email address (data@specmx-5.com), where data will be reviewed by *an* AiM *representative* directly. Failure to adhere to this guideline, or having a non-functioning *AIM* data *system*, may be grounds for penalty or disqualification.

Competitor data submissions are not protestable by competitors or entrants. Actions related to data submission and compliance will be determined by race officials only.

a. Vehicle must be equipped with current generation AiM data acquisition system (configurable in Race Studio 3) that can provide on track data to AiM *R*~~r~~ace *S*~~s~~tudio 3. *The data acquisition system is required to record the OBDII/ECU data stream. The data acquisition system may read the Flagtronics system, but it is not permitted to alter/manipulate data from the OBDII/ECU or Flagtronics system in any way.* The AiM system may be utilized to trigger a switch I.E., cooling fans or diff cooler pumps but must be wired via a separate analog circuit.

Refer to Section 17: Electrical Equipment above for installation requirements.

b. The connection at the OBDII port for the AiM system may be made in either one of two ways:

1. Through a dedicated OBDII AiM adaptor.

2. By direct wiring to the back of the OBDII port within 3” of the ODBII connector.

c. Fuel pressure datalogging is required.

d. Oil pressure datalogging is required.

e. All cars must run the ~~latest AIM Data Logger Spec MX-5 ECU Protocol.~~ *most current Mazda-Spec_MX5_NCecu protocol. It must used in the AIM data systems configuration with no edits or changes and all 21 channels enabled.*"

Taken Care Of

B-Spec

1. #39732 (Richard Hromin) Mini Cooper 11-13 and COUPE
Please see response to letter #40070 in current Fastrack, Mini Cooper B-Spec BOP Updates.

2. #39927 (Steve Introne) Recent Recommendations Related to Mini Cooper
Please see response to letter #40070 in current Fastrack, Mini Cooper B-Spec BOP Updates.

3. #39931 (Zach Introne) Recent Recommendations Related to Mini Cooper
Please see response to letter #40070 in current Fastrack, Mini Cooper B-Spec BOP Updates.

4. #39984 (Joha Divison) Review of Toyota Yaris
The committee already has approved two positive BOP changes to this car this year, which were a 50 lb. reduction of its minimum weight and the removal of the primary catalyst. The FPR has been left in place for the time being. It was originally implemented an effort to balance the aero advantage of the sedan over the hatchback body. The diameter of the FPR was carefully selected to have a small overall effect on this vehicle's performance. The bore diameter of the Yaris's throttle body is 45mm. Which means the 41/42mm plates that these cars are required to use are not overly restrictive. The committee will continue to monitor the performance of this vehicle in relation to the rest of the category.

5. #39986 (Javier Rodriguez) Request to Review Balance of performance
Please see the response to letter #39984 in current Fastrack, Review of Toyota Yaris.

C-Spec

1. #39979 (Michael Ogren) Please Raise Weights to Match Actual Build Weight
The committee just recommended updating the minimum weights in the most recent Fastrack for C-Spec for exactly the reasons you outlined.

2. #39989 (Mike Ogren) Support for letter 39987
Please see response to letter #40009 in current Fastrack, Add C-Spec to Majors Eligibility.

3. #40009 (Dean Fehribach) Add C-Spec to Majors Eligibility
The committee is strongly in favor of C-Spec being eligible for Majors/Super Tour participation. We have communicated to the Road Racing Competition Committee that we believe current B-Spec competitors at these events would be happy to share a run group with C-Spec as has been the standard at regionals. We are in the process of making a formal proposal for C-Spec to join B-Spec as a Majors/Super Tour eligible category with the ultimate goal of C-Spec earning an invitation to the National Championship Runoffs as soon as possible.

GT2
1. #38568 (KunWoo Park) Question about Ford Ecoboost Engine
Please see response to letter #38584 in current Fastrack.

2. #39156 (Brian Goldburg) Panoz Esperante GTS - Combine with letters #38494 & #38584
Please see response to letter #38584 in current Fastrack.

3. #39487 (Joe Stadelmann) Panoz GTS Parts Specifications
Please see response to letter #38584 in current Fastrack.

HP
1. #40111 (Michael Kelley) Support of 40110
Please see response to Letter #40110 in the current Fastrack.

2. #40113 (Robert Wismer) I Support Letter 40110
Please see response to Letter #40110 in the current Fastrack.

SM
1. #39351 (Brian Mowcomber) 2026 GCR NA8 Weight Reduction Request
Please see response to letter 39387 in current Fastrack.

T2-T4
1. #39969 (Aaron Kaplan) Ensuring Car Compliance
The committee recognizes the importance of ECU tune compliance. We are compiling information and working on programs and processes to confirm that racers are utilizing approved tunes. Considering the various vehicles and tuning methods in the classes, this is no small task. Your suggestions are appreciated and we will consider them as we move forward.

<u>What Do You Think</u>
None.

<u>Resume</u>
None.

Fastrack news
official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

DATE: April 20, 2026
NUMBER: TB 26-05
FROM: Road Racing Competition Committee
TO: Competitors, Stewards, and Scrutineers
SUBJECT: Errors and Omissions, Competition Adjustments, Clarifications, and Classifications

All changes are effective 5/1/2026 unless otherwise noted. If any day of a race event falls on the first day of the month, the previous month's rules will be in effect for that event only. The new rules will become effective at the conclusion of the race event, unless otherwise noted.

American Sedan
None.

B-Spec/C-Spec
1. #40070 (B-Spec/C-Spec Committee) Race Memo RM 26-01 B-Spec Mini Cooper Weight Adjustments with OEM
The BSAC reviewed historical data, results, and past BOP of this platform in arriving at this decision. It is our desire to see MINIs with the OEM manifold/approved Walker brand manifold competing at events. The BSAC will monitor the performance results of these changes closely at HST events and the Runoffs over the coming months. Should data show that these cars are outside of the desired performance window (I.E. too fast OR too slow) at their updated minimum weight, further BOP adjustments will be made to ensure continued competitive parity. Data from a minimum of three drivers/vehicles from Majors or Super Tour weekends will be evaluated before any further BOP adjustments are made. No further adjustments will be made to the header configuration before its expiration on 1/1/27.

In GCR Section 9.1.10 Make changes as followsper RM 26-01:
Mini Cooper (R56) MT (07-10): "*2600 (OEM Catalyst)* 2675 *(Header)*"

Mini Cooper (R56) AT (07-10): "~~2675~~*2600*"

Mini Cooper Clubman (R55) (07-10): "*2600 (OEM Catalyst)* 2675 *(Header)*"

Mini Cooper (R56LCI) MT (11-13): "~~2675~~*2600*"

Mini Cooper (R56LCI) AT (11-13): "~~2675~~*2600*"

Mini Cooper Clubman (R55) (11-15): "~~2675~~*2600*"

Mini Cooper Coupe (R58) (12-15): "~~2675~~*2600*"

Electric Vehicle
None.

Formula/Sports Racing
None.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

GCR

1. #39921 (SCCA Staff) 2026 GCR 9.3.29 Revisions

In Numbers and Class Identifications, GCR section 9.3.29.A, change as follows:

"Numbers shall be placed on the front and both sides of the car~~ so that they are legible~~. All closed-wheel cars must have the front number located on the hood. All ~~F~~*f*ormula cars with a rear wing must have legible numbers on each rear wing end plate. Numbers may be one, two, or three digits. Three-digit numbers must begin with the number "1." ~~and must meet the approval of the Chief of Timing and Scoring.~~ Class identifications must be placed on both sides of the car~~ so that they are legible~~. ~~Rear n~~*N*umbers and class identifications *on the rear of the car* are recommended. Cars running in multiple classes must clearly identify which class and weight they are running. The ~~numeral~~*number* "1" will be exclusively reserved for the current national champion in each class for Conference Majors/Super Tour events. The ~~numeral~~*number* "1" will be reserved until the end of the period for submitting advanced or pre-event entries~~,~~ and then will be released. If two or more national champions are entered in the same run group, the first to enter will have preference. Duplicate car numbers within the same run group are prohibited. See also GCR section 6.4.1.A."

In Size of Numbers and Class Identifications, GCR section 9.3.29.B, change as follows:

"*The minimum height of all* ~~N~~*n*umbers ~~must be at least~~*is* 8 inches~~ high,~~ with a *minimum* 1.5-inch stroke *width* on a ~~solid~~*single-color* contrasting background~~ (rear-winged Formula cars must have as large a number as possible on their rear wing end plates)~~. *All numbers must be the same color and style.* Metallic (reflective) ~~numbers and class letters~~*identification characters and backgrounds* are prohibited. ~~The distance between two numbers must be at least as wide as the stroke of the numbers. Front and side numbers must be surrounded by 6 inches of contrasting background free of all other graphics. If multiple digits are used, each number digit must be the same color. Cars with illegible numbers may not be scored. The Chief of Timing and Scoring and the Race Director/Chief Steward will determine legibility of markings.~~ *The minimum height of all* ~~C~~*c*lass identifications ~~must be at least~~*is* 4 inches~~ high,~~ with a *minimum* 1/2-inch stroke *width* on a ~~solid~~*single-color* contrasting background."

2. #39990 (Bev Heilicher) Errors & Omissions

In Chair of the SOM, GCR section 5.12.1.B.2, change as follows:

"The name(s) of anyone placed on probation, or whose competition privileges were suspended, must be faxed or emailed to the Road Racing Department on Monday following the event. Required information includes the name, member number, event date/location, and ~~the~~ name of the Chair of the SOM. The confiscated license(s) and tear-off coupon(s) from the Probation ~~Letter(s)~~*Log* must be sent with the Observer's Report."

In Appeal Procedures, GCR section 8.4.3.B.2, change as follows:

"a competition license surrendered to the Chair of the SOM or the Race Director or Chief Steward in return for a Probation ~~Letter~~*Log* must be received by the National Office; and"

In Appendix A, Penalty Definitions, section 26 b), change as follows:

"***Probation*** – A penalty against a specific privilege(s) (e.g.. competition license, specialty license) authorized by SCCA which requires observation for a specified amount of time and/or completion of a specific set of conditions. When a probation penalty is applied, a Membership – Probationary ~~License form~~*Log* will be issued and used during the probationary period."

In Appendix C, Non-Standard License Situations, section 3, change as follows:

"A. Probation ~~Letter~~*Log* as License

1. The Chair of the SOM or other review committee or Court of Appeals issues a Probation ~~Letter~~*Log* to temporarily replace the confiscated License of a member whose penalty is probation.

2. The member uses the Probation ~~Letter~~*Log* as a License until the terms of the probation have been met completely.
3. When the terms are completed, the member sends the Probation ~~Letter~~*Log* to the National Office and receives their License in return."

In Range of Penalties, GCR section 7.2.K, change as follows:
"Suspension of license privileges
SCCA license privileges for a driver, crew, or official may be suspended for a period of time not to exceed 12 months. ~~A license holder whose privileges are suspended must immediately surrender their license to the Chair of the SOM, review committee, or Court of Appeals.~~ The suspension is effective immediately. If a fine is imposed concurrently with the suspension, the suspension period will not be completed until the fine is received by the Chair of the SOM, review committee, or ~~the~~ National Office. *A competitor's Probationary Log must be given to the Chief Steward/Race Director before going on track.*"

General
None.

Grand Touring
GT2
1. #38584 (Brian Goldburg) Panoz Esperante GTS Letter ID Number: #38494 - Additional Info
In GT2 Spec Lines, GT Cars - PANOZ, Esperante GTS, change Notes as follows:
"~~Cars must be prepared to Panoz Esperante GTS specifications and competitors must have a copy of the current GTS rules in their possession. Wheels: (F) 18x10 (R) 18x11. Track (F) 64.0 (R) 67.8. Any tire with a diameter of 17" or 18" may be used provided the tire does not exceed a maximum cross section width of 11.5" in the front and 12.5" in the rear; or may use conventional GT2 tires and wheels per GTCS 9.1.2.F.4.c.10. Internal modification to stock Penske 7500 shocks are permitted. Shock seals are not required. Brakes are unrestricted. Front and rear anti-roll bars are unrestricted. Shock and springs are free, transmission type and ratios are free, differential gear ratio only is free (all GT2 transmission rules apply), roof vents allowed per GTCS.~~
Front Track 64.0"
Rear Track 67.8"
Panoz cars are allowed to prep to, and must meet GT2 rule set unless otherwise noted on spec line."

2. #39923 (Butch Kummer) Appendix L Update
In GCR, Section APPENDIX L. 2013 TA2 TECHNICAL REGULATIONS, 4.8.2.1., change as follows:
"Shock Absorbers: ~~$850~~*$1005* each
Front Brake Calipers: $715 each
Rear Brake Calipers: ~~$550~~*$585* each
Brake Pads: ~~$250/axle~~*$330 per axle*
Wheels: ~~$175~~*$165* each"

3. #40125 (Grand Touring Committee) GT2 Porsche 997.2 GT3 Cup EDIT
In GT2 Spec Lines, GT2 Cars - PORSCHE, 991.1 GT3 Cup, change Notes as follows:
"Modifications listed in Grand Am, IMSA Cup and World Challenge ~~or any other rules, except those listed above, are specifically not allowed~~ are permitted. Factory (OEM manufacturer) Lexan front windows allowed as delivered. ABS is allowed."

Improved Touring
None.

Legends Car
None.

Planning
None.

Production
1. #39976 (Production Committee) Miata track width - errors and omissions
In EP Spec Lines, Mazda MX-5 / Miata (94-97), change Track (F/R) mm/(in.) as follows:
Track (F/R) mm/(in.): "~~1483/1509 (58.4/59.4)~~*1516/1534(59.7/60.4)*"

2. #40098 (Anthony Parker) Triumph GT6 Spec Change.
In EP Spec Lines, Triumph GT6, change the "Drivetrain Notes" as follows:
"(2) auto-type w/~~44~~45mm choke(s)"

FP
1. #39977 (Production Committee) GCR Spec Line Correction
In FP Spec Lines, correct the carburation under the "Drivetrain Notes" section of the following spec lines as an E&O:
Volkswagen Jetta (includes GLI) (82-84):
"*(1)* 40 DCN, DCNF, IDF w/38mm choke(s)
(2) auto-type side-draft w/34mm choke(s) on I.R. manifold~~,~~"

Volkswagen Jetta (GLI, GL) (85-92):
"*(1)* 40 DCN, DCNF or IDF w/36mm choke(s)
(2) auto-type side-draft w/32mm choke(s) on I.R. manifold"

Volkswagen Rabbit (Includes Cabriolet):
"*(1)* 40 DCN, DCNF, IDF w/38mm choke(s)
(2) auto-type side-draft w/34mm choke(s) on I.R. manifold"

Volkswagen Scirocco:
"*(1)* 40 DCN, DCNF, IDF w/38mm choke(s)
(2) auto-type side-draft w/34mm choke(s) on I.R. manifold"

Volkswagen Scirocco (83 to 88):
"*(1)* 40 DCN, DCNF, IDF w/38mm choke(s)
(2) auto-type side-draft w/34mm choke(s) on I.R. manifold"

2. #39978 (Production Committee) CGR Spec Line Weight Correction
In FP Spec Lines, make the following correction to the "Base Weight (lbs)" section as an E&O:
Volkswagen Rabbit (Includes Cabriolet)
"178~~9~~*0*cc:
1803"

Volkswagen Scirocco (83 to 88)
"178~~9~~*0*cc:
1803"

1. #40110 (Doug DeRonne) Request to Classify BMW E21 320i
In HP Spec Lines, classify BMW 320i/is (E21) (80-83) as follows:

HP	Prep. Level	Base Weight (lbs)	Engine Type Mat'l Block/ Head	Displace-ment Bore x-Stroke mm/ (in.)	Drivetrain Notes	Chassis Notes	Wheel-base mm/ (in.)	Track (F/R) mm/(in.)
BMW 320i/is (E21) (80-83)	*2*	*2200*	*4 Cyl SOHC Iron/ Alum*	*1767 89.0x71.0 (3.50x2.80)*	*Fuel Injection Valve Size: (I) 44.0/(1.73) (E) 38.0/(1.50) Comp. ratio 11.0:1, Valve lift .425" Trans. Speeds: 5*	*Wheels: 15x7 Brakes Std: (F) 254/(10.0)Disc (R) 250/(9.8) Drum Trunk mounted fuel cell allowed.*	*2563 (100.9)*	*1481/1494 (58.3/58.8)*

2. #40116 (Production Committee) BMW 318is 84-85 engine displacement correction
In HP Spec Lines, BMW 318i/is E30 (84-85), change Displacement Bore x Stroke mm/ (in.) as follows:
"~~1797~~*1767* 89.0 x 71.0 (3.50x2.80)"

Spec Mazda (SM/SMX)
None.

Super Production
None.

Super Touring
STU
1. #40008 (Peter St Pierre) Turbo Restrictor Size Increase Request
In STU Spec Lines, Table A: Alternate Vehicle and Engine Requirements, Honda K20C1 Turbo I4, change Notes as follows:
"~~35~~*36*mm TIR required."

2. #40028 (Peter Federlin) GT86 Cups Car in STU
In STU Spec Lines, Table B: Alternate Vehicle and Engine Allowances, change Notes as follows:
"Must meet all 2022 Toyota GR Cup rules, *including tires or DOT tires conforming to section 9.1.4.O with a maximum section width of 245*."

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

Touring
T1
1. #39924 (Danny Kellermeyer) Clarification on Request #39716 T1 (Spec Line #1139)
In T1 Spec Lines # 1139, change as follows:
Max Displ: "LS1, LS6 ~~OEM~~
Restrictor Required: "~~70mm~~"
2. #39958 (Joe Aquilante) Mistake in Line 1430
In T1 Spec Line, Spec Lines # 1430, change Maximum Displ as follows:
"Coyote, Boss 302 (11-~~17~~*14*) 4957"

T3
1. #39935 (Philip Di Pippo) 2019 Mustang 2.3L Ecoboost Request
In T3 Spec Lines, Ford Mustang EcoBoost (2015-), change as follows:
Year: "(2015-*2023*)"
Maximum Weight: "~~3525~~*3475*"

2. #39983 (Brian Leib) 2013 Audi S4
In T3 Spec Lines, Audi S4 (12-14), change as follows:
Required Restrictor: "~~55mm FPR~~*60mm FPR*"
Tire Size: "~~255~~*275*"

3. #40007 (Scott Bolster) Request Update to T3 Camaro V6 (10-15) Spec Line
In T3 Spec Lines, Chevrolet Camaro V6 (10-15), change Wheel Size as follows:
"~~20 x 9~~*20 x 10*"

4. #40010 (Scotty B White) S550 Mustang 3.7
In T3 Spec Lines, Ford Mustang V6 (15-17), add to Notes the following:
"*Performance Pack 2 Splitter and Spoiler permitted.*"

T4
1. #39999 (Milos Milivojevic) 2003 Honda Civic Si Classification
In T4 Spec Lines, classify Honda Civic SI (02-03) *as follows:*

T4	Bore x Stroke(mm)/ Disp. (cc)	Required Restrictor	Wheel Size(in.)	Tire Size (max)	Gear Ratios	Final Drive	Brakes (mm)	Weight (lbs)	Notes:
Honda Civic SI (02-03)	*86.0 x 86.0 1998*		*17 x 8*	*225*	*3.06, 1.77, 1.21, 0.92, 0.74*	*4.50*	*(F) 262 (R) 260*	*2400*	*Any spring up to a maximum spring rate of 800 pounds front and 800 pound rear may be used Cold Air Intake system allowed. 26mm front and rear*

									*sway bar allowed. Header allowed. Front strut tower brace allowed. ***Must participate in 3 Super Tour events before this car is eligible for the Runoffs****

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Lincoln Larson vs. SOM COA Ref. No. 26-04-SE
April 08, 2026

FACTS IN BRIEF

On March 8, 2026, following Race 2 for Group 6 at the Hoosier Racing Tire SCCA Super Tour at Michelin Raceway Road Atlanta, Jason Fichter, driver of Spec MX-5 (SMX) #7, filed a Protest against Lincoln Larson, driver of SMX #16, alleging the use of a "non OE oil filter" in violation of General Competition Rules (GCR) 9.1.7.1.D.6.13.a.

The Stewards of the Meeting (SOM), George DeLong, Paul Gauzens, and Thomas Kirchman (Chair) met, heard witnesses, and reviewed the evidence. The SOM determined the oil filter in SMX #16 when examined and photographed in post-race impound was not an OE replacement filter. The SOM penalized Mr. Larson with loss of position, moving him behind all compliant cars and assessed 0 points on his competition license.

Mr. Larson appealed the decision of the SOM.

DATES OF THE COURT

The SCCA Court of Appeals (COA) Scott Bowman, Jack Kish, and Laurie Sheppard (Chair) met on April 2, 2026, to review, hear, and render a decision on the appeal.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Request to Appeal from Lincoln Larson, submitted March 16, 2026.
2. Official Observers Report and related documents, received March 25, 2026.
3. Additional witness statement from Bob Stretch, received March 25, 2026.
4. Additional witness statement from Logan Stretch, received March 25, 2026.
5. Chair SOM's Response to Appeal, received March 27, 2026.
6. Race Director's Response to Appeal, received March 31, 2026.

FINDINGS

In his appeal, Mr. Larson asserted Mr. Fichter did not submit the protest within the required 30-minute time frame following the end of the Group 6 race as required by GCR 8.3.1.F. (Cars in impound may be protested within 30 minutes after any session.) He further stated the oil filter part number is not stated in the rule set although some other part numbers are. Mr. Larson also said there was no notation made in SMX #16's logbook although GCR 8.3.3. states, "Non-compliant item(s) will be noted in the car's

Vehicle Logbook." He argued the protested drivers were told they could leave the impound area, but before they could do so, they were told they must remain – in his words, they were "reimpounded" without authority.

The SOM combined the protests against Cars #16, #48, #57 and #83 as all protests were identical and considered all as one. After consulting Race Director Kathy Barnes, the SOM accepted the protest as timely due to circumstances beyond the control of the protestor. The SOM interviewed Mr. Larson, driver of #16, Gavin Vaughan, driver of #48, and Johannes Saito, entrant for #57 and #83. The SOM reviewed pertinent GCR technical specifications, the Technical Inspection Report for each car prepared by Class Compliance Chief Scott Schmidt, and examined photographs of each car's oil filter in place during post-race impound. The SOM concluded the oil filter on each of the four cars was not an OE engine oil filter.

The COA notes GCR 8.3.1.F. states in its preamble to the time limit table, "…the SOM may extend the time in cases where the protestor can show … they were unable to meet the deadline because of circumstances beyond their control." Testimony from Race Director Kathy Barnes described Mr. Fichter's attempt to file the protest before she was available to receive it due to her responsibility to review other on-track issues during the race. The documented receipt time of the protest by the Race Director is 3:00pm. SOM Chair Tom Kirchman documented the SOM's consideration of circumstances beyond the protestor's control which caused the SOM to accept the protest with a justified 11-minute delay.

The COA reviewed all documents and photos considered by the SOM and researched the public availability of required parts information both in the GCR and on the internet. GCR 9.1.7.1.D.6.13.a. says, "OE engine oil filter is required; no substitutions permitted." GCR Appendix F. Technical Glossary contains the following definition: "OE – The described part is that which came on the vehicle or that which would be purchased from the original vehicle manufacturer or an authorized dealer for replacement." An internet search for "OE engine oil filter for 2012 Mazda MX-5" (an eligible car for the SMX class) returned multiple sources for Mazda part number LF05-14-302B to be used for MX-5 model years 2006-2015. GCR 9.1.7.1.C. says in part, "If the Mazda Factory Manual or these rules provide only a partial specification or no specification at all, the Mazda parts may not be modified beyond what is permitted in these rules."

GCR 5.12.3.C.4. authorizes a Race Director or Chief Steward to "Direct cars to be impounded at any time during the event." The COA finds the four protested cars were impounded under the authority of the Race Director and examined for violations alleged in Mr. Fichter's protest. The SOM carefully determined the protest was submitted per the GCR and their ruling was thoughtfully considered and consistent with the General Competition Rules and the penalty guidelines. Although the non-compliance was not

documented in the vehicle's logbook, that oversight alone is not sufficient grounds to overrule the SOM decision.

The COA finds the SOM acted within their authority and made a thoughtful and reasoned decision based on the evidence. The penalty assessed was within their purview. However, they did not apply the appropriate penalty points under GCR 7.4.A. which states, "Penalties assessed by the SOM …accumulate points on the member's record according to the following schedule". A penalty of Loss of Finishing Position accrues 2 penalty points on the member's competition license.

DECISION
The Court of Appeals upholds the decision of the SOM with the addition of 2 penalty points on Mr. Larson's competition license. Mr. Larson's appeal is well founded, and his appeal fee, less the amount retained by SCCA, will be returned.

Fastrack news
official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Gavin Vaughan vs. SOM COA Ref. No. 26-05-SE
April 08, 2026

FACTS IN BRIEF

On March 8, 2026, following Race 2 for Group 6 at the Hoosier Racing Tire SCCA Super Tour at Michelin Raceway Road Atlanta, Jason Fichter, driver of Spec MX-5 (SMX) #7, filed a Protest against Gavin Vaughan, driver of SMX #48, alleging the use of a "non OE oil filter" in violation of General Competition Rules (GCR) 9.1.7.1.D.6.13.a.

The Stewards of the Meeting (SOM), George DeLong, Paul Gauzens, and Thomas Kirchman (Chair) met, heard witnesses, and reviewed the evidence. The SOM determined the oil filter in SMX #48 when examined and photographed in post-race impound was not an OE replacement filter. The SOM penalized Mr. Vaughan with loss of position, moving him behind all compliant cars and assessed 0 points on his competition license.

Mr. Vaughan appealed the decision of the SOM.

DATES OF THE COURT

The SCCA Court of Appeals (COA) Scott Bowman, Jack Kish, and Laurie Sheppard (Chair) met on April 2, 2026, to review, hear, and render a decision on the appeal.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Request to Appeal from Gavin Vaughan, submitted March 16, 2026.
2. Official Observers Report and related documents, received March 25, 2026.
3. Additional witness statement from Bob Stretch, received March 25, 2026.
4. Additional witness statement from Logan Stretch, received March 25, 2026.
5. Chair SOM's Response to Appeal, received March 27, 2026.
6. Race Director's Response to Appeal, received March 31, 2026.

FINDINGS

In his appeal, Mr. Vaughan asserted Mr. Fichter did not submit the protest within the required 30-minute time frame following the end of the Group 6 race as required by GCR 8.3.1.F. (Cars in impound may be protested within 30 minutes after any session.) He further stated the oil filter part number is not stated in the rule set although some other part numbers are. Mr. Vaughan also said there was no notation made in SMX #48's logbook although GCR 8.3.3. states, "Non-compliant item(s) will be noted in the

car's Vehicle Logbook." He argued the protested drivers were told they could leave the impound area, but before they could do so, they were told they must remain – in his words, they were "reimpounded" without authority.

The SOM combined the protests against Cars #16, #48, #57 and #83 as all protests were identical and considered all as one. After consulting Race Director Kathy Barnes, the SOM accepted the protest as timely due to circumstances beyond the control of the protestor. The SOM interviewed Lincoln Larson, driver of #16, Mr. Vaughan, driver of #48, and Johannes Saito, entrant for #57 and #83. The SOM reviewed pertinent GCR technical specifications, the Technical Inspection Report for each car prepared by Class Compliance Chief Scott Schmidt, and examined photographs of each car's oil filter in place during post-race impound. The SOM concluded the oil filter on each of the four cars was not an OE engine oil filter.

The COA notes GCR 8.3.1.F. states in its preamble to the time limit table, "…the SOM may extend the time in cases where the protestor can show … they were unable to meet the deadline because of circumstances beyond their control." Testimony from Race Director Kathy Barnes described Mr. Fichter's attempt to file the protest before she was available to receive it due to her responsibility to review other on-track issues during the race. The documented receipt time of the protest by the Race Director is 3:00pm. SOM Chair Tom Kirchman documented the SOM's consideration of circumstances beyond the protestor's control which caused the SOM to accept the protest with a justified 11-minute delay.

The COA reviewed all documents and photos considered by the SOM and researched the public availability of required parts information both in the GCR and on the internet. GCR 9.1.7.1.D.6.13.a. says, "OE engine oil filter is required; no substitutions permitted." GCR Appendix F. Technical Glossary contains the following definition: "OE – The described part is that which came on the vehicle or that which would be purchased from the original vehicle manufacturer or an authorized dealer for replacement." An internet search for "OE engine oil filter for 2012 Mazda MX-5" (an eligible car for the SMX class) returned multiple sources for Mazda part number LF05-14-302B to be used for MX-5 model years 2006-2015. GCR 9.1.7.1.C. says in part, "If the Mazda Factory Manual or these rules provide only a partial specification or no specification at all, the Mazda parts may not be modified beyond what is permitted in these rules."

GCR 5.12.3.C.4. authorizes a Race Director or Chief Steward to "Direct cars to be impounded at any time during the event." The COA finds the four protested cars were impounded under the authority of the Race Director and examined for violations alleged in Mr. Fichter's protest. The SOM carefully determined the protest was submitted per the GCR and their ruling was thoughtfully considered and consistent with the General Competition Rules and the penalty guidelines. Although the non-compliance was not

documented in the vehicle's logbook, that oversight alone is not sufficient grounds to overrule the SOM decision.

The COA finds the SOM acted within their authority and made a thoughtful and reasoned decision based on the evidence. The penalty assessed was within their purview. However, they did not apply the appropriate penalty points under GCR 7.4.A. which states, "Penalties assessed by the SOM …accumulate points on the member's record according to the following schedule". A penalty of Loss of Finishing Position accrues 2 penalty points on the member's competition license.

DECISION
The Court of Appeals upholds the decision of the SOM with the addition of 2 penalty points on Mr. Vaughan's competition license. Mr. Vaughan's appeal is well founded, and his appeal fee, less the amount retained by SCCA, will be returned.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Johannes Saito vs. SOM COA Ref. No. 26-06-SE
April 08, 2026

FACTS IN BRIEF

On March 8, 2026, following Race 2 for Group 6 at the Hoosier Racing Tire SCCA Super Tour at Michelin Raceway Road Atlanta, Jason Fichter, driver of Spec MX-5 (SMX) #7, filed a Protest against Tyler Gonzalez, driver of SMX #57, alleging the use of a “non OE oil filter” in violation of General Competition Rules (GCR) 9.1.7.1.D.13.a.

The Stewards of the Meeting (SOM), George DeLong, Paul Gauzens, and Thomas Kirchman (Chair) met, heard witnesses, and reviewed the evidence. The SOM determined the oil filter in SMX #57 when examined and photographed in post-race impound was not an OE replacement filter. The SOM penalized Mr. Gonzalez with loss of position, moving him behind all compliant cars and assessed 0 points on his competition license.

Johannes Saito, entrant for SMX #57, appealed the decision of the SOM.

DATES OF THE COURT

The SCCA Court of Appeals (COA) Scott Bowman, Jack Kish, and Laurie Sheppard (Chair) met on April 2, 2026, to review, hear, and render a decision on the appeal.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Request to Appeal from Johannes Saito, submitted March 18, 2026.
2. Official Observers Report and related documents, received March 25, 2026.
3. Chair SOM’s Response to Appeal, received March 27, 2026.
4. Race Director’s Response to Appeal, received March 31, 2026.

FINDINGS

In his appeal, Mr. Saito asserted Mr. Fichter did not present the protest within the required 30-minute time frame following the end of the Group 6 race as required by GCR 8.3.1.F. (Cars in impound may be protested within 30 minutes after any session.) He further stated “the rules are the rules and should be applied equally to all competitors” while arguing the protest should be voided as it was filed after the deadline cited above.

The SOM combined the protests against Cars #16, #48, #57 and #83 as all protests were identical and considered all as one. After consulting Race Director Kathy Barnes,

the SOM accepted the protest as timely due to circumstances beyond the control of the protestor. The SOM interviewed Lincoln Larson, driver of #16, Gavin Vaughn, driver of #48, and Mr. Saito, entrant for #57 and #83. The SOM reviewed pertinent GCR technical specifications, the Technical Inspection Report for each car prepared by Class Compliance Chief Scott Schmidt, and examined photographs of each car's oil filter in place during post-race impound. The SOM concluded the oil filter on each of the four cars was not an OE engine oil filter.

The COA notes GCR 8.3.1.F. states in its preamble to the time limit table, "…the SOM may extend the time in cases where the protestor can show … they were unable to meet the deadline because of circumstances beyond their control." Testimony from Race Director Kathy Barnes described Mr. Fichter's attempt to file the protest before she was available to receive it due to her responsibility to review other on-track issues during the race. The documented receipt time of the protest by the Race Director is 3:00pm. SOM Chair Tom Kirchman documented the SOM's consideration of circumstances beyond the protestor's control which caused the SOM to accept the protest with a justified 11-minute delay.

The COA finds the SOM acted within their authority and made a thoughtful and reasoned decision based on the evidence. The penalty assessed was within their purview. However, they did not apply the appropriate penalty points under GCR 7.4.A. which states, "Penalties assessed by the SOM …accumulate points on the member's record according to the following schedule". A penalty of Loss of Finishing Position accrues 2 penalty points on the member's competition license.

DECISION

The Court of Appeals upholds the decision of the SOM with the addition of 2 penalty points on Mr. Gonzalez's competition license. Mr. Saito's appeal is well founded, and his appeal fee, less the amount retained by SCCA, will be returned.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Johannes Saito vs. SOM COA Ref. No. 26-07-SE
April 08, 2026

FACTS IN BRIEF

On March 8, 2026, following Race 2 for Group 6 at the Hoosier Racing Tire SCCA Super Tour at Michelin Raceway Road Atlanta, Jason Fichter, driver of Spec MX-5 (SMX) #7, filed a Protest against Nate Cicero, driver of SMX #83, alleging the use of a "non OE oil filter" in violation of General Competition Rules (GCR) 9.1.7.1.D.13.a.

The Stewards of the Meeting (SOM), George DeLong, Paul Gauzens, and Thomas Kirchman (Chair) met, heard witnesses, and reviewed the evidence. The SOM determined the oil filter in SMX #83 when examined and photographed in post-race impound was not an OE replacement filter. The SOM penalized Mr. Cicero with loss of position, moving him behind all compliant cars and assessed 0 points on his competition license.

Johannes Saito, entrant for SMX #83, appealed the decision of the SOM.

DATES OF THE COURT

The SCCA Court of Appeals (COA) Scott Bowman, Jack Kish, and Laurie Sheppard (Chair) met on April 2, 2026, to review, hear, and render a decision on the appeal.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Request to Appeal from Johannes Saito, submitted March 18, 2026.
2. Official Observers Report and related documents, received March 25, 2026.
3. Chair SOM's Response to Appeal, received March 27, 2026.
4. Race Director's Response to Appeal, received March 31, 2026.

FINDINGS

In his appeal, Mr. Saito asserted Mr. Fichter did not present the protest within the required 30-minute time frame following the end of the Group 6 race as required by GCR 8.3.1.F. (Cars in impound may be protested within 30 minutes after any session.) He further stated "the rules are the rules and should be applied equally to all competitors" while arguing the protest should be voided as it was filed after the deadline cited above.

The SOM combined the protests against Cars #16, #48, #57 and #83 as all protests were identical and considered all as one. After consulting Race Director Kathy Barnes,

the SOM accepted the protest as timely due to circumstances beyond the control of the protestor. The SOM interviewed Lincoln Larson, driver of #16, Gavin Vaughn, driver of #48, and Mr. Saito, entrant for #57 and #83. The SOM reviewed pertinent GCR technical specifications, the Technical Inspection Report for each car prepared by Class Compliance Chief Scott Schmidt, and examined photographs of each car's oil filter in place during post-race impound. The SOM concluded the oil filter on each of the four cars was not an OE engine oil filter.

The COA notes GCR 8.3.1.F. states in its preamble to the time limit table, "…the SOM may extend the time in cases where the protestor can show … they were unable to meet the deadline because of circumstances beyond their control." Testimony from Race Director Kathy Barnes described Mr. Fichter's attempt to file the protest before she was available to receive it due to her responsibility to review other on-track issues during the race. The documented receipt time of the protest by the Race Director is 3:00pm. SOM Chair Tom Kirchman documented the SOM's consideration of circumstances beyond the protestor's control which caused the SOM to accept the protest with a justified 11-minute delay.

The COA finds the SOM acted within their authority and made a thoughtful and reasoned decision based on the evidence. The penalty assessed was within their purview. However, they did not apply the appropriate penalty points under GCR 7.4.A. which states, "Penalties assessed by the SOM …accumulate points on the member's record according to the following schedule". A penalty of Loss of Finishing Position accrues 2 penalty points on the member's competition license.

DECISION

The Court of Appeals upholds the decision of the SOM with the addition of 2 penalty points on Mr. Cicero's competition license. Mr. Saito's appeal is well founded, and his appeal fee, less the amount retained by SCCA, will be returned.

Fastrack® news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

ROAD RACING COMPETITION COMMITTEE MINUTES | May 5, 2026

We appreciate the feedback and perspectives that our members provide, and we'd like to thank you for your outreach and being part of the process. Should you have any requests or feedback to share with the Road Racing Competition Committee or a class advisory committee, please visit https://crbscca.com/ to submit a letter.

The Road Racing Competition Committee met by teleconference on April 7, 2026. Participating were Dayle Frame, Chairman; David Arken, David Locke, Jim Goughary, Sam Henry, Tony Ave and Shelly Pritchett, secretary. Also participating were: Bob Crawford, BoD Chairman, David Brown and Mark Weber, BoD liaisons; Sydney Davis Yagel, Senior Manager of SCCA Road Racing, Scott Schmidt, Road Racing Technical Manager, Scott Dobler, Road Racing Series Manager. The following decisions were made:

Member Advisory

None.

No Action Required

FC

1. #40199 (Robert Wright) Mazda MZR Rules

The Road Racing Competition Committee appreciates the submission of the 2026 Formula Race Promotions (FRP) technical specifications for the USF2000 tube frame car with the Mazda MZR engine. The RRCC needs additional information to make a decision on the request to replace the 2018 FRP technical specifications for the MZR-powered USF2000 car. Please submit information with a new letter to crbscca.com about the specific parts on the USF2000-MZR car, in addition to those parts for which allowances have already been made in the GCR, that are either unavailable or difficult to find along with specific descriptions of the corresponding and noncompliant parts that competitors may be using as replacement alternatives to the original parts.

FF

1. #39993 (Anthony Stefanelli) FF 5-Year Strategy Submission

The Road Racing Competition Committee appreciates the submission of the FF Five-Year Strategy and the effort which the class's stakeholders put into developing the plan. The RRCC believes the plan coordinates well with the SCCA's strategic plan and objectives.

GCR

1. #40097 (Graham Loughead) Clarification of 9.3.11 Camera and Mountings

The statement "Helmet-mounted cameras do not satisfy the forward-facing camera rule" simply means competitors cannot claim a helmet-mounted camera (whether outside or inside the helmet) constitutes the forward-facing camera required by GCR section 9.3.11.A.

General

1. #40117 (David Fiorelli) SCCA surveys

The most recent Runoffs survey was used to assist the National Staff with planning the run group order for the Runoffs by determining who planned to run multiple classes. We will consider sharing some of the information from broader surveys when it seems beneficial to the community.

STU

1. #39950 (Kip VanSteenburg) Maintaining Class Integrity
SCCA is still in support of combining these two classes. We have requested data to be collected at Atlanta, VIR and beyond to support the BoP effort.

2. #39956 (Jeff Cripe) In Agreement with Letter 39950
Please see letter # 39950 in current Fastrack.

3. #39957 (Austin Cripe) I am In Agreement of What is Written Within Letter 39950
Please see letter # 39950 in current Fastrack.

4. #39960 (Johan Schwartz) Support for letter 39950
Please see letter # 39950 in current Fastrack.

5. #39963 (James Creighton) I Support this Letter 39950
Please see letter # 39950 in current Fastrack.

6. #39965 (John Weisberg) Continued Inequality Between Traditional STU Cars and GT3.
Please see letter # 39950 in current Fastrack.

7. #39967 (Edgar Smith) Class Integrity
Please see letter # 39950 in current Fastrack.

8. #39968 (Rylan Hazelton) STU & GT3 Parity
Please see letter # 39950 in current Fastrack.

9. #40011 (Chris Edens) GT3/STU Merge
Please see letter # 39950 in current Fastrack.

10. #40017 (John Weisberg) Wings GT3/STU
Please see letter # 40020 in current Fastrack.

11. #40194 (Bjorn Stange) Clarification on Minimum Weights
You are correct that the 4% is applied at the end, after all other adders and subtractors. Consolidating the 4% into the weight table is currently under consideration.

T3

1. #40016 (Simon Foweather) SpecE46 Change
In future BOP adjustments, we will favor slowing the leaders rather than speeding up slower cars.

<u>Not Recommended</u>

B-Spec

1. #39502 (Kent Carter) Data Requirements to Support a Change in Balance of Performance
The RRCC is currently developing a standardized method to collect and analyze BOP data for all classes. We don't feel that B-Spec needs to have a unique collection method, even for underrepresented and new models. As an entry-level class, putting the

burden on a driver to purchase a data system in order to justify their car's existence seems counter-culture to the class. The RRCC & Advisory Committee will strive to obtain data at Hoosier Super Tours and Majors events for emerging models, and we appreciate any additional assistance that drivers and teams can provide regarding developing cars.

C-Spec

1. #39987 (Kent Carter) Make C-spec a Runoffs Eligible Class to Save SCCA

Several good points have been brought up by the authors of letters 39987, 39989, and 40009. The RRCC and Advisory Committees are working together to better understand the future of C-Spec, and they plan to include the Road Racing Planning Committee in further discussions, including ones about C-Spec's Majors eligibility and ultimate inclusion in future SCCA National Championship Runoffs. It's good to hear feedback about the class, such as the tire struggles, so that issues can be addressed allowing for growth within the class. While these discussions happen, we encourage all C-Spec participants to consider attending Majors and Super Tour events running under T4.

FA

1. #40072 (Alexandre Lima) Dallara Formula 3 Classification Request.

The Road Racing Competition Committee does not recommend this change. The performance of the European F3 Championship Dallara is well outside the performance envelope of the platforms currently allowed in the FA class due to its 3.4-liter Mecachrome V6 engine.

GCR

1. #39918 (Kent Carter) Replace Appendix P

Appendix P has served SCCA well as a guideline supporting GCR section 6.11.1 Rules of the Road when reviewing on-track incidents, and the Road Racing Competition Committee does not recommend replacing it at this time.

General

1. #40087 (Walter Hilderman) Fuel Cell vs Factory Aluminum Tank for Radical SR3

All Sports Racing cars running with SCCA require a fuel cell with bladder and foam. Deviating from this requirement is not something the RRCC feels necessary at this time.

GT1

1. #39005 (Daniel Speer) GT1 LS Limited Prep Rules Package

The Road Racing Competition Committee does not believe that adding another engine spec to GT1 is in the best interest of the class. We will continue to monitor the recent "LS" addition for now.

EP

1. #40245 (John Baucom) Fiat 124 Spider EP 1995cc Increase Choke Size from 36mm to 40mm

This vehicle specification saw a weight decrease and a choke size increase in 2025, and the full impact of those changes may not yet be fully reflected or understood. At this point, it would be helpful to either gather additional on-track performance race data or provide further context and supporting information to clarify why the current specification is believed to be uncompetitive as it stands.

FP

1. #40129 (Preston Obremski) Induction Request

The requested allowance is not recommended as it is beyond class philosophy. The limited modifications allowed to OE Fuel Injection intake manifolds for Level 2 vehicles is a key component to balance of performance (BOP) calculations. The factory manifold is considered when determining vehicle weight and other BOP items.

SM

1. #40186 (Brian Richards) Stock Exhaust Manifold

SMAC does not believe this would be a good change for the class due to potential performance gains by wrapping the header and manifold. Currently there are legal ways to reduce the heat on the inside of the chassis with heat resistant materials or insulation. See GCR section 9.3.23.

2. #40208 (David Moreno) Support Letter # 39387

Please see April Fastback response to letter # 39387.

ST General

1. #40108 (John Weisberg) Inclusion of Letter Writer.

Due to time restraints, it would not be practical to include every letter writer to the monthly zoom calls and manage bringing them in and removing them for just the discussion of their letter.

T2

1. #40211 (Randall Smart) Polycarbonate Windows

The TAC does not feel this change is warranted at this time.

<u>Recommended Items</u>

The following subjects will be referred to the Board of Directors for approval. Address all comments, both for and against, to the Road Racing Competition Committee. It is the BoD's policy to withhold voting on a rules change until there has been input from the membership on the presented rules. Member input is suggested and encouraged. Please send your comments via the form at www.clubracingboard.com.

General

1. #40298 (Stephen Blethen) Runoffs eligibility criteria

Effective 6/1/2026 In GCR, Section3.7.4.A.1.a, add the following:

"*For 2026 Only: Due to cancelled U.S. Majors Tour races in both the Northeast and Southern Conferences, drivers whose Division of Record on May 1, 2026 was Northeast Division or Southwest Division may substitute one additional Regional-sanctioned weekend for a second Majors weekend participation. A driver from these Divisions is now eligible to run 1 Majors + 3 Regional weekends to qualify for the 2026 National Championship Runoffs.*"

SM

1. #40203 (Spec Mazda (SM/SMX) Committee) Exhaust Heat Shielding

Effective 6/1/2026, GCR Section 9.3.23., change as follows

"Insulation or heat-resistant material may be added to the interior *& exterior* (cockpit) surfaces of the firewall, floor, and transmission tunnel."

SMX5

1. #40192 (Spec Mazda (SM/SMX) Committee) Update Wheel Stud Language
Effective 6/1/2026, GCR Section 9.1.7.1.15.b, change as follows:
"Aftermarket (any) wheel studs and lug nuts are permitted.~~, provided that a minimum of two (2) threads protrude beyond the lug nut when the wheel is installed with a minimum of two (2) full threads showing.~~ Wheel studs may not be gun drilled."

T4

1. #40340 (Touring Committee) SPB in T4 v2
In T4 Spec Lines, Effective 12/31/2026 removed Porsche Spec Boxster in its entirety.

<u>Taken Care Of</u>

B-Spec

1. #39550 (Richard Hromin) Request Allowance to Remove Catalytic Converter
The committee discussed this topic intensely over the past months. Not only within the context of sunsetting the OBX header for the 07-10 Mini Cooper/Clubman, but also regarding the category as a whole.

We considered as many avenues as we could, which culminated in the decision to approve specific aftermarket replacement catalysts/exhaust manifolds for each platform. Our rationale for arriving at that decision was as follows:

1. It was the best avenue available to maintain our current BOP
2. It provided parts availability to replace OEM parts that are becoming unavailable
3. Specifying a specific brand and part number is a solution tech can enforce

As these vehicles age, availability of certain parts is going to become an issue. We are already experiencing this phenomenon with suspension kits, as several Bilstein B14 kits have become difficult or impossible to acquire.

This is also the case with OEM catalysts/exhaust manifolds. For example, the OEM catalyst for the 07-08 Fit is no longer available from Honda. Additionally, many of these OEM cats/manifolds are cost prohibitive to purchase. An OEM replacement manifold for a Sonic is over $2,000 plus a core charge. That does not fit the cost-controlled philosophy of B-Spec.

Requiring OEM manifolds made sense with B-Spec was a pro category, as many of these cars were brand new and still in production. However, this is no longer the case. Allowing an aftermarket replacement version of the OEM parts was a logical evolution.

The committee did consider allowing the removal of catalyst material from stock manifolds. However, this solution posed several challenges in terms of tech enforcement, maintaining current BOP, and differences in exhaust configurations within the category.

There are several catalyst configurations within the category. For example, the Yaris, 1st-generation Fit, and Versa all feature cast manifolds with a separate primary catalyst.

However, the Sonic, 2nd/3rd-genration Fit, Fiesta, Rio, Accent, Mazda and Mini all have a catalyst that is integrated into the exhaust manifold. The 2G/3G Fits specifically have a manifold that is a single runner design as the cylinder head features a single exhaust port.

Due to the variety of exhaust configurations in the category, there was not a one size fits all solution. In most cases, removing the catalyst material from the manifolds would have required cutting the unit itself open and then re-welding it back together. For a category that is largely based around bolt-on catalog parts, this solution did not fit class philosophy.

Allowing the removal of catalyst material would have also potentially resulted in a wide-scale BOP change. Which the committee was not in favor of. That said, we did make specific allowances for the Versa and Yaris to remove their catalysts as they are a separate unit from the manifold. These were two platforms that appeared to need BOP help. The 1st-generation Fit was already permitted this allowance last year.

Additionally, we have already made positive BOP adjustments to the Mini in anticipation of the expiration of the OBX header and will continue to do so if data points to additional changes being needed. Further changes will likely focus on additional weight reduction, as many of these cars are still racing with over 100# of ballast, but plate changes would also still be considered.

The expiration of the OBX header leaves the Mazda 2 as the sole platform with an approved aftermarket header in the category. Thankfully, that part is provided by a direct stakeholder in the series that can guarantee its availability. Which was ultimately not the case for the supplier of the OBX header than had been approved for the Mini.
Ultimately, our goal as a committee is to provide a ruleset that is fair and cost effective. While there is ultimately only so much control we have over OEM and aftermarket parts availability, we will continue to do our best to ensure that this does not become a limiting factor to the category's growth or BOP management.

2. #39741 (James Rogerson) Primary/Upstream Catalyst Removal
Please see response to letter #39550 in current Fastrack, Request Allowance to Remove Catalytic Converter.

3. #39754 (BRADLEY DAVIS) Deletion of KW Suspension Pieces Still In Use
The committee reinstated the use of the world challenge-era suspension kits for the Mini Cooper. Several of the old world challenge kits were deleted in an effort to streamline the spec lines and not send new participants on wild goose chases for parts that have not existed in over a decade. Allowing parts that are not easily findable is not conducive to growing the class and is a practice we are trying to move away from. However, we do not want to alienate current participants in the process of achieving that goal.

4. #39928 (Steve Introne) Committee Evaluation
The B-Spec Advisory Committee and the RRCC have evaluated resume submissions and added two new members to the BSAC in this Fastrack. Thank you for your submission as it will be kept on file for future committee positions.

5. #40114 (Jacob New) Mini Cooper BOP
The committee recently made a recommendation to reduce the minimum weight of Mini Coopers not equipped with the OBX header in an effort to improve their performance. See Road Racing Memo 26-01 B-Spec Mini Cooper Weight Adjustments with OEM Catalyst or Header.

HP
1. #40214 (Jason Stine) Support of Letter #40213
Please see response to letter #40213 in the current Fastrack.

2. #40216 (Benjamin Johnson) Support for letter #40213
Please see response to letter #40213 in the current Fastrack.

3. #40217 (Donovan Helfrich Sr) Support for letter 40213
Please see response to letter #40213 in the current Fastrack.

4. #40218 (Jerry Oleson) Support of letter 40213
Please see response to letter #40213 in the current Fastrack.

5. #40219 (Bill Okell) Letter #40213
Please see response to letter #40213 in the current Fastrack.

6. #40223 (Kerry Foote) In Reference to Letter #40213
Please see response to letter #40213 in the current Fastrack.

7. #40225 (Kendall Jones) Spridget 1275 Help
Please see response to letter #40213 in the current Fastrack.

8. #40226 (Lee Fleming) Supporting Letter 40213
Please see response to letter #40213 in the current Fastrack.

9. #40227 (Eric Vickerman) Support of letter 40213
Please see response to letter #40213 in the current Fastrack.

10. #40228 (Mike Savage) support for letter #40213
Please see response to letter #40213 in the current Fastrack.

11. #40229 (Klaus I. Bock) Support for letter #40213
Please see response to letter #40213 in the current Fastrack.

12. #40230 (Joe Carr) 1275 1 1/2
Please see response to letter #40213 in the current Fastrack.

13. #40232 (David Savage) In support of letter 40213
Please see response to letter #40213 in the current Fastrack.

14. #40233 (Michael MacQueen) I Am Writing in Support of Competition Equalization for Spridget
Please see response to letter #40213 in the current Fastrack.

15. #40235 (Brian Linn) Support for Letter #40213
Please see response to letter #40213 in the current Fastrack.

16. #40238 (Jack Schulz) Specification Change 40228
Please see response to letter #40213 in the current Fastrack.

T2-T4

1. #40189 (David Mead) Missing Shock Verbiage
Please see letter # 40176 in current Fastrack.

T3

1. #40105 (Touring Committee) Any help for T3 86 and BRZ
Please see letter # 40169 in current Fastrack.

2. #40170 (Devin Anderson) Power of GR86/BRZ in T3
Please see letter # 40169 in current Fastrack.

T4

1. #40026 (Luis Goncalves) T4 Suspension Rule Cleanup
Please see letter # 40176 in current Fastrack.

2. #40063 (Scotty B White) Mustang Tire Sizes
Please see letter # 40183 in current Fastrack.

What Do You Think

None.

Resumes

1. #39991 (Richard Hromin) BSAC Committee
The BSAC accepts Richard Hromin's resume to join the committee.

2. #40195 (Thomas Pendergrass) BSAC resume
The BSAC accepts Thomas Pendergrass' resume to join the committee.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

DATE: May 20, 2026
NUMBER: TB 26-06
FROM: Road Racing Competition Committee
TO: Competitors, Stewards, and Scrutineers
SUBJECT: Errors and Omissions, Competition Adjustments, Clarifications, and Classifications

All changes are effective 6/1/2026 unless otherwise noted. If any day of a race event falls on the first day of the month, the previous month's rules will be in effect for that event only. The new rules will become effective at the conclusion of the race event, unless otherwise noted.

American Sedan
AS
1. #40167 (American Sedan Committee) Clarification for LM7 Holley Carburetor
In GCR, Section 9.1.6., ENGINE GM LM7 5.3L build sheet, change Notes as follows:
"Must use the full prep ~~4776 holly carburetor and spacer gasket~~ *Holley carburetor as described in 9.1.6.D.c.1.*"

B-Spec/C-Spec
1. #40034 (Gary D'Abate) ECU Location in Mazda2
In B-Spec Spec Lines, Mazda2 (10-14), add to Notes the following:
"*ECU housing may be trimmed and relocated within the engine bay.*"

2. #40122 (Kyle Keenan) Allow Cars With Combined Brake/Clutch Reservoir to Separate.
In B-Spec Spec Lines, Hyundai Accent Hatchback (12-17), Hyundai Accent Sedan (12-17), Kia Rio Hatchback (12-15), and Kia Rio Sedan (12-17), add to Notes the following:
"*Wilwood 260-10500 reservoir kit permitted.*"

Electric Vehicle
None.

Formula/Sports Racing
FA
1. #40175 (DEREK KULACH) Motor Classification
In FA Table 1, add the following:

Table 1

FA Spec Line	Engine Series	Max. Displ. (cc)	Max. Valves/ Cyl.	Notes	Req'd Restrictor	Min. Weight (lbs)
K.	*Mazda 13B Rotary*	*n/a*	*n/a*	*Bridgeport or peripheral port permitted. Engine may use one 48mm or 50mm dual-throat carburetor with 41.5mm venturi or fuel injection with 36mm SIR.*	*See notes*	*1300*

GCR
1. #40198 (Mike Smith) Response to letter #39921
In Size of Numbers and Class Identifications, GCR section 9.3.29.B, change as follows:
"The minimum height of all numbers is 8 inches high with a minimum 1.5-inch stroke width on a single-color contrasting background. All numbers must be the same color and style. Metallic (reflective) identification characters and backgrounds are prohibited. The minimum height of all class identifications is 4 inches high with a minimum 1/2-inch stroke width on a single-color contrasting background. *The Chief of Timing and Scoring and the Race Director/Chief Steward will determine legibility of markings.*"

General
None.

Grand Touring
GT1
1. #40147 (Mike McAleenan) Request for Huracan GT3 Evo Weight Reduction to 2950lbs
In GT1-ST Spec Lines, Lamborghini Huracan GT3 (2019-), change weight as follows:
"~~3000~~*2950*"

Improved Touring
None.

Legends Car
None.

Planning
None.

Production
EP
1. #40138 (John Wilson) Honda S2000 Hardtop
In EP Spec Lines, Honda S2000, add to Chassis Notes the following:
"*Mugen hardtop (P/N 0000-04-2312), or an aftermarket equivalent, is permitted.*"

HP
1. #40213 (Michael MILLER) Austin Healy Sprite/ MG Midget 1275 Induction Change Request
In HP Spec Lines, Austin-Healey Sprite Mk I, II, III, IV MG Midget Mk I, II, III, IV & 1500, change Drivetrain Notes as follows:
"(2) 1.25” SU w/ no modifications
(2) 1.5” SU w/ no modifications (on alternate manifold)
Valves: (I) 33.0/(1.30) (E) 29.5/(1.16)
Comp. ratio 12.0:1, Valve lift .450”
Trans. Speeds: 4

Drivetrain Level 2 preparation only.
Listed spec line weight does not change with alternate or stock transmission.

Alternate intake manifold, with narrowed balance tube to fit 1275cc head, permitted with use of 1.5" SU carbs (original P/N's 12H708, 12H1398, 12H2568)."

In HP Spec Lines, Austin-Healey Sprite Mk I, II, III, IV MG Midget (ALL), change Drivetrain Notes as follows:
"(2) 1.25" SU w/ no modifications
(2) 1.5" SU w/ no modifications (on alternate manifold)
Valves: (I) 33.0/(1.30) (E) 29.5/(1.16)
Comp. ratio 12.0:1, Valve lift .450"
Trans. Speeds: 4

Alternate intake manifold, with narrowed balance tube to fit 1275cc head, permitted with use of 1.5" SU carbs (original P/N's 12H708, 12H1398, 12H2568)."

Spec Mazda (SM/SMX)
None.

Super Production
None.

Super Touring
ST General
1. #40224 (David Wessel) Calculating Weight
In GCR, Section 9.1.4.1.H.6., change as follows:
"The minimum weight is determined by the installed engine displacement*, TIR or table spec line*. It is to be used as the base weight for any ~~chassis~~*weight* related adjustments. ~~Chassis related~~*All positive* adjustment*s* that are percentage based are performed by adding *the total of all* specified percent*ages* first and subtracting *the total of all negative* specified percentage*s* second~~ if necessary~~. Final step is addition or subtraction of specified weight in pounds."

In GCR, Section 9.1.4.2.H.4., change as follows:
"The minimum weight is determined by the installed engine displacement *or table spec line*. It is to be used as the base weight for any ~~chassis~~*weight* related adjustments. ~~Chassis related~~*All positive* adjustment*s* that are percentage based are performed by adding *the total of all* specified percent*ages* first and subtracting *the total of all negative* specified percentage*s* second~~ if necessary~~. Final step is addition or subtraction of specified weight in pounds."

STU
1. #40202 (Bjorn Stange) Request to allow BMW M50B20TU engine in STU
In STU Spec Lines, Table B: Alternate Vehicle and Engine Requirements, classify the following:
Make: "*BMW M50B20TU*"
Maximum Displacement: "*1991*"
Minimum Weight: "*Chart*"
Notes: "*Must meet all STU engine regulations.*"

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

Touring

T1

1. #40177 (James Candelaria) Trunk Lid Wording

In GCR, Section 9.1.9.1.A.1., change as follows:

"Hoods, trunk lids, *rear hatch* and front fenders may be replaced with panels of any type material, provided that the panel maintains the OEM profiles. For the sole purpose of tire fitment, wheel arches may be flared up to 3" and must maintain the OEM profile. The hood may have heat exhaust vents installed in it. Hood inlets (scoops) are not allowed. The vents shall not expose the mechanical components of the car when looking down from above. The permitted transmission and differential coolers may vent through rear license plate frame. There shall be a screen, painted the same color as the surrounding bodywork, covering the vent opening. Any OEM non-functional, decorative vents/ ducts may be made to be functional provided the exterior body appearance is not modified."

In GCR, Section 9.1.9.1.B.2.a., change as follows:

"The wing shall be mounted to the trunk/deck lid*, rear hatch* or bumper frame with 2 mounting brackets. Each mounting bracket shall attach to the wing at a point that is at least 2.0 inches inboard of endplates. The wing, and the portion of the mounting brackets located externally to the trunk/ deck lid, may only be reinforced by a diagonal strut having no aerodynamic effect, and/or by affixing the external parts of the brackets to internal parts of the brackets within the trunk/cargo area. The internal parts of the brackets may protrude through the trunk/deck lid to allow the two parts of each bracket to be fastened together."

T2

1. #40005 (Marshall Mast) 2015+ Ecoboost Mustang

In T2 Spec Lines, Ford Mustang Ecoboost 2.3 (2015-), change as follows:

Years: "(2015-*2023*)"

Restrictor: "~~50mm TIR~~"

Max Tire: "~~295~~*315*"

Weight: "~~3400~~*3300*"

2. #40174 (William Bolt) C6 Corvette - All Body Trims Requested

In T2 Spec Lines, Chevrolet Corvette C6 Coupe / Grand Sport (05-13), add to Notes the following:

"*Splitter and spoiler matching the OEM C6 ZR1 and Z06 carbon dimensions permitted.*"

3. #40209 (Derrick Ambrose) T2-TCR Table Mazda 3

In **T2-TCR Spec Lines,** Mazda 3TC, change Notes as follows:

"DOT approved tires with maximum section width of 275. ~~T2-TCR splitter and valance must comply with 9.1.4.D.3.f. T2-TCR chassis ride height must comply with 9.1.4.1.A.1 Must conform to "2024 TCR Technical Regulations" prep~~ *Must conform to "TC Technical Regulations" prepared by TCAmerica.*"

T3

1. #40036 (Marshall Mast) 2015+ Mustang Ecoboost Performance
In T3 Spec Lines, Ford Mustang EcoBoost (2015-), change Notes as follows:
"Rear spring relocated to shock allowed. 800lbs springs (F/R) allowed. EcoBoost Performance Package allowed in part or complete. Optional: 6 speed automatic transmission (with paddle shifters). Speed Factory Intercooler, part # SF-55-002 permitted. BMR rear upper control arm camber links part #UTCA064 permitted. ~~Non-EcoBoost Performance Pack base model 320mm front brakes, 2-piston front calipers allowed (-50lbs).~~ Ford Motorsports 6-piston M2300V 380mm brake kit allowed ~~with +100lb penalty~~, Sway bars allowed up to ~~35mm~~*38mm* (F) 25mm (R)."

2. #40149 (Daniel Brabec) Review Spec Lines for Camaro V-6
In T3 Spec Lines, delete Chevrolet Camaro V6 1LE (2016-) in its entirety.

In T3 Spec Lines, Chevrolet Camaro V6 (2016-), change as follows:
Year: "(2016-*2024*)"
Restrictor required: "~~50mm restrictor~~"
Max wheel size: "~~18~~*20* x 10"
Weight: "~~3500~~*3350*"
Notes: "*1LE options permitted. Cold air intake permitted. 800lb springs (F/R) permitted. Sway bars 38mm(F), 28mm(R) permitted. **This car is not eligible for Runoffs competition in 2026***"

3. #40169 (Devin Anderson) Power of GR86/BRZ in T3
In T3 Spec Lines, Subaru BRZ (2022+), change as follows:
Weight: "~~2975~~*2750*"
Notes: "Any spring up to 1000 F/R permitted. Front strut tower brace permitted. SPC or SPL rear lower control arms permitted. Cold air intake allowed. ~~Header Permitted Subaru brake parts 26292CA070 & 26292CA060 allowed.~~ Sway bars permitted 25m (f) 22mm (r) Max. OEM Trunk Spoiler permitted- E7210CC000."

In T3 Spec Lines, Toyota GR86 (2022-), change Notes as follows:
"Any spring up to 750 F/R permitted. Front strut tower brace permitted. SPC rear lower control arms permitted. Cold air intake allowed. *Header Permitted* ~~Toyota brake parts SU003-07197 & SU003-07198 allowed with 100 lb penalty.~~ Sway bars permitted 25m (f) max, 22mm (r) Max. OEM Trunk Spoiler permitted E7210CC000."

4. #40190 (David Mead) Allow T3 Ford Mustang 4.6 to Use the Coyote MT-82 6 speed.
In T3 Spec Lines, Ford Mustang Coupe GT & Shelby GT 4.6L & Cal. Special (05-10), change Gear Ratios as follows:
"*T3650-* 3.38, 2.00, 1.32, 1.00, 0.675 *MT-82- .66, 2.43, 1.69, 1.32, 1.0, 0.65*"

5. #40196 (Clayton Cavell) Porsche 986S Boxster S (2000-2004) Minimum Weight
In T3 Spec Lines, Porsche Boxster/ Boxster S (00-04), change Min. Weight as follows:
"3.2L: ~~3250~~*3050*
2.7l: ~~3000~~*2800*"

T4

1. #39973 (Touring Committee) SPB In T4
In T4 Spec Lines, Porsche Spec Boxster, add to Notes:
"*Not eligible for Runoffs in T4.*"

2. #40106 (Derrick Ambrose) 02-06 Mini Cooper S
in T4 Spec Lines, Mini Cooper S R53 (02-06), change Min. Weight as follows:
"~~2700~~*2650*"

3. #40107 (Derrick Ambrose) 02-06 Mini Cooper S Fuel
In T4 Spec Lines, Mini Cooper S R53 (02-06), please add to Notes the following:
"Bosch 0280158117 Injectors permitted."

4. #40176 (Touring Committee) Shock error
In GCR, Section 4.1.4.2.D.5.b.2., change as follows:
"The make of shock absorber may be changed. Their number, perch location(s), system of attachment, and attachment points shall not be altered. Their type (tube vs. lever, etc.) shall not be altered. The interchange of gas and hydraulic shock absorbers is permitted.

T2-T3: Shocks must be installed in the original mounting locations unless noted in the spec line. Remote reservoirs and multiple adjusters are permitted. Threaded shock bodies or adjusters may be used. Shocks can serve no purpose other than to damp motion.

T4 only: Any non-adjustable or single *adjustable (knob or screw)* shock absorber is allowed. Shocks must be installed in the original mounting locations. Remote reservoirs are not permitted. Threaded shock bodies or adjusters may be used. Shocks can serve no purpose other than to damp motion."

5. #40183 (Matthew Miller) Max Tire Sizes
In T4 Spec Lines, Ford Mustang V6 (05-10), change Max. Tire Size as follows:
"~~255~~*275*"

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Jordan Fureman vs. SOM COA Ref. No. 26-08-NE
May 11, 2026

FACTS IN BRIEF

On March 29, 2026, following Race 2 for Group 1 at the March MARRS Regional held on the Summit Point Circuit at Summit Point Motorsports Park, Arif Kazim, driver of Showroom Spec Miata (SSM) #98, protested Jordan Fureman, driver of SSM #8, for violation of General Competition Rules (GCR) 6.11.1. (On Course Driver Conduct). Mr. Kazim cited contact by Car #8 forcing Car #98 off course onto the grass and into a tire barrier, leading to Car #98 retiring from the race.

The Stewards of the Meeting (SOM), Marshall Lytle, Larry Oliver, Steve Pence, Lin Toland, and Terry Hanushek (Chair) met, heard witnesses, and reviewed the evidence. The SOM determined Mr. Fureman violated GCR 6.11.1.A. (Avoidable Contact) and 6.11.3.B. (Reentry from Off Course) by moving directly across the course from right to left resulting in side-to-side contact with Car #98 and forcing Car #98 off course. The SOM penalized Mr. Fureman with loss of position to finish behind Car #98, which incurred two penalty points on his competition license.

Mr. Fureman appealed the decision of the SOM.

DATES OF THE COURT

The SCCA Court of Appeals (COA) Costa Dunias, Rick Mitchell, and Lee Hill (Chair) met on April 23, 2026, to review, hear, and render a decision on the appeal.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Request to Appeal from Jordan Fureman, submitted March 31, 2026.
2. Official Observers Report and related documents, received April 15, 2026.
3. SOM Video from Car #8, Car #98, and Sunday Live Stream broadcast, received April 15, 2026.
4. SOM Photo of Car #8 showing evidence of left side contact, received April 15, 2026.
5. Appellant videos from Car #8, Car #98, following Car #132 (Christopher Kelley), and following Car #63 (John Hotz), received April 15, 2026.
6. Additional video from Mr. Fureman showing a different transit of the Turn 3-4 area, received April 15, 2026.
7. Response from SOM member Steve Pence, received April 28, 2026.

FINDINGS

In his appeal, Mr. Fureman asserted he was not responsible for the contact between his Car #8 and Car #98 because Car #98 was not sufficiently alongside to be visible prior to the contact, since the right front of Car #98 contacted the left rear tire of Car #8. The contact occurred at the turn in point for Turn 4. Mr. Fureman also stated that he made a proper effort to rejoin the track safely after being pushed off by Car #132.

The SOM interviewed both drivers, collected their witness statements, reviewed a witness statement from a spectator, and reviewed the in-car video from both cars, as well as the Live Stream broadcast video. The SOM determined that Mr. Fureman drifted off course driver right at the exit of Turn 3 (a 90-degree left-hand corner) and upon reentry, drove immediately to the left to set up for right-hand Turn 4 in violation of GCR 6.11.3.B. (Unsafe reentry). As he moved left, Mr. Fureman (Car #8) had side-to-side contact with Car #98 at the left edge of the track in violation of 6.11.1.A. (Avoidable Contact).

The COA reviewed all videos submitted, as well as the documentation provided by the SOM, including witness statements and all other evidence. Video from all sources shows Car #8 (Mr. Fureman), Car #98 (Mr. Kazim), and Car #132 (Mr. Kelley) were in line behind the overall leader for a single file restart. On the restart, Car #132 initiated an outside pass in right-hand turn 1, passing Car #98 and getting fully alongside Car #8. The three cars approached left-hand turn 3 in this same formation with Car #132 to the left of Car #8 and Car #98 following closely behind Car #8. In turn 3, Car #132 tracked out to the normal track boundary forcing Car #8 off course to avoid contact. Car #98 made a later apex than Cars #132 and #8, exited the corner at driver left with a speed advantage on Car #132 and moved alongside. Car #8 retained control of his car and maintained race direction and speed while returning to the course and moving ahead of Car #132. Once he cleared Car #132, Mr. Fureman moved left to set up for Turn 4. As he crossed in front of Car #132, his left rear tire contacted the right front of Car #98 which was overtaking Car #132 on the left edge of the track.

Videos from Car #132 (Mr.Kelley) and Car #63 (Mr.Hotz) provided by the appellant show Car #8 got a better exit from turn 3, even with two wheels in the gravel, and returned to the track fully in control and moving slightly faster than Car #132. Those videos also show Car #132 moved to the left leaving Mr. Fureman plenty of room to reenter safely and he did so. Video from Car #8 clearly shows Mr. Fureman checking his left side mirror repeatedly as he reentered and moved towards the left.

Car #132's video shows Car #98 (Mr. Kazim) visible alongside Car #132 on the left and moving faster than Car #132. It is clear from the videos of both trailing cars that as Mr. Fureman crossed in front of Car #132, he had limited time to see Car #98 in his mirror and very little time to realize that Car #98 was moving faster than Car #8. It is also clear

Mr. Kazim in Car #98 had time to anticipate the impending contact and could have taken steps to avoid it. From trailing car videos, it appears the nose of Car #98 moved into the contact point from behind just as the rear of Car #8 moved into the contact point from the right.

The COA finds Mr. Fureman's reentry after being forced wide at turn 3 was executed with due care and was accomplished safely. The COA also finds both drivers bore some responsibility for avoiding the contact. The COA disagrees Mr. Fureman is solely responsible for this incident and reduces his penalty to a Reprimand with the requisite one point on his competition license.

DECISION
The Court of Appeals upholds the decision of the SOM but modifies the penalty to a Reprimand and 1 point on Mr. Fureman's competition license. Mr. Fureman's original finishing position is to be restored and the associated 2 points on his license are to be removed. Mr. Fureman's appeal is well founded, and his appeal fee, less the amount retained by SCCA, will be returned.

Fastrack news
official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Jason Fichter vs. SOM COA Ref. No. 26-09-SE
May 20, 2026

FACTS IN BRIEF

On Saturday, April 5, 2026, following Race 1 for Group 6 at the Hoosier Racing Tire SCCA Super Tour Spring Sprints at Virginia International Raceway, Race Director Kathy Barnes filed a Request for Action (RFA) seeking investigation of contact between Spec MX-5 (SMX) #13, driven by Emy Kissick, and SMX #7, driven by Jason Fichter, at Turn 13 during the race.

The Stewards of the Meeting (SOM) Steve Pence and Russ Gardner (Chair) met, heard witnesses, reviewed video, and concluded Mr. Fichter violated General Competition Rules (GCR) 6.11.1.A. (Avoidable Contact) by contacting Car #13 at Turn 13-14 (Roller Coaster). The SOM penalized Mr. Fichter with loss of two positions in class which incurred two penalty points on his competition license.

Mr. Fichter appealed the SOM decision.

DATES OF THE COURT

The Court of Appeals (COA) Scott Bowman, Lee Hill, and Costa Dunias (Chairman) met on May 7, 2026, to review, hear, and render a decision.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Request to appeal from Mr. Fichter, submitted on April 8, 2026.
2. Notification of Appeal, received April 28, 2026.
3. Official Observer's Report, in-car videos, and related documents, received April 28, 2026.

FINDINGS

In his Appeal, Mr. Fichter asserted the penalty of loss of two positions plus 2 points against his license seemed excessive for the alleged infraction. He acknowledged he "tapped the rear of the 13 car" and "neither of our cars got upset, loose etc." He argued that "had the #13 braked at the normal braking point like the rest of the field does it would not have been an issue." He further asserted that SMX racers touch and push each other all the time based upon their being a spec class and "nearly all of these are NOT malicious".

The SOM based their decision on the in-car videos and witness statements from both drivers. Mr. Gardner explained it is undisputed that SMX #7 contacted SMX #13 while SMX #13 was completing a pass on a third car. The impact to Car #13's left quarter caused it to become unsettled, permitting the third car to regain position.

The COA reviewed the available videos from SMX #13 and SMX #7 which showed Car #13 was passing a car (SMX #86) on its right approaching Turns 13-14, a relatively high-speed portion of the track, and had reached marker 2 fully ahead of Car #86. As Car #13 approached marker 1, Car #7 hit Car #13 in the left rear quarter, unsettling Car #13 enough to cause Ms. Kissick to apply brakes to regain control of the car. This action allowed Car #86 to regain position. There was no other change in position.

The COA finds Mr. Fichter was solely responsible for contact with Car #7 which resulted in a change in position between Cars #86 and #7. The SOM properly heard the RFA, including all evidence and witness testimony. Mr. Fichter provided no new evidence in support of his appeal. The COA finds insufficient grounds to overturn the SOM's decision. The COA finds the SOM made a thoughtful and reasoned decision based on the testimony and video evidence available and applied a measured penalty which was within their purview.

DECISION
The COA upholds the SOM decision in its entirety. Mr. Fichter's appeal is not well founded, and his entire appeal fee is retained by SCCA.

Fastrack news official SCCA member notification
EFFECTIVE FIRST DAY OF THE MONTH UNLESS OTHERWISE NOTED

COURT OF APPEALS

JUDGEMENT OF THE COURT OF APPEALS
Mike Molter vs. SOM COA Ref. No. 26-10-CN
May 20, 2026

FACTS IN BRIEF

On April 19, 2026, following Qualifying for Group 6 at the CENDIV Drivers School and Double Regional held at Blackhawk Farms, Assistant Chief Steward Joseph Helser issued a Request for Action (RFA) to investigate reported nose-to-tail contact in Turn 1 involving Super Touring Under (STU) #186, driven by David Wessel, Spec Miata (SM) #99, driven by Michael Gardner, and SM #97, driven by Mike Molter.

The Stewards of the Meeting (SOM), Bev Heilicher, Jim Marinangel, and Karen Crider (Chair) met, heard witnesses, and reviewed the evidence. The SOM determined Mr. Molter in Car #97 violated GCR 6.11.1.A. (Avoidable Contact), 6.11.1.B. (Racing Room), and 6.11.1.D. (Decision to Pass) due to contact with Car #99 on the approach to Turn 7. The SOM penalized Mr. Molter with a reprimand, which incurred one penalty point on his competition license.

Mr. Molter appealed the decision of the SOM.

DATES OF THE COURT

The SCCA Court of Appeals (COA) Jack Kish, Laurie Sheppard, and Scott Bowman (Chair) met on May 7, 2026, to review, hear, and render a decision on the appeal.

DOCUMENTS AND OTHER EVIDENCE RECEIVED AND REVIEWED

1. Request to Appeal from Mike Molter, submitted April 27, 2026.
2. Official Observers Report and related documents, received April 30, 2026.
3. SOM Video from Car #99 and Car #186, received April 30, 2026.
4. SOM Photo of Car #97, received April 30, 2026.
5. Appellant documentation and attachments, received April 30, 2026.

FINDINGS

In his appeal, Mr. Molter asserted that he was not responsible for the contact between his Car #97 and Car #99. He argued Car #99 was not alongside prior to the turn and tracked wide hitting his right side. Mr. Molter provided his personal analysis of the contact in Turn 7, the layout of the track, weather conditions during the session, and general behavior of the group during the event.

The SOM interviewed the three drivers, collected their witness statements, reviewed witness statements from two corner marshals, and reviewed the in-car video from Car #186 and Car #99. No video was available from Car #97 which was the subject of a separate CSA. The SOM determined that prior to the contact in Turn 1, there were at least two contacts between Car #99 and Car #97 in Turn 6 through Turn 7. During the second contact (after Turn 6a), Mr. Molter did not alter his racing line while Car #99 was fully beside, violating GCR 6.11.1.A. (Avoidable Contact), 6.11.1.B. (Racing Room), and 6.11.1.D. (Decision to Pass).

The COA reviewed all videos submitted, the documentation provided by the SOM (witness statements, results, call log), and the material provided by Mr. Molter in his appeal. The videos show Car #99 initiated a pass attempt approaching Turn 6a just as Car #97 turned toward the apex. Car #99 locked his brakes and quickly came up alongside Car #97. The COA could not confirm if there was contact, but if not, it was very close. Car #97 appeared to react with a move to the left as the two cars exited the turn.

From this point until the braking zone for right-hand Turn 7, Car #97 (left) and Car #99 (right) were side-by-side, clearly visible to each other. Car #97 turned right toward the apex contacting Car #99, who was braking heavily and was at the extreme right side of the track. Both cars slowed and exited onto the front straight, with Car #97 right behind Car #99 as they headed to start/finish. Car #97 was extremely close to the tail of Car #99 as seen in that car's rearview mirror.

Car #186, a much faster STU car, passed both SM cars just after start/finish, moved to the left, and applied the brakes. It is clear that Car #99 hit the rear of Car #186. However, it is unclear if Car #97 hit Car #99 before this. Car #186 was going into the turn much faster and may have braked sooner than the slower SM cars, which could have caused the impact as well. Car #99 spun off drivers left, hit a berm, and was able to continue. Car #186 did not spin but sustained damage to the rear bumper cover.

The COA finds Mr. Molter did not provide racing room to Car #99 in Turn 7 going onto the front straight and caused avoidable contact. The SOM made a thoughtful and reasoned decision based on the testimony and video evidence available and applied a measured penalty which was within their purview.

DECISION

The Court of Appeals upholds the decision of the SOM in its entirety. Mr. Molter's appeal is well founded, and his appeal fee, less the amount retained by SCCA, will be returned.